



CMR3S-01
 CMR3S-02
 CMR3S-04
 CMR3S-06

**SURFACE MOUNT SUPER FAST RECOVERY
 SILICON RECTIFIER
 3.0 AMP, 100 THRU 600 VOLTS**



SMC CASE

Central™ Semiconductor Corp.

FEATURES:

- SUPER FAST RECOVERY (35ns MAX)
- HIGH RELIABILITY
- GLASS PASSIVATED CHIP
- SPECIAL SELECTIONS AVAILABLE
- SUPERIOR LOT TO LOT CONSISTENCY
- “C” BEND CONSTRUCTION PROVIDES STRAIN RELIEF, WHEN MOUNTED ON PC BOARD

DESCRIPTION:

The CENTRAL SEMICONDUCTOR 3.0 Amp Surface Mount Silicon Super Fast Recovery Rectifier is a high quality, well constructed, highly reliable component designed for use in all types of commercial, industrial, entertainment, computer, and automotive applications. To order devices on 16mm Tape and Reel (3000/13” Reel), add TR13 suffix to part number.

MARKING CODE: SEE MARKING CODE TABLE ON FOLLOWING PAGE

MAXIMUM RATINGS: (T_A=25°C unless otherwise noted)

	SYMBOL	CMR3S-01	CMR3S-02	CMR3S-04	CMR3S-06	UNITS
Peak Repetitive Reverse Voltage	V _{RRM}	100	200	400	600	V
DC Blocking Voltage	V _R	100	200	400	600	V
RMS Reverse Voltage	V _{R(RMS)}	70	140	280	420	V
Average Forward Current(T _L =75°C)	I _O			3.0		A
Peak Forward Surge Current (8.3ms)	I _{FSM}			100		A
Operating and Storage						
Junction Temperature	T _J ,T _{stg}			-65 to +150		°C
Thermal Resistance	θ _{JL}			16		°C/W


ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	TYP	MAX	UNITS
I _R	V _R =Rated V _{RRM}		5.0	μA
I _R	V _R =Rated V _{RRM} , T _A =100°C		200	μA
V _F	I _F =3.0A (CMR3S-01, CMR3S-02)		0.95	V
V _F	I _F =3.0A (CMR3S-04)		1.25	V
V _F	I _F =3.0A (CMR3S-06)		1.70	V
t _{rr}	I _F =500mA, I _R =1.0A, I _{rr} =250mA		35	nS
C _j	V _R =4.0V, f=1.0MHz	45		pF

R0 (5-October 2006)

**SURFACE MOUNT SUPER FAST RECOVERY
SILICON RECTIFIER
3.0 AMP, 100 THRU 600 VOLTS**

SMC CASE - MECHANICAL OUTLINE



MARKING CODES:

DEVICE	MARKING CODE
CMR3S-01	CS301
CMR3S-02	CS302
CMR3S-04	CS304
CMR3S-06	CS306

SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.030	0.060	0.76	1.52
B	0.004	0.008	0.10	0.20
C	0.305	0.320	7.75	8.13
D	0.006	0.012	0.15	0.31
E	0.079	0.103	2.00	2.62
F	0.260	0.280	6.60	7.11
G	0.108	0.124	2.75	3.15
H	0.220	0.245	5.59	6.22

SMC (REV: R1)