CZSH5-40C

SURFACE MOUNT
DUAL, COMMON CATHODE SILICON
SCHOTTKY POWER RECTIFIER
5 AMP, 40 VOLTS



www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CZSH5-40C is manufactured with two 5 Amp Schottky rectifiers assembled in a common cathode configuration and packaged in a SOT-223 case. This device has been designed for use in all types of commercial, industrial, entertainment, computer and automotive applications which require a high current device.

MARKING: FULL PART NUMBER



SOT-223 CASE

MAXIMUM RATINGS PER DIODE: (TA=25°C unless otherwise noted)

	SYMBOL		UNITS
Peak Repetitive Reverse Voltage	V_{RRM}	40	V
DC Blocking Voltage	V_{R}	40	V
RMS Reverse Voltage	V _{R(RMS)}	28	V
Average Forward Current (T _A =75°C)	Ìο	5	Α
Peak Forward Surge Current, tp=8.3ms	I _{FSM}	125	Α
Operating and Storage Junction Temperature	T_{J} T_{sta}	-65 to +150	°C

ELECTRICAL CHARACTERISTICS PER DIODE: (TA=25°C unless otherwise noted)


SYMBOL	TEST CONDITIONS	MAX	UNITS
I_{R}	V _R =40V	3.0	mA
I_{R}	V _R =40V, T _A =100°C	20	mA
V_{F}	I _F =5.0A	0.55	V


CZSH5-40C

SURFACE MOUNT DUAL, COMMON CATHODE SILICON SCHOTTKY POWER RECTIFIER 5 AMP, 40 VOLTS



SOT-223 CASE - MECHANICAL OUTLINE






DIMENSIONS						
	INCHES		MILLIMETERS			
SYMBOL	MIN	MAX	MIN	MAX		
Α	0°	10°	0°	10°		
В	0.059	0.071	1.50	1.80		
С	0.018	-	0.45			
D	0.000	0.004	0.00	0.10		
Е	15°		15°			
F	0.009	0.014	0.23	0.35		
G	0.248	0.264	6.30	6.70		
Н	0.114	0.122	2.90	3.10		
	0.130	0.146	3.30	3.70		
J	0.264	0.287	6.70	7.30		
K	0.024	0.033	0.60	0.85		
L	0.091		2.30			
М	0.181		4.60			

SOT-223 (REV: R3)

PIN CONFIGURATION



LEAD CODE:

- 1) Anode D1
- 2) Cathode D1, D2
- 3) Anode D2
- 4) Cathode D1, D2

Pin 2 and Pin 4 are common.

MARKING:

FULL PART NUMBER