

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

MPS404A

PNP SILICON
CHOPPER TRANSISTOR

JEDEC TO-92 CASE

DESCRIPTION

The CENTRAL SEMICONDUCTOR MPS404A type is an PNP silicon transistor manufactured by the epitaxial planar process, epoxy molded in a TO-92 package, designed for chopper applications.

MAXIMUM RATINGS ($T_A=25^\circ\text{C}$)


	<u>SYMBOL</u>		<u>UNITS</u>
Collector-Base Voltage	V_{CB0}	40	V
Collector-Emitter Voltage	V_{CEO}	35	V
Emitter-Base Voltage	V_{EBO}	25	V
Collector Current	I_C	150	mA
Power Dissipation	P_D	625	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	$^\circ\text{C}$
Thermal Resistance	θ_{JA}	200	$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

<u>SYMBOL</u>	<u>TEST CONDITIONS</u>	<u>MIN</u>	<u>TYP</u>	<u>MAX</u>	<u>UNITS</u>
I_{CB0}	$V_{CB}=10\text{V}$			100	nA
I_{EBO}	$V_{EB}=10\text{V}$			100	nA
BV_{CB0}	$I_C=10\mu\text{A}$	40			V
BV_{CEO}	$I_C=10\text{mA}$	35			V
BV_{EBO}	$I_E=10\mu\text{A}$	25			V
$V_{CE(SAT)}$	$I_C=12\text{mA}, I_B=400\mu\text{A}$			0.15	V
$V_{CE(SAT)}$	$I_C=24\text{mA}, I_B=1.0\text{mA}$			0.20	V
$V_{BE(SAT)}$	$I_C=12\text{mA}, I_B=400\mu\text{A}$			0.85	V
$V_{BE(SAT)}$	$I_C=24\text{mA}, I_B=1.0\text{mA}$			1.00	V
h_{FE}	$V_{CE}=0.15\text{V}, I_C=12\text{mA}$	100		400	
C_{ob}	$V_{CB}=6.0\text{V}, I_E=0, f=1.0\text{MHz}$		40		pF
t_d	$V_{CC}=10\text{V}, I_C=10\text{mA}, I_{B1}=1.0\text{mA}$		150		ns
t_r	$V_{CC}=10\text{V}, I_C=10\text{mA}, I_{B1}=1.0\text{mA}$		400		ns
t_s	$V_{CC}=10\text{V}, I_C=10\text{mA}, I_{B1}=I_{B2}=1.0\text{mA}$		3.0		μs
t_f	$V_{CC}=10\text{V}, I_C=10\text{mA}, I_{B1}=I_{B2}=1.0\text{mA}$		750		ns

(See Reverse Side)

R1

JEDEC TO-92 CASE - MECHANICAL OUTLINE

All Dimensions in Inches (mm).