



Features and Benefits

Video Encoding

- High-quality real-time encoding (I-, B-, and P-frames)
- Supports MPEG-2 (MP@ML, SP@ML) and MPEG-1
 - 525/60 (NTSC) up to 720x480 @ 30 fps
 - 625/50 (PAL) up to 720x576 @ 25 fps
- Variable and constant bit rate up to 15 Mb/sec
- Programmable group of pictures (GOP) lengths
- Adaptive field/frame (motion compensation type 8 discrete cosine transform [DCT])
- Field/frame motion estimation
 - B-frame: ± 100 horizontal x ± 64 vertical
 - P-frame: ± 100 horizontal x ± 64 vertical
 - Half-pel accuracy
- 4:2:2 to 4:2:0 conversion
- Time-based correction
- Speckle noise reduction
- Sharpness control
- Recursive noise reduction
- Inverse telecine (3:2 pulldown)
- Scene change detection
- Adaptive quantization
- Supports DVD-VR+Video, program, and transport streams
- AES, triple DES, and CPRM encryption
- Automatic VBI extraction

Analog Video Decoding

- Worldwide video standards support
 - NTSC-M/J/4.43
 - PAL-BDGH/M/N/Nc/60
 - SECAM
- Flexible video input multiplexer supporting composite, S-video, and component inputs with integrated anti-alias filtering
- 3-D adaptive comb filtering with time-based correction
- Full 10-bit ADCs and data path
- Macrovision, detection
- Programmable VBI data slicer for services such as closed caption, wide screen signaling (WSS), teletext, and program guides

Audio Encoding

- Dolby Digital (AC-3) 2-channel
- MPEG-1 layer II
- Sampling rates of 32 kHz, 44.1 kHz, and 48 kHz
- Compressed bit rates up to 384 kb/sec

Broadcast Audio Decoding

- Worldwide broadcast stereo audio standards support:
 - BTSC with and without dBx
 - EIAJ
 - A2
 - NICAM
 - FM/AM Mono
- Auto-detection and configuration of broadcast standards
- Two stereo channels of 3-band EQ, volume, soft mute, auto volume control, and soft clipping
- Flexible sample rate conversion on all audio inputs and outputs

Interfaces

- Video input:
 - Eight analog video inputs supporting composite, s-video, and YPbPr
 - Digital 8-bit 4:2:2 YCrCb ITU-R BT.656
 - Audio input:
 - Sound IF from tuners
 - Sony or Philips style serial audio
 - AC'97 Codec
 - S/PDIF
 - External MPEG transport stream capture interface
 - MPEG input and output supports one of the following:
 - PCI DMA master or PCI slave
 - 8-bit parallel program data
 - 1-bit serial peripheral interface (SPI) transport data
 - Optional advanced encryption standard (AES), triple-data encryption standard (DES) or CPRM encrypted output
 - 32-bit wide DDR SDRAM
 - Host interface supports one of the following
 - 32-bit, 33 MHz PCI, revision 2.3
 - 8-bit microcontroller
 - General-purpose input/output with 16 programmable pins
- ### Package
- Lead free 388-pin, 23 mm ball grid array (BGA)

© 2004, Conexant Systems, Inc. All Rights Reserved. Conexant and the Conexant logo are registered trademarks of Conexant Systems, Inc. All other trademarks are owned by their respective owners. Although Conexant strives for accuracy in all its publications, this material may contain errors or omissions and is subject to change without notice. **THIS MATERIAL IS PROVIDED AS IS AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.** Conexant shall not be liable for any special, indirect, incidental or consequential damages as a result of its use.

www.conexant.com
General Information:
U.S. and Canada: (888) 855-4562
International: (732) 345-7500
Headquarters
4000 MacArthur Blvd.
Newport Beach, CA 92660
Order# 102408A

