

40HF(R) Series

STANDARD RECOVERY DIODES 40 AMP

FEATURES

- Available as "HR" (high reliability) screened per MIL-PRF-19500, JANTX level. Add "HR" suffix to base part number.
- Available as non-RoHS (Sn/Pb plating), standard, and as RoHS by adding "-PBF" suffix.

MAXIMUM RATINGS

Parameter	Symbol	Test Conditions	40HF(R)		Units
			10 to 120	140 to 160	
Maximum average forward current	$I_{F(AV)}$		40 @ $T_c = 140^\circ\text{C}$	40 @ $T_c = 110^\circ\text{C}$	Amps
Maximum RMS forward current	$I_{F(RMS)}$		62		Amps
Maximum peak, on cycle, non-repetitive forward surge current	I_{FSM}	@ 50Hz @ 60Hz	570 595		Amps
Maximum I^2t for fusing	I^2t	@ 50Hz @ 60Hz	1600 1450		A^2s
Maximum repetitive peak reverse voltage	V_{RRM}		100-1200	1400-1600	Volts
Junction temperature range	T_j		-65 to +190	-65 to +160	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Part number	Maximum repetitive peak reverse voltage	Maximum non-repetitive peak reverse voltage	Maximum reverse current at $T_j = T_j$ maximum
	V_{RRM}	V_{RSM}	I_{RRM}
	Volts	Volts	mA
40HF10(R)	100	200	9
40HF20(R)	200	300	
40HF40(R)	400	500	
40HF60(R)	600	700	
40HF80(R)	800	900	
40HF100(R)	1000	1100	
40HF120(R)	1200	1300	
40HF140(R)	1400	1500	4.5
40HF160(R)	1600	1700	

40HF(R) Series

STANDARD RECOVERY DIODES 40 AMP

FORWARD CONDUCTION

Parameter	Symbol	Test Conditions			40HF(R)		Units
					10 to 120	140 to 160	
Maximum average forward current at case temperature	$I_{F(AV)}$	180° conduction, half sine wave			40 @ $T_C = 140^\circ\text{C}$	40 @ $T_C = 110^\circ\text{C}$	Amps
Maximum RMS forward current	$I_{F(RMS)}$				62		
Maximum peak, one cycle, non-repetitive forward surge current	I_{FSM}	t = 10ms	No voltage reapplied	Sinusoidal half wave, initial $T_J = T_J$ maximum	570		Amps
		t = 8.3ms			595		
		t = 10ms	100% V_{RRM} reapplied		480		
		t = 8.3ms			500		
Maximum I^2t for fusing	I^2t	t = 10ms	No voltage reapplied	Sinusoidal half wave, initial $T_J = T_J$ maximum	1600		A^2s
		t = 8.3ms			1450		
		t = 10ms	100% V_{RRM} reapplied		1150		
		t = 8.3ms			1050		
Maximum I^2vt for fusing	I^2vt	T = 0.1ms to 10ms, no voltage reapplied			16000		A^2Vs
Value of threshold voltage (up to 1200V)	$V_{F(TO)}$	$T_J = T_J$ maximum			0.65		Volts
Value of threshold voltage (up to 1400V, 1600V)					0.76		
Value of forward slope resistance (up to 1200V)	r_{f1}	$T_J = T_J$ maximum			4.29		mΩ
Value of forward slope resistance (up to 1400V, 1600V)					3.8		
Maximum forward voltage drop	V_{FM}	$I_{pk} = 125A, T_J = 25^\circ\text{C}, t_p = 400\mu\text{s}$ rectangular wave			1.30	1.50	Volts
THERMAL CHARACTERISTICS							
Maximum junction and storage temperature range	T_J, T_{stg}				-65 to 190	-65 to 160	°C
Maximum thermal resistance, junction to case	R_{thJC}	DC operation			0.95		K/W
Thermal resistance, case to heatsink	R_{thCS}	Mounting surface, smooth, flat and greased			0.25		K/W
Maximum allowable mounting torque (+0%, -10%)		Not lubricated thread, tightening on nut ⁽¹⁾			3.4 (30)		N-m (lbf-in)
		Lubricated thread, tightening on nut ⁽¹⁾			2.3 (20)		
		Not lubricated thread, tightening on hexagon ⁽²⁾			4.2 (37)		
		Lubricated thread, tightening on hexagon ⁽²⁾			3.2 (28)		

Note 1: Recommended for pass through-holes.

Note 2: Recommended for holed threaded heatsinks.

40HF(R) Series

STANDARD RECOVERY DIODES 40 AMP


ΔR_{thJC} Conduction

Conduction angle	Sinusoidal conduction	Rectangular conduction	Test conditions	Units
180°	0.14	0.10	$T_J = T_{J \text{ maximum}}$	K/W
120°	0.16	0.17		
90°	0.21	0.22		
60°	0.30	0.31		
30°	0.50	0.50		

*The table above shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC

MECHANICAL CHARACTERISTICS

Case	DO-5 (R)
Marking	Alpha numeric
Polarity	Cathode is stud
Reverse polarity	Anode is stud



	DO-5(R)			
	Inches		Millimeters	
	Min	Max	Min	Max
A	1/4-28 UNF2A threads			
B	0.669	0.688	16.990	17.480
C	-	0.794	-	20.160
D	-	1.000	-	25.400
E	0.422	0.453	10.720	11.510
F	0.115	0.200	2.920	5.080
G	-	0.450	-	11.430
H	0.220	0.249	5.580	6.320
J	0.250	0.375	6.350	9.530
K	0.156	-	3.960	-
M	-	0.667	-	16.940
N	0.030	0.080	0.760	2.030
P	0.140	0.175	3.560	4.450

40HF(R) Series

STANDARD RECOVERY DIODES 40 AMP




Fig. 1 - Current Ratings Characteristics




Fig. 3 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics




Fig. 5 - Forward Power Loss Characteristics

40HF(R) Series

STANDARD RECOVERY DIODES
40 AMP




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Forward Power Loss Characteristics




Fig. 8 - Forward Power Loss Characteristics




Fig. 9 - Maximum Non-Repetitive Surge Current




Fig. 11 - Forward Voltage Drop Characteristics (Up To 1200 V)




Fig. 10 - Maximum Non-Repetitive Surge Current




Fig. 12 - Forward Voltage Drop Characteristics (For 1400 V/1600 V)




Fig. 13 - Thermal Impedance Z_{thJC} Characteristics