


Technical Characteristics

Product Features	Maximum Ratings			
Fixed or adjustable attenuation tuning	Max. Input Power	250mW		
Low insertion loss	Operating Temperature	-55 to +95°C		
SMA connector standard	Storage Temperature	-65 to +125°C		
Impedance 50 or 75 ohms	Specifications @	25°C		
Compact size Meets MIL-E-5400 and MIL-E-16400 environmental requirements	Maximum Ratings			
Meets Mit-E-5400 and Mit-E-16400 environmental requirements	ECCN: EAR 99 (Unless otherwise specified)			
	HTS: 8543.7080.00			

Parameters	Freq. (GHz)	Minimum	Typical	Maximum	Units	Conditions
Attenuation	2.0 to 6.0		4.0		dB	
Insertion Loss	6.0		0.6		dB	
VSWR	2.0 to 6.0		1.8:1			
Linearity	2.0 to 6.0		+/-0.5		dB	
Max. Input Power	2.0 to 6.0			250	mW	

Package Outline



DISCLAIMER: Subject to change without notice. Rev(B) 09/12/19

Copyright© EclipseMDI

ā


1.408.526.1100

EQN0206-04 Negative Slope Equalizer

2.0 to 6.0 GHz



Test Data



DISCLAIMER: Subject to change without notice. Rev(B) 09/12/19

Quality products that serve the industry. Today and tomorrow.

Copyright© EclipseMDI

1.408.526.1100