

ESS1218A3 Bias Schottky Diode Detector

SMA-F/SMA-M Negative Output Polarity

12.0 to 18.0 GHz Octave Band



Technical Characteristics

Product Features
High Dynamic Range @100 uA typ. bias
Flat Frequency Response
Ultra Wideband and Ultra fast
Low Video Output Resistance (350 ohms typ.)
Negative Polarity is Standard
High Reliability Hermetically Sealed Coax
RoHS Compliant

Max. Ratings	
Storage Temperature:	Storage temperature range: -65°C to +125°C
Operating Temperature:	Operating temperature range: -55°C to +90°C
Maximum input power:	Maximum input power: 200mW

Product Export Classification

ECCN: EAR99 (Unless otherwise specified)

HTS: 8542330000

Electrical Specifications

Parameters	Freq. (GHz)	Min.	Typical	Max.	Units
Voltage Sensitivity	12.0 to 18.0 GHz	1800			mV/mW
Bias			100		μA
Tangential Sensitivity	12.0 to 18.0 GHz		-52		dBm
Flatness	12.0 to 18.0 GHz		0.25		+/-dB
Video Capacitance			10		pF
CW Power Handling				200	mWatts
Operating Temperature		-55		+125	°C

NOTES:

1. TSS is measured with a 2 MHz video bandwidth and 2dB NF amplifier.
2. Typical values are measured at +25°C and are not guaranteed.

Outline Drawing

