



Aluminum Electrolytic Capacitors

Selection chart

Date: December 2010

© EPCOS AG 2010. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

Selection chart

High voltage series

85 °C

4-pin snap-in, compact

| |
|---|
| <p>B43510 385 ... 500 V 85 °C / > 5000 h 105 °C at $V_{OP} \leq 0.88 \cdot V_R$</p> |
| Page |

Solder pins, compact

| |
|---|
| <p>B43520 385 ... 500 V 85 °C / > 5000 h 105 °C at $V_{OP} \leq 0.88 \cdot V_R$</p> |
| Page |

105 °C

4-pin snap-in, compact

| |
|---|
| <p>B43515 350 ... 450 V 105 °C / > 3000 h</p> |
| Page |

Solder pins, compact

| |
|---|
| <p>B43525 350 ... 450 V 105 °C / > 3000 h</p> |
| Page |

*4-pin snap-in, outstanding
ripple current capability*

| |
|--|
| <p>B43511 350 ... 450 V 85 °C / > 12000 h 105 °C at $V_{OP} \leq 0.93 \cdot V_R$</p> |
| Page |

*Solder pins, outstanding
ripple current capability*

| |
|--|
| <p>B43521 350 ... 450 V 85 °C / > 12000 h 105 °C at $V_{OP} \leq 0.93 \cdot V_R$</p> |
| Page |