

Aluminum Electrolytic Capacitors

Overview

Date: December 2010

© EPCOS AG 2010. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.



Overview

| Tem- | Series | Useful life | Features | Preferred | V _R | C _R | Page |
|--|------------------|-------------|-------------------------------|--------------------------------|----------------|----------------|------|
| perature | | | | applications | | | |
| °C | | h | | | V DC | μF | |
| Low-volta | ge series (E | 341) | | | | | |
| +85 | B41456 | > 12000 | Compact, long | Professional | 16 | 2200 | |
| | B41458 | | useful life | power supplies | 100 | 680000 | |
| +105 | B41560 | > 3000 | Extremely | Professional | 25 | 1500 | |
| | B41580 | | compact, high ripple current | power supplies | 100 | 330000 | |
| | B41550 | > 20000 | SIKOREL, | Highly | 16 | 1500 | |
| | B41570 | | outstanding reliability | professional power supplies | 100 | 220000 | |
| +125 | B41554 | > 5000 | SIKOREL, | Highly | 16 | 1500 | |
| | | | outstanding | professional | 100 | 220000 | |
| | | | reliability | power supplies | | | |
| High-volta | age series (| B43) | | | | | |
| +85 | B43464 | > 5000 | Standard version | Uninterruptible | 350 | 1000 | |
| | B43484 | | | power supplies, | 450 | 12000 | |
| | | | | frequency | | | |
| | | | | converters | | | |
| | B43455 | > 10000 | Long useful life | Frequency | 350 | 1000 | |
| | B43457 | | | converters, uninterruptible | 450 | 15000 | |
| | B43456 | > 12000 h | Extremely | power supplies, | 350 | 560 | |
| | B43458 | | compact, high | professional | 550 | 18000 | |
| | | | ripple current | power supplies | | | |
| | B43564 | > 15000 | High ripple | parrat supprise | 200 | 820 | |
| | B43584 | | current, long | | 500 | 33000 | |
| | | | useful life | | | | |
| +105 | B43740 | > 6000 | Extra long useful | Frequency | 350 | 1000 | |
| | B43760 | | life, outstanding reliability | converters, traction | 450 | 18000 | |
| | B43750 | > 8000 | Extremely high | | 350 | 560 | |
| | B43750 B43770 | > 0000 | ripple current | Power electronics. | 450 | 5300 | |
| | D43770 | | (up to 110 A) | traction, | 430 | 3000 | |
| | | | (ap to 110 A) | professional | | | |
| | | | | power supplies | | | |
| Accessories (ring clip, cap nuts, clamps, insulating parts) | | | | | | | |
| Accessories (initial only, out traits, oratings, modulating parts) | | | | | | | |