



Aluminum Electrolytic Capacitors

Selection chart

Date: December 2010

© EPCOS AG 2010. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

Selection chart

Low-voltage series

85 °C

Compact

<p>B41456 / B41458 16 ... 100 V 85 °C / > 12000 h</p>
Page

105 °C

Extremely compact

<p>B41560 / B41580 25 ... 100 V 105 °C / > 3000 h</p>
Page

125 °C

SIKOREL

<p>B41554 16 ... 100 V 125 °C / > 5000 h</p>
Page

SIKOREL

<p>B41550 / B41570 16 ... 100 V 105 °C / > 20000 h</p>
Page

High-voltage series

85 °C

Standard

<p>B43464 / B43484 350 ... 450 V 85 °C / > 5000 h</p>
Page

105 °C

Extra long useful life

<p>B43740 / B43760 350 ... 450 V 105 °C / > 6000 h</p>
Page

Long useful life

<p>B43455 / B43457 350 ... 450 V 85 °C / > 10000 h</p>
Page

Extremely high ripple current

<p>B43750 / B43770 350 ... 450 V 105 °C / > 8000 h</p>
Page

Extremely compact

<p>B43456 / B43458 350 ... 550 V 85 °C / > 12000 h</p>
Page

High ripple current

<p>B43564 / B43584 200 ... 500 V 85 °C / > 15000 h</p>
Page