



Aluminum Electrolytic Capacitors

Selection chart

Date: December 2010

© EPCOS AG 2010. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.

Selection chart

Low-voltage series

85 °C

Standard

B41231 10 ... 100 V 85 °C / > 2000 h
Page

105 °C

Standard

B41252 10 ... 100 V 105 °C / > 2000 h
Page

Excellent performance

B41505 10 ... 100 V 105 °C / > 5000 h
Page

Selection chart

High-voltage series

85 °C

Ultra compact

<p>B43305 200 ... 450 V 85 °C / > 2000 h 105 °C at $V_{OP} \leq 0.93 \cdot V_R$</p>
Page

Long useful life

<p>B43501 160 ... 500 V 85 °C / > 10000 h 105 °C at $V_{OP} \leq 0.93 \cdot V_R$</p>
Page

Long useful life, ultra compact

<p>B43601 200 ... 450 V 85 °C / > 10000 h 105 °C at $V_{OP} \leq 0.93 \cdot V_R$</p>
Page

Outstanding ripple current

<p>B43540 200 ... 450 V 85 °C / > 10000 h 105 °C at $V_{OP} \leq 0.93 \cdot V_R$</p>
Page

105 °C

Compact

<p>B43504 200 ... 450 V 105 °C / > 3000 h</p>
Page

Ultra compact

<p>B43508 200 ... 450 V 105 °C / > 3000 h</p>
Page

Outstanding ripple current, ultra compact

<p>B43543 200 ... 450 V 105 °C / > 3000 h</p>
Page

Excellent performance

<p>B43505 200 ... 450 V 105 °C / > 5000 h</p>
Page