

49MJ CRYSTAL



Specifications		
Parameters	Standard	Options
Frequency range	1,800 MHz - 250,000 MHz	lower frequencies on demand
Frequency stability	Please specify	
Overall		
Initial at 25°C		
Temperature		
Aging first year		
Aging over Years		
Operating temperature	0° C ~ +70°C	-20°C ~ +70°C -40°C ~ +85°C Other on custom request
Storage temperature	-40°C ~ +85°C	-55°C ~ +125°C
Load capacitance C1	4 pF ~ 120 pF or serie	
Equivalent series resistance ESR	see ESR table	Other on request
Shunt capacity Co	< 7 pF	Other
Aging	± 3 ppm /first year max.	Other on custom request
Insulation resistance	500 Mohms minimum at 100 VDC	
Drive level	10,0 to 2000 uW dependent of frequency	
Motional capacity C1	Please specify , if required	
Quality factor Q		
Co/C1		
Motional inductance L		
DFL (difference between 2 loadresonant frequencies)		
DLD (drive level dependency)		
Spurious		
Marking	Freq + Code + Week +Year	


49MJ CRYSTAL

ESR table


Frequency range	Mode	ESR (ohms)
1.800 MHz - 1,999 MHz	Fund.	650 max.
2.000 MHz - 2,449 MHz	Fund.	550 max.
2.450 MHz - 2,999 MHz	Fund.	350 max.
3.000 MHz - 3,499 MHz	Fund.	200 max.
3.500 MHz - 3,699 MHz	Fund.	150 max.
3.700 MHz - 3,999 MHz	Fund.	120 max.
4.000 MHz - 4,999 MHz	Fund.	100 max.
5.000 MHz - 5,999 MHz	Fund.	60 max.
6.000 MHz - 6,999 MHz	Fund.	50 max.
7.000 MHz - 7,999 MHz	Fund.	40 max.
8.000 MHz - 9,999 MHz	Fund.	35 max.
10.000 MHz - 11,999 MHz	Fund.	30 max.
12.000 MHz - 17,999 MHz	Fund.	25 max.
18.000 MHz - 40,000 MHz	Fund.	20 max.
18.000 MHz - 24,999 MHz	3 rd	60 max.
25.000 MHz - 39,999 MHz	3 rd	50 max.
40.000 MHz - 89,999 MHz	3 rd	40 max.
90.000 MHz - 150,000 MHz	3 rd	80 max.
50.000 MHz - 59,999 MHz	5 th	90 max.
60,000 MHz - 150,000 MHz	5 th	100 max.
80,000 MHz - 210,000 MHz	7 th	150 max.
100,000 MHz - 250,000 MHz	9 th	200 max.

Drawing

Package	HC49U metal jacket	HC49T metal jacket (11mm height)
---------	--------------------	----------------------------------



SOLDER PAD LAYOUT



case	x
49U MJ	13.46 mm
49T MJ	11.0 mm