

## OVEN CONTROLLED CRYSTAL OSCILLATOR

<b>Features:</b>	High stability vs. temperature up to $\pm 3E-8$	Frequency range: 1—75M
------------------	---	------------------------

**OPTION GUIDE:** OX32-----38-----H-----12-----JT-----[SIN]-----13M

Temperature stability	Aging	Output	Supply Voltage
38: $\pm 3E-8$ 58: $\pm 5E-8$ 17: $\pm 1E-7$ 27: $\pm 2E-7$ 37: $\pm 3E-7$ 57: $\pm 5E-7$	J: $\pm 5E-7$ /year I: $\pm 3E-7$ /year H: $\pm 2E-7$ /year G: $\pm 1E-7$ /year	SIN HCMOS	5: 5V $\pm 5\%$ 12: 12V $\pm 5\%$


Temperature choice

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	U	W	X
-60	-55	-50	-45	-40	-30	-20	-10	0	+10	+25	+40	+45	+50	+55	+60	+65	+70	+75	+80	+85

### SPECIFICATION

Output	SIN	Square Form
Duty cycle	×	40...60%
Short term stability per 1 sec, typical	$< 1E-10$	
Daily fluctuation	$\leq \pm 0.02$ ppm	
Frequency stability vs. load changes	$< \pm 1E-8 @ 50 \Omega \pm 10\%$	$< \pm 1E-8 @ 1k \Omega \pm 10\%$
Frequency stability vs. power supply changes	$< \pm 1E-8 @ V_{cc} \pm 10\%$	
Peak current during warm-up @ 25°C	$< 500$ mA	
Frequency pulling range	$> \pm 5E-6 @ 0.5V \text{ --- } 4.5V$	
Linearity	$\pm 10\%$	
Phase noise, typical for 10M		
1 Hz	-90 dBc/Hz	
10 Hz	-120 dBc/Hz	
100 Hz	-140 dBc/Hz	
1k Hz	-150 dBc/Hz	
10k Hz	-155 dBc/Hz	
Harmonic suppression	40dB	×
Spurious suppression	70dB	
Input impedance	100k $\Omega$	
Storage temperature range	-40...+85°C	

### Package



### Pin configuration:

1. Freq. Adj
2. V Reference
3. Supply voltage
4. RF-Output
5. GND

Note:

Not all combinations are available, any requests, please consult factory