

SX5C OSCILLATOR



Specifications





Parameters	Standard	Options
Frequency range	0,5 MHz - 160 MHz	
Logic output	HCMOS/TTL compatible	TTL only
Frequency stability		
Overall	+/- 50 ppm	+/-15 ppm best possible
Initial at 25°C	Please specify	
Temperature		
vs supply voltage change		
vs load change		
Aging first year		
Aging over Years		
Operating temperature	0° C ~ +70°C	-20°C ~ +70°C
		-40°C ~ +85°C
		Other on custom request
Storage temperature	-40°C ~ +85°C	-55°C ~ +125°C
Supply voltage	5,0 V ± 5% or 3,3 V +5%	1,8 V ; 2,5 V ; 2,8 V
		Other on custom request
Current	Other	
0,500 MHz - 29,999 MHz		
30,000 MHz - 49,999 MHz		
50,000 MHz - 99,999 MHz		
100,00 MHz - 160,00 MHz		
Load	15 pF	Other - dependent of logic output
Rise/fall time	Other on custom request	
0,500 MHz - 29,999 MHz		
30,000 MHz - 49,999 MHz		
50,000 MHz - 99,999 MHz		
100,00 MHz - 160,00 MHz		
Duty cycle	40/60 %	45/55 %
		Other on custom request
Phase noise	Please specify (if required)	
Harmonics		
Sub-harmonics		
Jitter		

SX5C OSCILLATOR

Specifications

Parameters	Standard	Options
Start-up time	10 ms max.	Other on custom request
Tristate	High or open = enable Low = disable	no tristate
Marking	Freq + Code + Week +Year	
Package	SX5 4 pad	

Drawing



Recommended
Solder Pattern

Pin configuration	4 pad version	
	#1: E/D or NC	
	#2 : GND	
	#3 : Output	
	#4 : Vcc	

HM International

Demer 26 B-2230 Herselt BELGIUM

Tel. +32(0)14548955 Fax. +32(0)14549443

email : info@hminternational.be

www.hminternational.be