



TB39 CRYSTAL

Specifications

Parameters	Standard	Options
Frequency range	1,000 MHz - 100,000 MHz	
Frequency tolerance at 25°C	± 20 ppm	Other on custom request
Operating temperature range	-20°C ~ +70°C	Other on custom request
Temperature stability	± 30 ppm	Other on custom request
Load capacitance Cl	10 pF ~ 80 pF or serie	
Storage temperature	-40°C ~ +85°C	-55°C ~ +125°C
Equivalent series resistance ESR	see ESR table	
Aging	± 5 ppm/ first year	
Shunt capacity Co	< 5 pF	
Insulation resistance	500 Mohms minimum at 100 VDC	
Drive level	10,0 to 100 uW dependent of frequency	
Marking	Freq	

ESR table

Frequency range	Mode	ESR (ohms)
1.000 MHz - 3.999 MHz	Fund.	200 max.
4.000 MHz - 5.499 MHz	Fund.	150 max.
5.500 MHz - 5.999 MHz	Fund.	100 max.
6.000 MHz - 9.999 MHz	Fund.	80 max.
10.000 MHz - 11.999 MHz	Fund.	60 max.
12.000 MHz - 15.999 MHz	Fund.	50 max.
16.000 MHz - 30.000 MHz	Fund.	40 max.
26.000 MHz - 35.999 MHz	3 rd	100 max.
36.000 MHz - 100.000 MHz	3 rd	50 max.

Drawing

Package	TB39
---------	------

HM International
 Demer 26 B-2230 Herselt BELGIUM
 Tel. +32(0)14548955 Fax. +32(0)14549443
 email : info@hminternational.be www.hminternational.be