



SIPMOS[®] Small-Signal-Transistor
Feature

- n-channel
- enhancement mode
- Logic level, dv/dt rated
- Pb-free lead plating; RoHS compliant

Product Summary

$V_{DS}^{1)}$	600	V
$R_{DS(on),max}$	45	Ω
I_D	0.09	A

SOT89


Type	Package	Pb-free	Tape and Reel Information	Marking
BSS225	SOT89	Yes	L6327: 3000PCS/reel	KD

Maximum ratings, at $T_j=25\text{ }^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	$T_A=25\text{ }^\circ\text{C}$	0.09	A
		$T_A=70\text{ }^\circ\text{C}$	0.073	
Pulsed drain current	$I_{D,pulse}$	$T_A=25\text{ }^\circ\text{C}$	0.36	
Reverse diode dv/dt	dv/dt	$I_D=0.09\text{ A}$, $V_{DS}=480\text{ V}$, $di/dt=200\text{ A}/\mu\text{s}$, $T_{j,max}=150\text{ }^\circ\text{C}$	6	kV/ μs
Gate source voltage	V_{GS}		± 20	V
ESD sensitivity (HBM) as per MIL-STD 883			Class 1a	
Power dissipation	P_{tot}	$T_A=25\text{ }^\circ\text{C}$	1.00	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 150	$^\circ\text{C}$
IEC climatic category; DIN IEC 68-1			55/150/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Thermal characteristics

Thermal resistance, junction - minimal footprint	R_{thJA}		-	-	125	K/W
--	------------	--	---	---	-----	-----

Electrical characteristics, at $T_j=25\text{ °C}$, unless otherwise specified
Static characteristics

Drain-source breakdown voltage ¹⁾	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}, I_D=250\text{ }\mu\text{A}$	600	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=0\text{ V}, I_D=94\text{ }\mu\text{A}$	1.3	1.9	2.3	
Drain-source leakage current	$I_{D(off)}$	$V_{DS}=600\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ °C}$	-	-	0.1	μA
		$V_{DS}=600\text{ V}, V_{GS}=0\text{ V}, T_j=150\text{ °C}$	-	-	5	
Gate-source leakage current	I_{GSS}	$V_{GS}=20\text{ V}, V_{DS}=0\text{ V}$	-	10	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$V_{GS}=4.5\text{ V}, I_D=0.09\text{ A}$	-	28	45	Ω
		$V_{GS}=10\text{ V}, I_D=0.09\text{ A}$	-	30	45	
Transconductance	g_{fs}	$ V_{DS} >2 I_D R_{DS(on)max}, I_D=0.075\text{ A}$	0.05	0.14	-	S

¹⁾ V_{DS} is zero-hour rated, see note at p.8

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Dynamic characteristics

Input capacitance	C_{iss}	$V_{GS}=0\text{ V}, V_{DS}=25\text{ V},$ $f=1\text{ MHz}$	-	99	131	pF
Output capacitance	C_{oss}		-	7.6	11	
Reverse transfer capacitance	C_{rss}		-	3.1	4.4	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=300\text{ V},$ $V_{GS}=10\text{ V}, I_D=0.09\text{ A},$ $R_G=6\ \Omega$	-	14.0	20.0	ns
Rise time	t_r		-	38.0	57.0	
Turn-off delay time	$t_{d(off)}$		-	62.0	93	
Fall time	t_f		-	41.0	62	

Gate Charge Characteristics


Gate to source charge	Q_{gs}	$V_{DD}=400\text{ V},$ $I_D=0.09\text{ A},$ $V_{GS}=0\text{ to }10\text{ V}$	-	0.32	0.43	nC
Gate to drain charge	Q_{gd}		-	1.4	2.1	
Gate charge total	Q_g		-	3.9	5.8	
Gate plateau voltage	$V_{plateau}$		-	3.3	-	V

Reverse Diode

Diode continuous forward current	I_S	$T_A=25\text{ }^\circ\text{C}$	-	-	0.09	A
Diode pulse current	$I_{S,pulse}$		-	-	0.36	
Diode forward voltage	V_{SD}	$V_{GS}=0\text{ V}, I_F=0.09\text{ A},$ $T_J=25\text{ }^\circ\text{C}$	-	0.75	1.2	V
Reverse recovery time	t_{rr}	$V_R=300\text{ V}, I_F=0.09\text{ A},$ $di_F/dt=100\text{ A}/\mu\text{s}$	-	246	370	ns
Reverse recovery charge	Q_{rr}		-	248	373	nC


1 Power dissipation

$P_{tot}=f(T_A)$



2 Drain current


$I_D=f(T_A); V_{GS} \geq 10\text{ V}$



3 Safe operating area

$I_D=f(V_{DS}); T_A=25\text{ °C}; D=0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJA}=f(t_p)$


parameter: $D=t_p/T$



5 Typ. output characteristics

$I_D = f(V_{DS}); T_j = 25\text{ }^\circ\text{C}$


parameter: V_{GS}



6 Typ. drain-source on resistance


$R_{DS(on)} = f(I_D); T_j = 25\text{ }^\circ\text{C}$

parameter: V_{GS}




7 Typ. transfer characteristics

$I_D = f(V_{GS}); |V_{DS}| > 2|I_D|R_{DS(on)max}$




8 Typ. forward transconductance

$g_{fs} = f(I_D); T_j = 25\text{ }^\circ\text{C}$



9 Drain-source on-state resistance


$R_{DS(on)}=f(T_j); I_D=0.1\text{ A}; V_{GS}=10\text{ V}$



10 Typ. gate threshold voltage


$V_{GS(th)}=f(T_j); V_{DS}=V_{GS}; I_D=94\ \mu\text{A}$

parameter: I_D



11 Typ. capacitances


$C=f(V_{DS}); V_{GS}=0\text{ V}; f=1\text{ MHz}; T_j=25^\circ\text{C}$



12 Forward characteristics of reverse diode

$I_F=f(V_{SD})$


parameter: T_j



13 Typ. gate charge


$V_{GS}=f(Q_{gate}); I_D=0.1\text{ A pulsed}$

parameter: V_{DD}




14 Drain-source breakdown voltage

$V_{BR(DSS)}=f(T_j); I_D=250\ \mu\text{A}$




Package Outline:




¹⁾Ejector pin markings possible

Footprint:



Dimensions in mm

Packaging:



note:

Due to small size of the package, creeping currents between leads external to the package can occur in the application. Extra protection from contamination for the package (i.e. protective laquer) is necessary to maintain the values, specified in this document. Values given in this document are only valid for 0 hour lifetime, if no suitable external protection is applied.

Published by
Infineon Technologies AG
Bereich Kommunikation
St.-Martin-Straße 53
D-81541 München
© Infineon Technologies AG 1999
All Rights Reserved.

Attention please!

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

Information

For further information on technology, delivery terms and conditions and prices, please contact your nearest Infineon Technologies office in Germany or our Infineon Technologies representatives worldwide (see address list).

Warnings

Due to technical requirements, components may contain dangerous substances.
For information on the types in question, please contact your nearest Infineon Technologies office.

Infineon Technologies' components may only be used in life-support devices or systems with the expressed written approval of Infineon Technologies if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.