

PMB 6275

SMARTi®PM+

Quad Band Micro EDGE Transceiver

SMARTi®PM+ (PMB 6275) is a Quad Band EDGE/GPRS Transceiver in a groundbreaking new 3 x 3 mm² wafer level ball grid array package. It enables the design of Quad Band Micro EDGE RF systems in less than 100 mm² PCB area.


Its high level of integration and outstanding small mechanical dimensions make this single chip CMOS transceiver the perfect match for all size sensitive GSM850/GSM900/GSM1800/GSM1900 voice and high performance data applications.

The SMARTi PM+ lines up with any standard linear Power Amplifier from all major vendors and therefore provides sourcing flexibility according to customer individual preferences. The standard analogue IQ interface and the 3-wire bus for control do match all major Cellular Basebands.

The unique Small Signal Polar Modulator architecture offers excellent RF performance and robustness in customer mobile phone assembly lines. The advanced, simple programming and calibration schemes do furthermore reduce cost of ownership significantly.

Features

- Receiver
 - Direct conversion receiver architecture
 - Automatic DC offset compensation
 - GPRS/EDGE class 1 to 12
- Transmitter
 - Polar modulator for EDGE
 - Single-ended 50 Ω outputs enable direct connection with Power Amplifier
 - PA bias control interface for efficiency EDGE enhancement of contemporary linear EDGE-Power Amplifier
 - Programmable Gain Amplifier (PGA) for accurate output power level control in 8PSK mode
 - Integrated ramping generator for 8PSK mode



- Integrated low tolerance base band filter
- Very low power budget
- GPRS/EDGE class 1 to 12
- RF-Synthesizer
 - ΣΔ-Synthesizer for multi-slot operation
 - Fast lock-in times (< 150 μs)
 - Integrated loop filter
- RF Oscillator
 - Fully integrated, low noise RF VCO for quad-band operation
- Reference Oscillator
 - Fully integrated VCXO
 - Fully digital controlled crystal oscillator core with highly linear tuning characteristic
 - 26 MHz Reference Oscillator can be applied externally
 - Three single ended clock outputs
- Baseband interface
 - Multiplexed differential I/Q baseband
 - TX-input voltages and RX-output voltages
 - Three wire bus for transceiver control
- Frontend module interface
 - Two FEM control outputs
- Ultra Low RF BOM < 20 components needed

www.infineon.com/wireless


Communication Solutions



Never stop thinking

SMARTi PM+

Quadband Micro EDGE Radio System (PCB area < 100 mm², 20 components)



Applications

- GSM/EDGE single, dual, triple, and quad band
Mobile Phones and Data Modems/PC cards

Technologies

- 130 nm CMOS Technology
- Single Supply Voltage
- SG-VFWLB-47 package 3 x 3 mm²

How to reach us:
<http://www.infineon.com>

Published by
Infineon Technologies AG
81726 Munich, Germany

© Infineon Technologies AG 2007.
All Rights Reserved.

Legal Disclaimer

The information given in this Product Brief shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system.

Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Ordering No. B118-H8955-X-X-7600
Printed in Germany
PS 010775 nb