


Probes For Fine Pitch Connections



TSOP FlexProbes 0,50mm (.0197") Pitch

TSOP FlexProbes 0,50mm (.0197") Pitch


Data/Application Sheets

ALPTEX Part Number	Description Standard Pinout, "Hermi" Connector, Direct Solder Type, 32/40/48 Lead	
923706		
923707	Standard Pinout, "Hermi" Connector, Socket Type, 40/48 Lead	
923710	Standard Pinout, Socket Connector, Socket Type, 40/48/56 Lead	
923712	Standard Pinout, Socket Connector, Direct Solder Type, 32/40/48/56 Lead	
923723	Reverse Pinout, "Hermi" Connector, Socket Type, 40/48 Lead	
923724	Reverse Pinout, "Hermi" Connector, Socket Type, 40/48/56 Lead	_

.pdf files are also available for the following:

- 0,8mm (.0315") Pitch SSOP FlexProbes...SSOP_FP.pdf
- 1,27mm (.050") Pitch PSOP FlexProbes...PSOP_FP.pdf
- 1,27mm (.050") Pitch PLCC FlexProbes...PLCC_FP.pdf
- 0,75mm (.0295") Pitch microBGA FlexProbes...mBGA_FP.pdf
- FlexProbe Extenders...EXTENDFP.pdf

(Direct Solder)





50 Position Interface Connector -Mates With MERITEC Surface Mount Hermaphroditic Connector (ALPTEX Part #923718-50)

_			ALPTEX
	PACKAGE	# LEADS	PART NUMBER
		32	923706-32
	TSOP	40	923706-40
		48	923706-48

FEATURES:

- THE MOST FLEXIBLE "TARGET" INTERCONNECT AVAILABLE...MINIMIZES PHYSICAL STRAIN ON THE TARGET PADS.

- A UNIQUE SOLUTION FOR CONNECTING DIRECTLY TO YOUR P. C. BOARD.
 REFLOW SOLDERS TO STANDARD TSOP PAD PATTERN.
 ELIMINATES NEED TO ALTER P. C. BOARD BETWEEN DEVELOPMENT AND PRODUCTION PHASES.
- COMPACT LENGTH VIRTUALLY ELIMINATES CROSSTALK / EMI PROBLEMS.
 MERITEC HERMAPHRODITIC CONNECTOR PROVIDES A DEPENDABLE AND COMPACT INTERFACE FOR YOUR TEST / EMULATION CIRCUITRY.
- MADE ENTIRELY IN THE U.S.A.
 FLEXPROBES FOR EMULATING OTHER POPULAR COMPONENT PACKAGES ARE ALSO AVAILABLE...CONSULT FACTORY.


Incorporated P.O. Box 476 Orwell, Ohio 44076 (440)437-5570 • (440)437-5571 FAX www.alptex.com

TSOP FlexProbe Application Data 48TSOP Pin # 40TSOP Pin # **ALPTEX Part Number 923706-XX** 32TSOP Pin # (Direct Solder) 25 48 NC 25 27 29 31 33 35 37 39 41 43 45 47 2 4 6 8 10 12 14 16 18 20 22 4 NC 21 23 257 29 31 33 35 37 39 2 4 6 8 10 12 14 16 18 2 NC NC NC NC NC 17 19 21 23 25 27 29 31 2 4 6 8 NC NC NC NC 18 20 22 24 26 28 30 32 1 3 5 7 9 11 13 15 NC NC NC 22 24 26 28 30 32 4 36 38 40 1 3 5 7 9 11 13 15 17 9 NC NC 21 40 17 FlexProbe Pinout **As Viewed From Bottom** TSOP Pin # (Interface Connector - Near Side) 10 12 14 16 NC NC NC NC 20 24 Note: This FlexProbe is designed to be reflow soldered directly to the P. C. Board. It is not intended for use with sockets.

.190 Typ .250 .100 Typ .030 Typ P C Board Pad Pattern For Mating MERITEC Connector **ALPTEX Part #923718-50** (Solder Pads - Near Side) 1.200 Pin # 1 (Of Target) 1.700 .050 ±.003 - 24 Places Tolerance Non-Accumulative .035 Incorporated P.O. Box 476 Orwell, Ohio 44076 .062 ±.001 Ø Thru - 2 Places (440)437-5570 • (440)437-5571 FAX

ALL STATEMENTS, SPECIFICATIONS AND TECHNICAL INFORMATION ON THIS DATA SHEET ARE SUBJECT TO CHANGE AT ANY TIME WITHOUT NOTICE.

www.alptex.com



50 Position Interface Connector -Mates With MERITEC Surface Mount Hermaphroditic Connector (ALPTEX Part #923718-50)

			ALPTEX
	PACKAGE	# LEADS	PART NUMBER
	TSOP	40	923707-40
		48	923707-48

FEATURES:

- THE MOST FLEXIBLE "TARGET" INTERCONNECT AVAILABLE...MINIMIZES PHYSICAL STRAIN ON THE SOCKET.
 A UNIQUE SOLUTION FOR CONNECTING TO MERITEC TSOP SOCKETS.

- FITS INTO SOCKET LIKE A COMPONENT PACKAGE.

 UTILIZES THE MERITEC SOCKET'S "POSITIVE LOCK" FEATURE TO MAINTAIN A SECURE CONNECTION DURING USE.
- SPRING TEMPER NICKEL-SILVER CONTACTS EXCEED INDUSTRY
- COMPONENT LEAD REQUIREMENTS.


 COMPACT LENGTH VIRTUALLY ELIMINATES CROSSTALK / EMI PROBLEMS.


 MERITEC HERMAPHRODITIC CONNECTOR PROVIDES A DEPENDABLE AND COMPACT INTERFACE FOR YOUR TEST / EMULATION CIRCUITRY.
- MADE ENTIRELY IN THE U.S.A.
- FLEXPROBES FOR EMULATING OTHER POPULAR COMPONENT PACKAGES ARE ALSO AVAILABLE...CONSULT FACTORY.



TSOP FlexProbe Application Data ALPTEX Part Number 923707-XX 48TSOP Pin # 40TSOP Pin # NC 25 27 29 31 33 35 37 39 41 43 45 47 2 4 6 8 10 12 14 16 18 20 22 4 NC NC 21 23 25 27 29 31 33 35 37 39 2 4 6 8 10 12 14 16 18 20 NC NC NC NC 22 24 26 28 30 32 4 36 38 40 1 3 5 7 9 11 13 15 17 19 NC NC 26 28 30 32 34 36 38 40 42 44 46 48 25 48 21 FlexProbe Pinout **As Viewed From Bottom** Ш TSOP Pin # (Interface Connector - Near Side) 13 15 17 19 21 23 20 24

Note: This FlexProbe is designed to mate with MERITEC TSOP Socket #980020-XX-XX ONLY. It is not intended for use with other sockets or in solder down applications.







_			ALPTEX
	PACKAGE	# LEADS	PART NUMBER
		40	923710-40
	TSOP	48	923710-48
		56	923710-56

FEATURES:

- THE MOST FLEXIBLE "TARGET" INTERCONNECT AVAILABLE...MINIMIZES PHYSICAL STRAIN ON THE SOCKET.


 A UNIQUE SOLUTION FOR CONNECTING TO MERITEC TSOP SOCKETS.

 FITS INTO SOCKET LIKE A COMPONENT PACKAGE.


 UTILIZES THE MERITEC SOCKET'S "POSITIVE LOCK" FEATURE TO MAINTAIN

- A SECURE CONNECTION DURING USE.
 SPRING TEMPER NICKEL-SILVER CONTACTS EXCEED INDUSTRY COMPONENT LEAD REQUIREMENTS.
- COMPACT LENGTH VIRTUALLY ELIMINATES CROSSTALK / EMI PROBLEMS.
- MADE ENTIRELY IN THE U.S.A.
- FLEXPROBES FOR EMULATING OTHER POPULAR COMPONENT PACKAGES ARE ALSO AVAILABLE...CONSULT FACTORY.






Note: This FlexProbe is designed to mate with MERITEC TSOP Socket #980020-XX-XX ONLY. It is not intended for use with other sockets or in solder down applications.



(Direct Solder)






		ALPTEX
PACKAGE	# LEADS	PART NUMBER
	32	923712-32
TSOP	40	923712-40
1306	48	923712-48
	56	923712-56

FEATURES:


- THE MOST FLEXIBLE "TARGET" INTERCONNECT AVAILABLE...MINIMIZES • THE MOST FLEXIBLE TRAGET INTERCONNECT AVAILABLE...MINIMIZES PHYSICAL STRAIN ON THE TARGET PADS.
 • A UNIQUE SOLUTION FOR CONNECTING DIRECTLY TO YOUR P. C. BOARD.
 • REFLOW SOLDERS TO STANDARD TSOP PAD PATTERN.

- ELIMINATES NEED TO ALTER P. C. BOARD BETWEEN DEVELOPMENT AND PRODUCTION PHASES.
- COMPACT LENGTH VIRTUALLY ELIMINATES CROSSTALK / EMI PROBLEMS.
 MADE ENTIRELY IN THE U.S.A.
 FLEXPROBES FOR EMULATING OTHER POPULAR COMPONENT
- PACKAGES ARE ALSO AVAILABLE...CONSULT FACTORY.


Incorporated P.O. Box 476 Orwell, Ohio 44076 (440)437-5570 • (440)437-5571 FAX www.alptex.com



Note: This FlexProbe is designed to be reflow soldered directly to the P. C. Board.
It is not intended for use with sockets.



(Reverse Pinout)





		ALPTEX
PACKAGE	# LEADS	PART NUMBER
TSOP	40	923723-40
	48	923723-48

FEATURES:

- THE MOST FLEXIBLE "TARGET" INTERCONNECT AVAILABLE...MINIMIZES PHYSICAL STRAIN ON THE SOCKET.
- A UNIQUE SOLUTION FOR CONNECTING TO MERITEC TSOP SOCKETS.
- ENABLES AN INTERFACE MAPPED FOR THE STANDARD FLEXPROBE (ALPTEX #923707) TO COMMUNICATE CORRECTLY WITH A REVERSE PINOUT TARGET.
- FITS INTO SOCKET LIKE A COMPONENT PACKAGE.
 UTILIZES THE MERITEC SOCKET'S "POSITIVE LOCK" FEATURE TO MAINTAIN A SECURE CONNECTION DURING USE
- SPRING TEMPER NICKEL-SILVER CONTACTS EXCEED INDUSTRY COMPONENT LEAD REQUIREMENTS.
- COMPACT LENGTH VIRTUALLY ELIMINATES CROSSTALK / EMI PROBLEMS.
 MERITEC HERMAPHRODITIC CONNECTOR PROVIDES A DEPENDABLE AND COMPACT INTERFACE FOR YOUR TEST / EMULATION CIRCUITRY.
- MADE ENTIRELY IN THE U.S.A.
- FLEXPROBES FOR EMULATING OTHER POPULAR COMPONENT PACKAGES ARE ALSO AVAILABLE...CONSULT FACTORY.


Incorporated P.O. Box 476 Orwell, Ohio 44076 (440)437-5570 • (440)437-5571 FAX www.alptex.com

TSOP Socket #980020-XX-XX ONLY.

solder down applications.


It is not intended for use with other sockets or in

TSOP FlexProbe Application Data 48TSOP Pin # **ALPTEX Part Number 923723-XX** 40TSOP Pin # (Reverse Pinout) NC 24 22 20 18 16 14 12 10 8 6 4 2 47 45 43 37 35 33 129 27 25 NC NC 20 18 16 14 12 10 8 6 4 2 39 37 35 33 31 29 27 25 23 21 NC NC NC 19 17 15 13 11 9 7 5 3 1 40 38 36 34 32 28 26 24 2 NC 24 88888888888 TSOP Pin # 25 FlexProbe Pinout Note: This FlexProbe is designed to mate with MERITEC As Viewed From Top



(Interface Connector - Near Side)

(Reverse Pinout)





		ALPTEX
PACKAGE	# LEADS	PART NUMBER
	40	923724-40
TSOP	48	923724-48
	56	923724-56

FEATURES:


- THE MOST FLEXIBLE "TARGET" INTERCONNECT AVAILABLE...MINIMIZES
- PHYSICAL STRAIN ON THE SOCKET.

 A UNIQUE SOLUTION FOR CONNECTING TO MERITEC TSOP SOCKETS.

 ENABLES AN INTERFACE MAPPED FOR THE STANDARD FLEXPROBE (ALPTEX #923710) TO COMMUNICATE CORRECTLY WITH A REVERSE PINOUT TARGET.
- FITS INTO SOCKET LIKE A COMPONENT PACKAGE.

 UTILIZES THE MERITEC SOCKET'S "POSITIVE LOCK" FEATURE TO MAINTAIN A SECURE CONNECTION DURING USE.
- SPRING TEMPER NICKEL-SILVER CONTACTS EXCEED INDUSTRY COMPONENT LEAD REQUIREMENTS.
- COMPACT LENGTH VIRTUALLY ELIMINATES CROSSTALK / EMI PROBLEMS.
- MADE ENTIRELY IN THE U.S.A.
 FLEXPROBES FOR EMULATING OTHER POPULAR COMPONENT PACKAGES ARE ALSO AVAILABLE...CONSULT FACTORY.





(Interface Connector - Near Side)

As Viewed From Top

Note: This FlexProbe is designed to mate with MERITEC TSOP Socket #980020-XX-XX ONLY. It is not intended for use with other sockets or in solder down applications.

