

**Laser Diode Driver with Waveform Generator**



The EL6296 is a highly integrated laser diode driver designed to support multi-standard writable optical drives.

It accomplishes this by incorporating a waveform generator wherein the diode currents and timing details can be programmed before operation. The data input circuitry inspects the NRZ serial data waveform and generates programmed waveforms in recognition of 3, 4, 5, or 6 or more clock periods of space changing to 3, 4, 5, or 6 or more clock periods of mark, and vice versa.

This programmable architecture allows reprogramming of the timers to support different media, DVD or CD standards, and different speeds. The programming is accomplished through a serial interface port. Two outputs are provided to support dual-laser multi-standard optical heads.

The EL6296 requires 3.3V and 5V supplies, with all the logical interface operating on the 3.3V supply.

**Ordering Information**

PART NUMBER	PACKAGE	TAPE & REEL	PKG. DWG. #
EL6296CL	24-Pin QFN	-	MDP0046
EL6296CL-T7	24-Pin QFN	7"	MDP0046
EL6296CL-T13	24-Pin QFN	13"	MDP0046
EL6296CLZ (See Note)	24-Pin QFN (Pb-free)	-	MDP0046
EL6296CLZ-T7 (See Note)	24-Pin QFN (Pb-free)	7"	MDP0046
EL6296CLZ-T13 (See Note)	24-Pin QFN (Pb-free)	13"	MDP0046

NOTE: Intersil Pb-free products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which is compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J Std-020B.


**Features**

- Pb-free available
- Complete programmable laser diode driver
- 350mA maximum total output
- 8-bit x 8-bit multiplying DAC output provides 8-bit full scale adjustment and 8-bit resolution at any full scale output
- 0.17ns timer resolution
- Two laser outputs allows read/write DVD and CD combinations
- Programmable waveform values support 2.6GB DVD-RAM, 4.7GB DVD-RAM, DVD-R, DVD+RW, DVD-RW, CD-RW, and CD-R
- Analog input supports APC
- HFM oscillator programmable to 100mA<sub>p-p</sub> from 100MHz to 500MHz
- PLL allows reduced-frequency clock on flex cable
- Separate serial input works up to 25Mb/sec

**Applications**

- Combination DVD writable and CD writable drives
- DVD camcorders
- DVD video recorders

**Pinout**



All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9001 quality systems.  
Intersil Corporation's quality certifications can be viewed at [www.intersil.com/design/quality](http://www.intersil.com/design/quality)

*Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.*

For information regarding Intersil Corporation and its products, see [www.intersil.com](http://www.intersil.com)