

Dual 4-Channel DVD, 3-Channel CD Driver with Oscillator & LVDS

The EL6835 is a high performance, dual output, laser driver for writeable ‘super-combo’ CD - DVD drives. The ENA pin enables the chip, while the SEL1 pin selects the I_{OUT} pin. Various waveforms can be generated where the amplitude is determined by the currents flowing into I_{INR}, I_{IN2}, I_{IN3}, and I_{IN4}. The timing is determined by the signals at WEN2-WEN2B, WEN3-WEN3B, and WEN4-WEN4B. The oscillator is enabled when OSCEN is high. The amplified I_{INR} current of the selected channel is enabled when the ENA pin is high. The total output current is the sum of the read current, the enabled write currents, and the oscillator current when enabled.

Usually a voltage DAC will drive a resistor that is in series with the I_{INR}, I_{IN2}, I_{IN3} and I_{IN4} input. The resistor allows the user to optimize the current gain for each channel.

Output write current pulses are enabled when a high is applied to the WEN2-WEN2B, WEN3-WEN3B, or WEN4-WEN4B pin. The write current will flow to the selected output. When SEL1 is high I_{OUT1} is selected. WENRB enables read and oscillator current when low.

The R_F oscillators frequency is determined by R_{FREQ1} or R_{FREQ2}, and its amplitude by R_{AMP1} or R_{AMP2}.

Ordering Information

PART NUMBER (See Note)	PART MARKING	PACKAGE (Pb-Free)	TAPE & REEL	PKG. DWG. #
EL6835CLZ	6835CLZ	32-Pin QFN	-	MDP0046
EL6835CLZ-T13	6835CLZ	32-Pin QFN	13"	MDP0046
EL6835CLUZ		32-Pin TEP-QFN	-	XX
EL6835CLUZ-T13		32-Pin TEP-QFN	13"	XX

NOTE: Intersil Pb-free plus anneal products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which are RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.

Features

- Two channels for CD or DVD
- Voltage-controlled output current source requiring one external set resistor per channel
- Rise time = 0.8ns
- Fall time = 0.8ns
- DVD - Channel 2 to 275mA max
- DVD - Channel 3 to 195mA max
- DVD - Channel 4 to 115mA max
- CD - Channel 2 to 405mA max
- CD - Channel 3 to 290mA max
- On-chip oscillator with frequency and amplitude control by use of external resistors to ground
- Oscillator frequency to 600MHz
- Oscillator amplitude to 100mA_{P-P}
- Single +5V supply (±10%)
- Chip ENAs for power savings
- External LVDS termination
- Pb-Free plus anneal available (RoHS compliant)

Applications

- Super combo drives

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9001 quality systems.
Intersil Corporation's quality certifications can be viewed at www.intersil.com/design/quality

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com