

**E-Series RF 1:1 Transformer**  
0.05 – 3 MHz

**ETC1-1T-2**  
**V2**


**Features**

- 1:1 Impedance Ratio
- Surface Mount
- Tape and reel packaging available

**Description**

M/A-COM's ETC1-1T-2 is a 1:1 RF transformer in a low cost, surface mount package. Typical applications include single to balanced mode conversion and impedance matching. Parts are packaged in tape & reel.

**SM - 22 Package**



**Electrical Specifications:  $T_A = 25^\circ\text{C}$ ,  $Z_0 = 50\Omega$ <sup>1</sup>**

Parameter	Test Conditions	Frequency	Units	Min	Typ	Max
RF Frequency	—	0.05 - 3	MHz	—	—	—
Insertion Loss	—	0.05 - 3	dB	—	—	2.0
		0.2 - 3	dB	—	—	1.0
Amplitude Imbalance	—	0.05 - 3	dB	—	—	0.2
		0.2 - 3	dB	—	—	0.1
Phase Imbalance	—	0.05 - 3	Degrees	—	—	2°
		0.2 - 3	Degrees	—	—	1°

**Absolute Maximum Ratings<sup>1</sup>**

Parameter	Absolute Maximum
RF Power	250 mW
DC Current	30 mA
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +125°C

1. Operation of this device above any one of these parameters may cause permanent damage.

**Ordering Information**

Part Number	Package
ETC1-1T-2TR	Tape and Reel (2000 piece Reel)

E-Series RF 1:1 Transformer  
0.05 – 3 MHz

ETC1-1T-2  
V2

**Pin Configuration**

Pin No.	Function
1	Secondary
2	Secondary CT
3	Secondary Dot
4	Primary Dot
5	Primary

**Schematic**

