

2500 HN series

Single Output DC/DC Converter



DESCRIPTIONS

The 2500HN, single output power modules are 16 to 25 watt DC/DC converters available in a single output configuration providing 3.3 VDC to 15 VDC outputs in a compact, industry standard 2.0" X 1.6" X 0.4" package. These 400kHz, switching converters are available in 12, 24 and 48 VDC inputs making them one of the most versatile product lines in the market with efficiencies up to 87%. Advanced surface mount construction allows these converters to achieve outstanding thermal performance eliminating the need for thermal potting compounds and thereby enhancing manufacturing efficiency to reduce costs.

OUTPUT CHARACTERISTICS

	Min	Typ	Max	Unit/Comments
Output Voltage Set Point		±1		% Output voltage at nominal line & FL
Total Band Error	-2	+2		% Output voltage including line/load regulation setting
Line Regulation		±0.5		% Output voltage measured from min. input line to maximum
Load Regulation		±0.5		% Output voltage measured from FL to 10% load
Temperature Coefficient	±0.01			% per degree C
Ripple/Noise	60	100		mV p-p measured at 20 MHz bandwidth with ext. 1 μ F cap.
Output Voltage and Current				Refer to model selection chart
Load Transient Response		±2		% Deviation of Vout voltage for a 25% load change for 200 μ s
Short Circuit Protection				Indefinite, Automatic Recovery
Output Voltage Trim Range		±10		% Output voltage. Place ext. resistor between pins 8 - 6 to trim down. Between pins 8 - 7 to trim up.
Overvoltage Protection	125			%; Clamp type (5VDC output set at 6.8VDC)

MARTEK
POWER

www.martekpower.com

FEATURES

- Up to 87% Efficiency
- Single Output, 25 watt converter
- Available in 12, 24 and 48 VDC Inputs
- Industry Standard 2" X 1.6" X 0.4" Package
- Output Over Voltage, Input Over Voltage & Short Circuit Protection

INPUT CHARACTERISTICS

	Min	Typ	Max	Units/Comments
Input Voltage				
12 VDC Input Models	9	12	18	VDC
24 VDC Input Models	18	24	36	VDC
48 VDC Input Models	36	48	75	VDC
Under Voltage Shutdown				
12 VDC Input Models	8			VDC
24 VDC Input Models	17			VDC
48 VDC Input Models	33			VDC
Over Voltage Shutdown				
12 VDC Input Models	20			VDC
24 VDC Input Models	40			VDC
48 VDC Input Models	80			VDC
Full Load Input Current				
12 VDC Input Models		2.1		A
24 VDC Input Models		1.26		A
48 VDC Input Models		0.62		A
Input Fuse Requirements				
12 VDC Input Models	7			Amps; Slow blow type
24 VDC Input Models	4			Amps; Slow blow type
48 VDC Input Models	2			Amps; Slow blow type
Efficiency by Model				
2503S12HN	78			%; FL Nominal Line
2505S12HN	80			%; FL Nominal Line
2512S12HN	82			%; FL Nominal Line
2515S12HN	84			%; FL Nominal Line
2503S24HN	79			%; FL Nominal Line
2505S24HN	83			%; FL Nominal Line
2512S24HN	86			%; FL Nominal Line
2515S24HN	87			%; FL Nominal Line
2503S48HN	80			%; FL Nominal Line
2505S48HN	84			%; FL Nominal Line
2512S48HN	86			%; FL Nominal Line
2515S48HN	87			%; FL Nominal Line
Switching Frequency	360	400	440	kHz; Factory set
Remote Shut Down	Off	0	0.80	VDC; Referenced to input (-)
	On	3.5		VDC or open; Referenced to input (-)
Input - Output Capacitance		1000		pF
Input Filter				LC type
Isolation Voltage	1500			VDC
Isolation Resistance	100			MOhms

Martek Power reserves the right to change specifications without notice.


MODEL SELECTION CHART

	Input Voltage (VDC)	Output Voltage (VDC)	Full Load Output Current (A)
2503S12HN	12	3.3	5.0
2505S12HN	12	5.0	4.0
2512S12HN	12	12.0	1.7
2515S12HN	12	15.0	1.33
2503S24HN	24	3.3	6.0
2505S24HN	24	5.0	5.0
2512S24HN	24	12.0	2.0
2515S24HN	24	15.0	1.66
2503S48HN	48	3.3	6.0
2505S48HN	48	5.0	5.0
2512S48HN	48	12.0	2.0
2515S48HN	48	15.0	1.66

GENERAL CHARACTERISTICS

	Min	Typ	Max	Unit/Comments
Operating Temp. Range	-40		+110	°C; measured at baseplate
Storage Temp. Range	-55		+125	°C; measured at baseplate
Material Flammability				UL94V-0
Altitude: Operating			10,000	Feet
Non-Operating			40,000	Feet
Relative Humidity	5		95	% Humidity, non-condensing
Weight			22	Grams
Size				2" X 1.6" X 0.4"
Case Material				Black coated aluminum
Agency Approvals				UL/CUL1950, TUV, EN60950

OUTLINE DRAWING



PIN OUT CHART

Pins	FUNCTION
1	+ INPUT
2	- INPUT
4	CONTROL
5	NO PIN
6	+ OUTPUT
7	- OUTPUT
8	TRIM


Notes:

1. Unless otherwise specified dimensions are in inches (mm).
2. Controlling dimension in inch.
3. Tolerances

Inches	mm
X.XX = ± 0.02	X.X = ± 0.5
X.XXX = ± 0.010	X.XX = ± 0.25


All specifications are typical at nominal input, nominal load and 25° C unless otherwise specified.
External, low ESR, 33 microfarad (minimum) capacitor across output is recommended for operation.

How To ORDER




DERATING CURVES


MODEL 2500HN Single 3.3V & 5V (Without heatsink)




MODEL 2500HN Single 3.3V & 5V (With heatsink)



MODEL 2500HN Single 12V & 15V (Without heatsink)



MODEL 2500HN Single 12V & 15V (With heatsink)



OUTPUT VOLTAGE ADJUSTMENT (2500HN SINGLE SERIES)

The converter's output voltage may be trimmed by up to $\pm 5\%$ of the nominal output voltage.

TRIM UP

Trim output voltage up by connecting an external resistor between Pins 7 and 8. Use the following equation, reference Table 1 for variables A and B.

$$R_{adj-up} = \frac{A}{\Delta \%} - B \text{ (k}\Omega\text{)}$$

Example:

Trim 5% up for 12V Output units,
where A = 1.58, B = 20, $\Delta \% = 0.05$

$$R_{adj-up} = \frac{1.58}{0.05} - 20 = 11.6 \text{ k}\Omega$$




Table 1.

Output Voltage	A	B
3.3V	1.25	4.7
5V	1.00	10
12V	1.58	20
15V	1.67	20

TRIM DOWN

Trim output voltage down by connecting an external resistor between Pins 6 and 8. Use the following equation, reference Table 2 for variables C and D.

$$R_{adj-down} = \frac{C}{\Delta \%} - D \text{ (k}\Omega\text{)}$$

Example:

Trim 5% down for 15V Output units,
where C = 8.33, D = 30, $\Delta \% = 0.05$

$$R_{adj-down} = \frac{8.33}{0.05} - 30 = 136.6 \text{ k}\Omega$$




Table 2.

Output Voltage	C	D
3.3V	2.07	8.02
5V	1.00	12
12V	6.09	27.7
15V	8.33	30

2500 HN series



www.martekpower.com

Dual Output DC/DC Converter



DESCRIPTIONS

The 2500HN, dual output power modules are 20 to 25 watt DC/DC converters available in a dual output configuration providing both digital and analog outputs in a compact, industry standard 2.0" X 1.6" X 0.4" package. These 400kHz, switching converters are available in 12, 24 and 48 VDC inputs making them one of the most versatile product lines in the market with efficiencies up to 87%. Advanced surface mount construction allows these converters to achieve outstanding thermal performance eliminating the need for thermal potting compounds and thereby enhancing manufacturing efficiency to reduce costs.

OUTPUT CHARACTERISTICS

	Min	Typ	Max	Unit/Comments
Output Voltage Set Point		±1		% Output voltage at nominal line & FL
Total Band Error	-3	+3		% Output voltage including line/load regulation setting
Line Regulation		±0.5		% Output voltage measured from min. input line to maximum
Load Regulation		±1		% Output voltage measured from FL to 10% load
Temperature Coefficient	±0.01			% per degree C
Ripple/Noise	60	100		mV p-p measured at 20 MHz bandwidth with external 1 μF capacitor
Output Voltage and Current				Refer to model selection chart
Load Transient Response		±2		% deviation of Vout voltage for a 25% load change for 200μS
Short Circuit Protection				Indefinite, Automatic Recovery
Output Voltage Trim Range	±10			% Output voltage
Oversupply Protection	135			%; Clamp type

FEATURES

- Up to 87% Efficiency
- Dual Output, Up To 25 watt converter
- Available in 12, 24 and 48 VDC Inputs
- Industry Standard 2.0" X 1.6" X 0.4" Package
- Output Over Voltage, Input Over Voltage and Short Circuit Protection

INPUT CHARACTERISTICS

	Min	Typ	Max	Units/Comments
Input Voltage				
12 VDC Input Models	9	12	18	VDC
24 VDC Input Models	18	24	36	VDC
48 VDC Input Models	36	48	75	VDC
Under Voltage Shutdown				
12 VDC Input Models		8		VDC
24 VDC Input Models		17		VDC
48 VDC Input Models		33		VDC
Over Voltage Shutdown				
12 VDC Input Models		20		VDC
24 VDC Input Models		40		VDC
48 VDC Input Models		80		VDC
Full Load Input Current				
12 VDC Input Models			2.10	A
24 VDC Input Models			1.26	A
48 VDC Input Models			0.62	A
Input Fuse Requirements				
12 VDC Input Models			7	Amps; Slow blow type
24 VDC Input Models			4	Amps; Slow blow type
48 VDC Input Models			2	Amps; Slow blow type
Efficiency by Model				
2505D12HN		80		%; FL Nominal Line
2512D12HN		82		%; FL Nominal Line
2515D12HN		84		%; FL Nominal Line
2505D24HN		83		%; FL Nominal Line
2512D24HN		86		%; FL Nominal Line
2515D24HN		87		%; FL Nominal Line
2505D48HN		84		%; FL Nominal Line
2512D48HN		86		%; FL Nominal Line
2515D48HN		87		%; FL Nominal Line
Switching Frequency	360	400	440	kHz; Factory set
Remote Shut Down	Off	0	0.80	VDC; Referenced to input (-)
	On	3.5		VDC or open; Referenced to input (-)
Input - Output Capacitance				
		1000		pF
Input Filter				
Isolation Voltage		1500		VDC
Isolation Resistance		100		MΩms


MODEL SELECTION CHART

	Input Voltage (VDC)	Output Voltage (VDC)	Full Load Output Current (A)
2505D12HN	12	± 5	± 2.00
2512D12HN	12	± 12	± 0.85
2515D12HN	12	± 15	± 0.67
2505D24HN	24	± 5	± 2.50
2512D24HN	24	± 12	± 1.00
2515D24HN	24	± 15	± 0.83
2505D48HN	48	± 5	± 2.50
2512D48HN	48	± 12	± 1.00
2515D48HN	48	± 15	± 0.83

GENERAL CHARACTERISTICS

	Min	Typ	Max	Unit/Comments
Operating Temp. Range	-40		+110	°C; measured at baseplate
Storage Temp. Range	-55		+125	°C; measured at baseplate
Material Flammability				UL94V-0
Altitude: Operating Non-Operating			10,000 Feet 40,000 Feet	
Relative Humidity	5		95	% Humidity, non-condensing
Weight			22	Grams
Size				2" X 1.6" X 0.4"
Case Material				Black coated aluminum
Agency Approvals				UL/CUL1950, TUV, EN60950

OUTLINE DRAWING



PIN OUT CHART

Pins	FUNCTION
1	+ INPUT
2	- INPUT
4	CONTROL
5	+ OUTPUT
6	COMMON
7	- OUTPUT
8	TRIM


Notes:

1. Unless otherwise specified dimensions are in inches (mm).
2. Controlling dimension in inch.
3. Tolerances

Inches	mm
X.XX = ± 0.02	X.X = ± 0.5
X.XXX = ± 0.010	X.XX = ± 0.25


All specifications are typical at nominal input, nominal load and 25° C unless otherwise specified.
External, low ESR, 33 microfarad (minimum) capacitor across output is recommended for operation.

How To ORDER




DERATING CURVES


MODEL 2500HN Dual 3.3V & 5V (Without heatsink)




MODEL 2500HN Dual 3.3V & 5V (With heatsink)



MODEL 2500HN Single 12V & 15V (Without heatsink)



MODEL 2500HN Dual 12V & 15V (With heatsink)



OUTPUT VOLTAGE ADJUSTMENT (2500HN DUAL SERIES)

The converter's output voltage may be trimmed by up to $\pm 10\%$ of the nominal output voltage.

TRIM UP

Trim output voltage up by connecting an external resistor between Pins 7 and 8. Use the following equation, reference Table 1 for variable A.

$$R_{adj-up} = \frac{A}{\Delta \%} - 16 \text{ (k}\Omega\text{)}$$

Example:

Trim 5% up for 12V Output units,
where $A = 1.79$, $\Delta \% = 0.05$

$$R_{adj-up} = \frac{1.79}{0.05} - 16 = 19.8 \text{ k}\Omega$$

Both outputs trimmed up by 5%.




Table 1.

Output Voltage	A
$\pm 5V$	1.5
$\pm 12V$	1.79
$\pm 15V$	1.83

TRIM DOWN

Trim output voltage down by connecting an external resistor between Pins 5 and 8. Use the following equation, reference Table 2 for variables C and D.

$$R_{adj-down} = \frac{C}{\Delta \%} - D \text{ (k}\Omega\text{)}$$

Example:

Trim 5% down for 5V Output units,
where $C = 4.5$, $D = 22$, $\Delta \% = 0.05$

$$R_{adj-down} = \frac{4.5}{0.05} - 22 = 68 \text{ k}\Omega$$

Both outputs trimmed down by 5%.




Table 2.

Output Voltage	C	D
$\pm 5V$	4.5	22
$\pm 12V$	15.4	33.2
$\pm 15V$	20.2	38

2500 HN series

Triple Output DC/DC Converter



The 2500HN (high-density, non-encapsulated), triple output power modules are 25 watt DC/DC converters available in a triple output configuration providing both digital and analog outputs in a compact, industry standard 2" X 2" X 0.4" package. These 400kHz, switching converters are available in 12, 24 and 48 VDC inputs making them one of the most versatile product lines in the market with efficiencies up to 85%. Advanced surface mount construction allows these converters to achieve outstanding thermal performance eliminating the need for thermal potting compounds and thereby enhancing manufacturing efficiency to reduce costs.

OUTPUT CHARACTERISTICS

	Min	Typ	Max	Unit/Comments
Output Voltage Set Point:				
Main		±1		% Output voltage
Auxiliary		±3		
Total Band Error:				% measured at min.
Main	-2	+2		line and full load
Auxiliary	-5	+5		and, max. line and min. load
Line Regulation:		±0.5		% Output voltage measured from min. input line to max.
Load Regulation:				% Output voltage
V1		±1		measured from FL
V2 and V3		±5		to min load
Ripple/Noise				
Main	100			mV; p-p measured
Auxiliary	1%			@ 20 MHz bandwidth
Output Voltage and Current				Refer to model selection chart
Temperature Coefficient	±0.02			% Output Voltage
Short Circuit Protection				Continuous
Oversupply Protection	130			% Output Voltage; Clamp Type



www.martekpower.com

FEATURES

- Up to 85% Efficiency
- Triple Output, 25 watt converter
- Available in 12, 24 and 48 VDC Inputs
- Industry Standard 2" X 2" X 0.4" Package
- Over Voltage, Over Temperature and Short Circuit Protection

INPUT CHARACTERISTICS

	Min	Typ	Max	Unit/Comments
Input Voltage				
12 VDC Input Models	9	12	18	VDC
24 VDC Input Models	18	24	36	VDC
48 VDC Input Models	36	48	75	VDC
Over Voltage Shutdown				
12 VDC Input Models			18.9	VDC
24 VDC Input Models			37.8	VDC
48 VDC Input Models			78.8	VDC
Full Load Input Current				
12 VDC Input Models			2660	mA
24 VDC Input Models			1310	mA
48 VDC Input Models			650	mA
Efficiency by Model				
2505/12T12HN			83	%; FL Nominal Line
2505/15T12HN			83	%; FL Nominal Line
2505/12T24HN			84	%; FL Nominal Line
2505/15T24HN			84	%; FL Nominal Line
2505/12T48HN			85	%; FL Nominal Line
2505/15T48HN			85	%; FL Nominal Line
Switching Frequency	360	400	440	kHz; Factory set
Remote Shut Down				
Off		0	0.80	VDC; Referenced to input
On		3.5		input (-)
Input - Output Capacitance			2000	pF
Isolation Voltage			1500	VDC
Isolation Resistance			100	MOhms

MODEL SELECTION CHART


	Input Voltage (VDC)	Output Voltage (VDC)	Min. Output Current (mA)	Nominal Output Current (mA)	Max Output Current (mA)*
2505/12T12HN	12	5	300	3000	4000
		± 12	± 41	± 412	± 500
2505/15T12HN	12	5	300	3000	4000
		± 15	± 33	± 333	± 500
2505/12T24HN	24	5	300	3000	4000
		± 12	± 41	± 412	± 500
2505/15T24HN	24	5	300	3000	4000
		± 15	± 33	± 333	± 500
2505/12T48HN	48	5	300	3000	4000
		± 12	± 41	± 412	± 500
2505/15T48HN	48	5	300	3000	4000
		± 15	± 33	± 333	± 500

GENERAL CHARACTERISTICS

	Min	Typ	Max	Unit/Comments
Operating Temperature Range	-40		+105	°C measured at baseplate
Storage Temperature Range	-55		+125	°C
Over Temperature Shutdown	+110		+120	°C
Weight		30		Grams
Size				2" X 2" X 0.4"
Case Material				Black coated aluminum
Agency Approvals				UL/CUL1950 TUV, EN60950

* Total output power may not exceed 25 watts.

OUTLINE DRAWING



PIN OUT CHART

Pins	FUNCTION
1	REMOTE ON/OFF
3	- Vin
4	+ Vin
5	- V3out
6	COMMON
7	+ V1out
8	+V2out


Notes:

1. Unless otherwise specified dimensions are in inches (mm).
2. Controlling dimension in inch.
3. Tolerances

Inches	mm
X.XX = ±0.02	X.X = ±0.5
X.XXX= ±0.010	X.XX = ±0.25


All specifications are typical at nominal input, nominal load and 25° C unless otherwise specified.
External, low ESR, 10 microfarad (minimum) capacitor across output is recommended for operation.

How To ORDER



DERATING CURVES

MODEL 2500HN Triple (Without heatsink)



MODEL 2500HN Triple (With heatsink)

