

RF TRANSFORMERS WIDEBAND

12.5 to 1800 Ω

5 kHz to 2500 MHz

SURFACE MOUNT



MODEL NO.	Ω RATIO Note D	FREQUENCY (MHz)	INSERTION LOSS *			CASE STYLE Note B	CONNECTION	PRICE \$ Qty. (10-49)
			3 dB MHz	2 dB MHz	1 dB MHz			
◆ ADT1.5-17*	1.5	.5-1700	.5-1700	1-1500	2-1100	CD542	la	3.45***
◆◆ TC4-11	50/12.5	2-1100	—	2-1100	5-700	AT224	kp	4.95
◆ TC1.5-1	1.5	.5-2200	.5-2200	1-2000	2-1100	AT224	jt	4.95
◆○ TC9-1-75	75/8	0.3-475	0.3-475	0.5-450	0.9-370	AT224	kp	4.95
T2-1-KK81	2	.050-600	.050-600	.1-400	5-200	KK81	fd	3.95
T3-1-KK81	3	.5-800	.5-800	2-400	—	KK81	fd	4.45
T4-2-KK81	4	.2-600	.2-600	.5-500	2-250	KK81	fd	3.95
T8-1-KK81	8	.15-250	.15-250	.25-200	2-100	KK81	fd	3.95
T14-1-KK81	14	.2-150	.2-150	.5-100	2-50	KK81	fd	4.95
T2-1	2	.050-600	.050-600	.1-400	5-200	◆	fd	3.95
T3-1	3	.5-800	.5-800	2-400	—	◆	fd	4.45
T4-2	4	.2-600	.2-600	.5-500	2-250	◆	fd	3.95
T8-1	8	.15-250	.15-250	.25-200	2-100	◆	fd	3.95
T14-1	14	.2-150	.2-150	.5-100	2-50	◆	fd	4.95
TMO2-1	2	.050-600	.050-600	.1-400	5-200	A11	fe	7.95
TMO4-2	4	.2-600	.2-600	.5-500	2-250	A11	fe	7.95
TMO14-1	14	.2-150	.2-150	.5-100	2-50	A11	fe	8.45
FT1.22-1	1.22	.005-100	.005-100	.01-50	.05-25	H16	—	35.95
FT1.5-1	1.5	.1-400	.1-400	.5-200	1-100	H16	—	35.95
FTB1-1	1	.2-500	.2-500	.5-300	1-100	H16	—	36.95
FTB1-6	1	.01-125	.01-125	.05-50	.1-25	H16	—	36.95
■ FTB1-1-75	1	.5-500	.5-500	5-300	10-100	H16	—	36.95

NOTES:

- ◆ Two case styles available: Plug-in case style X65; Radial lead case style W38.
- * Insertion loss referenced to mid-band loss.
- ◆ Aqueous washable.
- Denotes 75 ohm model, for coax connector models 75 ohm BNC connectors are standard.
- Non-hermetic
- ◆ Stepdown, 50 ohm primary, 5.2 pF across secondary
- Stepdown, 75 ohm primary, 51 pF across secondary
- * Protected under U.S. Patent 6133525
- *** Price for quantities 10-49.
- A. General Quality Control Procedures, Environmental Specifications, Hi-Rel and MIL description are given in section 0, see "Mini-Circuits Guarantees Quality" article.
- B. Connector types and case mounted options, case finishes are given in section 0, see "Case Styles & Outline Drawings".
- C. Prices and Specifications subject to change without notice.
- D. Impedance ratio= secondary/primary.
- 1. Absolute power, voltage and current ratings:
 - 1a. RF input power: all models 0.25W except where noted (●● 1W rating; ●●● 2W rating)
 - 1b. DC current, 30mA
- 2. For ADT,ADTL, TC,TCM,TCML, and T series, operating temperature range is -20°C to +85°C.




Distribution Centers NORTH AMERICA 800-654-7949 • 417 335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

INTERNET <http://www.minicircuits.com>

ISO 9001 CERTIFIED

001122

Surface Mount □, Plug-In & Coaxial



Style X65



Standard W38



TMO

	MODEL NO.	Ω RATIO Note D	FREQUENCY (MHz)	INSERTION LOSS *			CASE STYLE Note B	CONNECTION	PRICE \$ Qty. (1-9)
				3 dB MHz	2 dB MHz	1 dB MHz			
F 	T-622-KK81	1:1:1	0.1-200	0.1-200	0.5-100	5-80	KK81	ff	3.25
	T-626-KK81	1:1:1	0.01-10	0.01-10	0.02-5	.04-2	KK81	ff	3.95
	T2-613-1-KK81	1:1:2	0.07-200	0.07-200	0.1-100	0.5-50	KK81	fg	1.95
	T-622	1:1:1	0.1-200	0.1-200	0.5-100	5-80	◆	ff	3.25
	T-626	1:1:1	0.01-10	0.01-10	0.02-5	.04-2	◆	ff	3.95
	T2-613-1	1:1:2	0.07-200	0.07-200	0.1-100	0.5-50	◆	fg	1.95
G 	◆ TCML1-11	1	600-1100	—	600-1100	700-1000	DB714	mh	4.95
	◆ TCML1-19	1	800-1900	800-1900	—	800-1400	DB714	mh	4.95
	◆ ADTL1-12*	1	20-1200	—	20-1200	50-1000	CD542	kn	2.95***
	◆ ADTL1-18-75*	1	5-1800	—	5-1800	25-1200	CD542	kn	2.95***
	◆ ADTL1-4-75*	1	0.5-1000	0.5-1000	1-600	5-400	CD542	kn	2.95***
	NEW ◆ ADTL2-18*	2	30-1800	30-1800	—	100-1500	CD542	kn	3.95***
H 	NEW ◆ TCM4-19	4	10-1900	10-1900	20-1000	30-700	DB714	gs	6.95
	◆ TCM4-25	4	500-2500	500-2500	700-1500	750-1200	DB714	gs	5.95

pin connections see case style outline drawings

PORT	fd	fe	ff	fg	gs	jt	kn	kp	la	mh
PRIMARY DOT	6	1	X1 Y2 Z3	X1 Y5 Z3	6	6	1	6	1	6
PRIMARY	3	6	X6 Y5 Z4	X2 Y6 Z4	4	4	3	3	3	4
PRIMARY CT	—	—	—	—	—	—	—	—	—	—
SECONDARY DOT	1	2	—	—	3	1	6	1	6	1
SECONDARY	3	6	—	—	1	4	4	3	3	3
SECONDARY CT	—	—	—	—	2	—	—	—	—	—
CASE EXT.	3	6	—	—	—	—	—	—	—	—
CASE GND	—	7,8	—	—	—	—	—	—	—	—
NOT USED	2,4,5	3,4,5	—	—	5	2,3,5	2,5	—	2,4,5	2,5
DEMO BOARD	—	—	—	—	—	TB-41	—	—	TB-40	—

NSN GUIDE

MCL NO.	NSN
FTB1-1-75	5950-01-132-8034
FTB1-6	5950-01-225-8773
FT1.5-1	5950-01-325-4686
T2-1	5950-01-106-1218
T4-2	5950-01-361-1794
TMO2-1	5950-01-183-6414
TMO4-2	5950-01-091-3553
TMO8-1	5950-01-442-8008



The Design Engineers Search Engine

Provides Actual Data Instantly
At: <http://www.minicircuits.com>

In Stock... Immediate Delivery
For Custom Versions Of Standard Models
Consult Our Applications Dept.

