

# CASE STYLES

## OUTLINE DIMENSIONS (inch/mm)

case no.	A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt. grams.	NOTES*
BV278	6.00 152.40	4.50 114.30	1.38 35.05	.15 3.81	5.700 144.78	.15 3.81	4.200 106.68	.38 9.65	2.25 57.15	.75 19.05	.75 19.05	.156 3.96							960	A8,D16
BW459	1.00 25.40	.75 19.05	.61 15.49	.38 9.65	.29 7.37	.25 6.35	.26 6.60	.35 8.89	.65 16.51	.688 17.48	.156 3.96	.13 3.30	1.07 27.18	.140 3.56					25	A4,A18,D17
BY493	1.38 35.05	1.00 25.40	.75 19.05	.125 3.18	.35 8.89	.52 13.21	.27 6.86	.78 19.81	.68 17.27	.125 3.18	1.50 38.10	1.281 32.54	1.000 25.40	.19 4.83	.11 2.79	.35 8.89			40	A4,D17
CA531	.052 1.32	.067 1.70	.106 2.69	.122 3.10	.040 1.02	.064 1.63	.087 2.21	.118 3.00	.067 1.70	.083 2.11	.033 .84	.042 1.07	.014 0.36	.020 0.51	.012 0.30	.007 0.18	.020 0.51	.012 0.30	.020	A13, F31
CB518	.270 6.86	.310 7.87	—	.090 2.29	.080 2.03	.055 1.40	.050 1.27	.018 0.46	.074 1.88	.030 0.76	.290 7.37								.30	A21, F32
CB539	.293 7.44	.300 7.62	—	.090 2.29	.085 2.16	.050 1.27	.050 1.27	.018 0.46	.067 1.70	.030 0.76	.315 8.00								.30	A21, F33
CC51	2.00 50.80	2.00 50.80	.75 19.05	.938 23.83	.13 3.30	1.750 44.45	.125 3.17	.38 9.65	1.00 25.40	1.25 31.75									120.0	A10, D11
CC258	2.00 50.80	2.00 50.80	.75 19.05	.938 23.83	.13 3.30	1.750 44.45	.125 3.17	.38 9.65	1.00 25.40	1.25 31.75									200.0	A4, D24
CD541	.280 7.11	.310 7.87	.220 5.58	.100 2.54	.082 2.08	.055 1.40	.100 2.54	.030 0.76	—	.065 1.65	.300 7.62								.40	A23, F34
CD542	.280 7.11	.310 7.87	.220 5.58	.100 2.54	.112 2.84	.055 1.40	.100 2.54	.030 0.76	—	.065 1.65	.300 7.62								.40	A23, F35
CD636	.280 7.11	.310 7.87	.220 5.58	.100 2.54	.162 4.11	.055 1.40	.100 2.54	.030 0.76	—	.065 1.65	.300 7.62								.45	A23, F45
CD637	.280 7.11	.310 7.87	.220 5.58	.100 2.54	.206 5.23	.055 1.40	.100 2.54	.030 0.76	—	.065 1.65	.300 7.62								.45	A23, F46
CF564	.282 7.16	.382 9.70	.069 1.75	.0083 0.21	.318 8.08	.002 0.05	.060 1.52	.030 0.76	.012 0.30	.09 2.29	.428 10.87	.060 1.52	.030 0.76	.282 7.16	.020 0.51	.010 0.25	.235 5.97	.120 3.05	.40	A13, F41
CG581	.375 9.53	.500 12.70	.230 5.84	.087 2.21	—	.150 3.81	.100 2.54	.510 12.95	.155 3.94	.093 2.36	.385 9.78	.040 1.02	.080 2.03	.024 0.61	.060 1.52				.60	A24, F36

tolerance .x±.1 .xx±.03 .xxx±.015 inch

oz. = grams x.0353

### \*NOTES:

- A. MATERIAL AND FINISH  
 A4. Case material: aluminum alloy. Finish: irridite per MIL-C-5541  
 A8. Case material: aluminum alloy. Finish: case irridite. Heat sink black anodize.  
 A10. Case material: aluminum alloy. Finish: grey paint or yellow irridite.  
 A13. Case material: plastic. Lead finish: tin-lead plate.  
 A18. Mounting bracket finish: irridite or clear anodize.  
 A21. Open-style, ceramic base. Termination finish: solder plate over nickel  
 A23. Case material: plastic. Lead finish: solder plate.  
 A24. Case material: ceramic. Lead finish: solder plate.
- D. CONNECTORS  
 D11. Connectors: Please specify: Type N or SMA  
 D16. Connectors: please specify. Unless otherwise noted SMA is standard for ZHL-2-12; for all other models BNC is standard. TNC, N, SMA available on request, consult factory.  
 D17. Connectors: Female SMA only.  
 D24. Connectors: female BNC standard. Type N or SMA consult factory.
- F. PACKAGING  
 F1-46. Tape and reel packaging available. See Tape & Reel packaging information for details.  
 To order Tape & Reel version add -TR suffix to model.

OUTLINE DRAWINGS

