


PRODUCT INFORMATION

870nm

1A229
High-Performance LED

Battery-Operated Equipment



This device operates at very low drive current, which makes it well suited for battery-operated equipment. In fact, it can be driven directly by TTL circuitry.



Optical and Electrical Characteristics (25°C Case Temperature)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Fiber-Coupled Power (Fig. 1, 2, & 3) (Table 1)	P_{fiber}	2	3		μW	$I_F=5\text{ mA}$ (Note 1) Fiber: 50/125 μm
Rise and Fall Time (10-90%)	t_r, t_f		85	100	ns	$I_F=5\text{ mA}$ (no bias) Graded Index NA=0.20
Bandwidth (3dB $_{e1}$)	f_c		4		MHz	$I_F=5\text{ mA}$
Peak Wavelength	λ_p	850	870	890	nm	$I_F=5\text{ mA}$
Spectral Width (FWHM)	$\Delta\lambda$		60		nm	$I_F=5\text{ mA}$
Forward Voltage (Fig. 4)	V_F		1.4	1.6	V	$I_F=5\text{ mA}$
Reverse Current	I_R			1	μA	$V_R=1\text{ V}$
Capacitance	C		250		pF	$V_R=0\text{ V}, f=1\text{ MHz}$

Note 1: Measured at the exit of 100 meters of fiber.



All dimensions in mm

The anode is in electrical contact with the case.

TO-46 Package With Lens

Absolute Maximum Ratings

PARAMETER	SYMBOL	LIMIT
Storage Temperature	T_{stg}	-55 to +125°C
Operating Temperature	T_{op}	-55 to +125°C
Electrical Power Dissipation	P_{tot}	16 mW
Continuous Forward Current ($f \leq 10\text{ kHz}$)	I_F	10 mA
Peak Forward Current (duty cycle $\leq 50\%$, $f \geq 1\text{ MHz}$)	I_{FRM}	20 mA
Reverse Voltage	V_R	1.5 V
Soldering Temperature (2mm from the case for 10 sec)	T_{slid}	260°C

Thermal Characteristics

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
Temperature Coefficient - Optical Power	dP/dT_j		-0.6		%/°C
Temperature Coefficient - Wavelength	$d\lambda/dT_j$		0.3		nm/°C

11930.11 1994-09-20



Europe: Tel (46) 8 58 02 45 00 Fax (46) 8 58 02 01 10
Tel (44) 1291 436180 Fax (44) 1291 436771

America: Tel 1-800-96MITEL Fax (613) 592-6909
Asia: Tel (65) 293 5312 Fax (65) 293 8527

Typical Fiber-Coupled Power			
Core Diameter/Cladding Diameter Numerical Aperture			
50/125 μm 0.20	62.5/125 μm 0.275	100/140 μm 0.29	200/230 μm 0.37
3 μW	8 μW	15 μW	20 μW

Table 1

