



# PRODUCT INFORMATION

820nm

**1A363**  
High-Performance LED

**Datacom**

This is the ultimate in high speed for 850 nm LEDs. It is designed for ATM 622 Mbps applications and offers an excellent price/performance ratio for cost-effective solutions. Its double-lens optical system results in optimum coupling of power into the fiber. And it matches the 1A354 PIN Photodiode.



**TO-46 Package With Lens**

## Optical and Electrical Characteristics (25° C Case Temperature)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION
Fiber-Coupled Power (Fig. 1, 2, & 3) (Table 1)	$P_{\text{fiber}}$	25	35		$\mu\text{W}$	$I_F=50\text{ mA}$ (Note 1) Fiber: 62.5/125 $\mu\text{m}$
Rise and Fall Time (10-90%)	$t_r, t_f$		0.5	0.7	ns	$I_F=50\text{ mA}$ (no bias) Graded Index
Bandwidth (3dB <sub>el</sub> )	$f_c$		700		MHz	$I_F=50\text{ mA}$ NA=0.275
Peak Wavelength	$\lambda_p$	800	820	840	nm	$I_F=50\text{ mA}$
Spectral Width (FWHM)	$\Delta\lambda$		50		nm	$I_F=50\text{ mA}$
Forward Voltage (Fig. 5)	$V_F$		2.0	2.2	V	$I_F=50\text{ mA}$
Reverse Current	$I_R$			20	$\mu\text{A}$	$V_R=1\text{ V}$
Capacitance	$C$		10		pF	$V_R=0\text{ V}, f=1\text{ MHz}$

**Note 1:** Measured at the exit of 100 meters of fiber.

## Absolute Maximum Ratings

PARAMETER	SYMBOL	LIMIT
Storage Temperature	$T_{\text{stg}}$	-55 to +125°C
Operating Temperature (derating: Fig. 4)	$T_{\text{op}}$	-55 to +125°C
Electrical Power Dissipation (derating: Fig. 4)	$P_{\text{tot}}$	130 mW
Continuous Forward Current ( $f \leq 10\text{ kHz}$ )	$I_F$	60 mA
Peak Forward Current (duty cycle $\leq 50\%$ , $f \geq 1\text{ MHz}$ )	$I_{\text{FRM}}$	100 mA
Reverse Voltage	$V_R$	1.5 V
Soldering Temperature (2mm from the case for 10sec)	$T_{\text{sld}}$	260°C

## Thermal Characteristics

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
Thermal Resistance - Infinite Heat Sink	$R_{\text{thjc}}$			200	°C/W
Thermal Resistance - No Heat Sink	$R_{\text{thja}}$			500	°C/W
Temperature Coefficient - Optical Power	$dP/dT_j$		-0.6		%/°C
Temperature Coefficient - Wavelength	$d\lambda/dT_j$		0.3		nm/°C

12703.11 1994-09-20



Europe: Tel (46) 8 58 02 45 00 Fax (46) 8 58 02 01 10  
Tel (44) 1291 436180 Fax (44) 1291 436771

America: Tel 1-800-96MITEL Fax (613) 592-6909  
Asia: Tel (65) 293 5312 Fax (65) 293 8527

**Typical Fiber-Coupled Power**

Core Diameter/Cladding Diameter Numerical Aperture	
50/125 $\mu\text{m}$ 0.20	62.5/125 $\mu\text{m}$ 0.275
20 $\mu\text{W}$	35 $\mu\text{W}$

Table 1

