



- Notes:**
- 1) Not to scale
  - 2) Dimensions in inches
  - 3) (Dimensions in millimeters)
  - 4) Ref. JEDEC Standard M0-150
  - 5) A & B Maximum dimensions include allowable mold flash

Dim	20-Pin		24-Pin		28-Pin	
	Min	Max	Min	Max	Min	Max
A		0.079 (2)	-	0.079 (2)		0.079 (2)
A <sub>1</sub>	0.004 (0.10)		0.004 (0.10)		0.004 (0.10)	
B	0.0087 (0.22)	0.013 (0.33)	0.0087 (0.22)	0.013 (0.33)	0.0087 (0.22)	0.013 (0.33)
C		0.008 (0.21)		0.008 (0.21)		0.008 (0.21)
D	0.27 (6.9)	0.295 (7.5)	0.31 (7.9)	0.33 (8.5)	0.39 (9.9)	0.41 (10.5)
E	0.2 (5.0)	0.22 (5.6)	0.2 (5.0)	0.22 (5.6)	0.2 (5.0)	0.22 (5.6)
e	0.025 BSC (0.65 BSC)		0.025 BSC (0.65 BSC)		0.025 BSC (0.65 BSC)	
F	0.049 REF (1.25 REF)		0.049 REF (1.25 REF)		0.049 REF (1.25 REF)	
G	0.065 (1.65)	0.073 (1.85)	0.065 (1.65)	0.073 (1.85)	0.065 (1.65)	0.073 (1.85)
H	0.29 (7.4)	0.32 (8.2)	0.29 (7.4)	0.32 (8.2)	0.29 (7.4)	0.32 (8.2)
L	0.022 (0.55)	0.037 (0.95)	0.022 (0.55)	0.037 (0.95)	0.022 (0.55)	0.037 (0.95)

Small Shrink Outline Package (SSOP) - N Suffix