

# 74AVC2T45

Dual-bit, dual-supply voltage level translator/transceiver;  
3-state

Rev. 7 — 8 February 2013

Product data sheet

## 1. General description

The 74AVC2T45 is a dual-bit, dual-supply transceiver that enables bidirectional level translation. It features two data input-output ports (nA and nB), a direction control input (DIR) and dual-supply pins ( $V_{CC(A)}$  and  $V_{CC(B)}$ ). Both  $V_{CC(A)}$  and  $V_{CC(B)}$  can be supplied at any voltage between 0.8 V and 3.6 V making the device suitable for translating between any of the low voltage nodes (0.8 V, 1.2 V, 1.5 V, 1.8 V, 2.5 V and 3.3 V). Pins nA and DIR are referenced to  $V_{CC(A)}$  and pins nB are referenced to  $V_{CC(B)}$ . A HIGH on DIR allows transmission from nA to nB and a LOW on DIR allows transmission from nB to nA.

The device is fully specified for partial power-down applications using  $I_{OFF}$ . The  $I_{OFF}$  circuitry disables the output, preventing any damaging backflow current through the device when it is powered down. In Suspend mode when either  $V_{CC(A)}$  or  $V_{CC(B)}$  are at GND level, both A and B are in the high-impedance OFF-state.

## 2. Features and benefits

- Wide supply voltage range:
  - ◆  $V_{CC(A)}$ : 0.8 V to 3.6 V
  - ◆  $V_{CC(B)}$ : 0.8 V to 3.6 V
- High noise immunity
- Complies with JEDEC standards:
  - ◆ JESD8-12 (0.8 V to 1.3 V)
  - ◆ JESD8-11 (0.9 V to 1.65 V)
  - ◆ JESD8-7 (1.2 V to 1.95 V)
  - ◆ JESD8-5 (1.8 V to 2.7 V)
  - ◆ JESD8-B (2.7 V to 3.6 V)
- ESD protection:
  - ◆ HBM JESD22-A114F Class 3B exceeds 8000 V
  - ◆ MM JESD22-A115-A exceeds 200 V
  - ◆ CDM JESD22-C101C exceeds 1000 V
- Maximum data rates:
  - ◆ 500 Mbit/s (1.8 V to 3.3 V translation)
  - ◆ 320 Mbit/s (<1.8 V to 3.3 V translation)
  - ◆ 320 Mbit/s (translate to 2.5 V or 1.8 V)
  - ◆ 280 Mbit/s (translate to 1.5 V)
  - ◆ 240 Mbit/s (translate to 1.2 V)
- Suspend mode
- Latch-up performance exceeds 100 mA per JESD 78 Class II



- Inputs accept voltages up to 3.6 V
- Low noise overshoot and undershoot < 10 % of  $V_{CC}$
- $I_{OFF}$  circuitry provides partial Power-down mode operation
- Multiple package options
- Specified from  $-40\text{ }^{\circ}\text{C}$  to  $+85\text{ }^{\circ}\text{C}$  and  $-40\text{ }^{\circ}\text{C}$  to  $+125\text{ }^{\circ}\text{C}$

### 3. Ordering information

Table 1. Ordering information

| Type number | Package   |        |   | Version  |
|-------------|---|--------|---|----------|
|             | Temperature range   | Name   | Description   |          |
| 74AVC2T45DP | $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ | TSSOP8 | plastic thin shrink small outline package; 8 leads; body width 3 mm; lead length 0.5 mm                 | SOT505-2 |
| 74AVC2T45DC | $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ | VSSOP8 | plastic very thin shrink small outline package; 8 leads; body width 2.3 mm                              | SOT765-1 |
| 74AVC2T45GT | $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ | XSON8  | plastic extremely thin small outline package; no leads; 8 terminals; body $1 \times 1.95 \times 0.5$ mm | SOT833-1 |
| 74AVC2T45GF | $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ | XSON8  | extremely thin small outline package; no leads; 8 terminals; body $1.35 \times 1 \times 0.5$ mm         | SOT1089  |
| 74AVC2T45GD | $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ | XSON8  | plastic extremely thin small outline package; no leads; 8 terminals; body $3 \times 2 \times 0.5$ mm    | SOT996-2 |
| 74AVC2T45GN | $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ | XSON8  | extremely thin small outline package; no leads; 8 terminals; body $1.2 \times 1.0 \times 0.35$ mm       | SOT1116  |
| 74AVC2T45GS | $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$ | XSON8  | extremely thin small outline package; no leads; 8 terminals; body $1.35 \times 1.0 \times 0.35$ mm      | SOT1203  |

### 4. Marking

Table 2. Marking

| Type number | Marking code <sup>[1]</sup> |
|-------------|-----------------------------|
| 74AVC2T45DP | B45                         |
| 74AVC2T45DC | B45                         |
| 74AVC2T45GT | B45                         |
| 74AVC2T45GF | B5                          |
| 74AVC2T45GD | B45                         |
| 74AVC2T45GN | B5                          |
| 74AVC2T45GS | B5                          |

[1] The pin 1 indicator is located on the lower left corner of the device, below the marking code.

### 5. Functional diagram




Fig 1. Logic symbol




Fig 2. Logic diagram

### 6. Pinning information

#### 6.1 Pinning




Fig 3. Pin configuration SOT505-2 and SOT765-1




Fig 4. Pin configuration SOT833-1, SOT1089, SOT1116 and SOT1203




Fig 5. Pin configuration SOT996-2

## 6.2 Pin description

**Table 3.** Pin description

| Symbol      | Pin | Description  |
|-------------|-----|--|
| $V_{CC(A)}$ | 1   | supply voltage A (referenced to pins 1A, 2A and DIR) |
| 1A          | 2   | data input or output                                 |
| 2A          | 3   | data input or output                                 |
| GND         | 4   | ground (0 V)   |
| DIR         | 5   | direction control                                    |
| 2B          | 6   | data input or output                                 |
| 1B          | 7   | data input or output                                 |
| $V_{CC(B)}$ | 8   | supply voltage B (referenced to pins 1B and 2B)      |

## 7. Functional description

**Table 4.** Function table<sup>[1]</sup>

| Supply voltage            | Input              | Input/output <sup>[2]</sup> |         |
|---------------------------|--------------------|-----------------------------|---------|
| $V_{CC(A)}$ , $V_{CC(B)}$ | DIR <sup>[3]</sup> | nA                          | nB      |
| 0.8 V to 3.6 V            | L                  | nA = nB                     | input   |
| 0.8 V to 3.6 V            | H                  | input                       | nB = nA |
| GND <sup>[4]</sup>        | X                  | Z                           | Z       |

[1] H = HIGH voltage level; L = LOW voltage level; X = don't care; Z = high-impedance OFF-state.

[2] The input circuit of the data I/O is always active.

[3] The DIR input circuit is referenced to  $V_{CC(A)}$ .

[4] If at least one of  $V_{CC(A)}$  or  $V_{CC(B)}$  is at GND level, the device goes into Suspend mode.

## 8. Limiting values

**Table 5. Limiting values**

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

| Symbol      | Parameter               | Conditions                    | Min            | Max             | Unit |
|-------------|-------------------------|-------------------------------|----------------|-----------------|------|
| $V_{CC(A)}$ | supply voltage A        |                               | -0.5           | +4.6            | V    |
| $V_{CC(B)}$ | supply voltage B        |                               | -0.5           | +4.6            | V    |
| $I_{IK}$    | input clamping current  | $V_I < 0$ V                   | -50            | -               | mA   |
| $V_I$       | input voltage           |                               | [1] -0.5       | +4.6            | V    |
| $I_{OK}$    | output clamping current | $V_O < 0$ V                   | -50            | -               | mA   |
| $V_O$       | output voltage          | Active mode                   | [1][2][3] -0.5 | $V_{CCO} + 0.5$ | V    |
|             |                         | Suspend or 3-state mode       | [1] -0.5       | +4.6            | V    |
| $I_O$       | output current          | $V_O = 0$ V to $V_{CCO}$      | -              | $\pm 50$        | mA   |
| $I_{CC}$    | supply current          | $I_{CC(A)}$ or $I_{CC(B)}$    | -              | 100             | mA   |
| $I_{GND}$   | ground current          |                               | -100           | -               | mA   |
| $T_{stg}$   | storage temperature     |                               | -65            | +150            | °C   |
| $P_{tot}$   | total power dissipation | $T_{amb} = -40$ °C to +125 °C | [4] -          | 250             | mW   |

[1] The minimum input voltage rating and output voltage ratings may be exceeded if the input and output current ratings are observed.

[2]  $V_{CCO}$  is the supply voltage associated with the output port.

[3]  $V_{CCO} + 0.5$  V should not exceed 4.6 V.

[4] For TSSOP8 package: above 55 °C the value of  $P_{tot}$  derates linearly at 2.5 mW/K.  
 For VSSOP8 package: above 110 °C the value of  $P_{tot}$  derates linearly with 8 mW/K.  
 For XSON8 packages: above 118 °C the value of  $P_{tot}$  derates linearly with 7.8 mW/K.

## 9. Recommended operating conditions

**Table 6. Recommended operating conditions**

| Symbol              | Parameter                           | Conditions                 | Min   | Max       | Unit |
|---------------------|-------------------------------------|----------------------------|-------|-----------|------|
| $V_{CC(A)}$         | supply voltage A                    |                            | 0.8   | 3.6       | V    |
| $V_{CC(B)}$         | supply voltage B                    |                            | 0.8   | 3.6       | V    |
| $V_I$               | input voltage                       |                            | 0     | 3.6       | V    |
| $V_O$               | output voltage                      | Active mode                | [1] 0 | $V_{CCO}$ | V    |
|                     |                                     | Suspend or 3-state mode    | 0     | 3.6       | V    |
| $T_{amb}$           | ambient temperature                 |                            | -40   | +125      | °C   |
| $\Delta t/\Delta V$ | input transition rise and fall rate | $V_{CCI} = 0.8$ V to 3.6 V | [2] - | 5         | ns/V |

[1]  $V_{CCO}$  is the supply voltage associated with the output port.

[2]  $V_{CCI}$  is the supply voltage associated with the input port.

## 10. Static characteristics

**Table 7. Typical static characteristics at  $T_{amb} = 25\text{ °C}$  [1][2]**

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

| Symbol    | Parameter                 | Conditions   | Min | Typ         | Max        | Unit          |
|-----------|---------------------------|--|-----|-------------|------------|---------------|
| $V_{OH}$  | HIGH-level output voltage | $V_I = V_{IH}$ or $V_{IL}$<br>$I_O = -1.5\text{ mA}$ ; $V_{CC(A)} = V_{CC(B)} = 0.8\text{ V}$                                      | -   | 0.69        | -          | V             |
| $V_{OL}$  | LOW-level output voltage  | $V_I = V_{IH}$ or $V_{IL}$<br>$I_O = 1.5\text{ mA}$ ; $V_{CC(A)} = V_{CC(B)} = 0.8\text{ V}$                                       | -   | 0.07        | -          | V             |
| $I_I$     | input leakage current     | DIR input; $V_I = 0\text{ V}$ or $3.6\text{ V}$ ;<br>$V_{CC(A)} = V_{CC(B)} = 0.8\text{ V}$ to $3.6\text{ V}$                      | -   | $\pm 0.025$ | $\pm 0.25$ | $\mu\text{A}$ |
| $I_{OZ}$  | OFF-state output current  | A or B port; $V_O = 0\text{ V}$ or $V_{CCO}$ ;<br>$V_{CC(A)} = V_{CC(B)} = 0.8\text{ V}$ to $3.6\text{ V}$                         | [3] | $\pm 0.5$   | $\pm 2.5$  | $\mu\text{A}$ |
| $I_{OFF}$ | power-off leakage current | A port; $V_I$ or $V_O = 0\text{ V}$ to $3.6\text{ V}$ ;<br>$V_{CC(A)} = 0\text{ V}$ ; $V_{CC(B)} = 0.8\text{ V}$ to $3.6\text{ V}$ | -   | $\pm 0.1$   | $\pm 1$    | $\mu\text{A}$ |
|           |                           | B port; $V_I$ or $V_O = 0\text{ V}$ to $3.6\text{ V}$ ;<br>$V_{CC(B)} = 0\text{ V}$ ; $V_{CC(A)} = 0.8\text{ V}$ to $3.6\text{ V}$ | -   | $\pm 0.1$   | $\pm 1$    | $\mu\text{A}$ |
| $C_I$     | input capacitance         | DIR input; $V_I = 0\text{ V}$ or $3.3\text{ V}$ ;<br>$V_{CC(A)} = V_{CC(B)} = 3.3\text{ V}$  | -   | 1.0         | -          | pF            |
| $C_{I/O}$ | input/output capacitance  | A and B port; Suspend mode;<br>$V_O = V_{CCO}$ or GND; $V_{CC(A)} = V_{CC(B)} = 3.3\text{ V}$                                      | -   | 4.0         | -          | pF            |

[1]  $V_{CCO}$  is the supply voltage associated with the output port.

[2]  $V_{CCI}$  is the supply voltage associated with the data input port.

[3] For I/O ports, the parameter  $I_{OZ}$  includes the input leakage current.

**Table 8. Static characteristics [1][2]**

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

| Symbol   | Parameter                | Conditions                                    | -40 °C to +85 °C |     | -40 °C to +125 °C |     | Unit |
|----------|--------------------------|---|------------------|-----|-------------------|-----|------|
|          |                          |   | Min              | Max | Min               | Max |      |
| $V_{IH}$ | HIGH-level input voltage | data input                                    |                  |     |                   |     |      |
|          |                          | $V_{CCI} = 0.8\text{ V}$                      | $0.70V_{CCI}$    | -   | $0.70V_{CCI}$     | -   | V    |
|          |                          | $V_{CCI} = 1.1\text{ V}$ to $1.95\text{ V}$   | $0.65V_{CCI}$    | -   | $0.65V_{CCI}$     | -   | V    |
|          |                          | $V_{CCI} = 2.3\text{ V}$ to $2.7\text{ V}$    | 1.6              | -   | 1.6               | -   | V    |
|          |                          | $V_{CCI} = 3.0\text{ V}$ to $3.6\text{ V}$    | 2                | -   | 2                 | -   | V    |
|          |                          | DIR input                                     |                  |     |                   |     |      |
|          |                          | $V_{CC(A)} = 0.8\text{ V}$                    | $0.70V_{CC(A)}$  | -   | $0.70V_{CC(A)}$   | -   | V    |
|          |                          | $V_{CC(A)} = 1.1\text{ V}$ to $1.95\text{ V}$ | $0.65V_{CC(A)}$  | -   | $0.65V_{CC(A)}$   | -   | V    |
|          |                          | $V_{CC(A)} = 2.3\text{ V}$ to $2.7\text{ V}$  | 1.6              | -   | 1.6               | -   | V    |
|          |                          | $V_{CC(A)} = 3.0\text{ V}$ to $3.6\text{ V}$  | 2                | -   | 2                 | -   | V    |

**Table 8. Static characteristics ...continued** [\[1\]\[2\]](#)

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

| Symbol           | Parameter                 | Conditions  | -40 °C to +85 °C       |                        | -40 °C to +125 °C      |                        | Unit |
|------------------|---------------------------|---|------------------------|------------------------|------------------------|------------------------|------|
|                  |                           |   | Min                    | Max                    | Min                    | Max                    |      |
| V <sub>IL</sub>  | LOW-level input voltage   | data input  |                        |                        |                        |                        |      |
|                  |                           | V <sub>CCI</sub> = 0.8 V  | -                      | 0.30V <sub>CCI</sub>   | -                      | 0.30V <sub>CCI</sub>   | V    |
|                  |                           | V <sub>CCI</sub> = 1.1 V to 1.95 V  | -                      | 0.35V <sub>CCI</sub>   | -                      | 0.35V <sub>CCI</sub>   | V    |
|                  |                           | V <sub>CCI</sub> = 2.3 V to 2.7 V   | -                      | 0.7                    | -                      | 0.7                    | V    |
|                  |                           | V <sub>CCI</sub> = 3.0 V to 3.6 V   | -                      | 0.9                    | -                      | 0.9                    | V    |
|                  |                           | DIR input   |                        |                        |                        |                        |      |
|                  |                           | V <sub>CC(A)</sub> = 0.8 V  | -                      | 0.30V <sub>CC(A)</sub> | -                      | 0.30V <sub>CC(A)</sub> | V    |
|                  |                           | V <sub>CC(A)</sub> = 1.1 V to 1.95 V  | -                      | 0.35V <sub>CC(A)</sub> | -                      | 0.35V <sub>CC(A)</sub> | V    |
| V <sub>OH</sub>  | HIGH-level output voltage | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>   |                        |                        |                        |                        |      |
|                  |                           | I <sub>O</sub> = -100 μA;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 0.8 V to 3.6 V                                     | V <sub>CCO</sub> - 0.1 | -                      | V <sub>CCO</sub> - 0.1 | -                      | V    |
|                  |                           | I <sub>O</sub> = -3 mA;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 1.1 V  | 0.85                   | -                      | 0.85                   | -                      | V    |
|                  |                           | I <sub>O</sub> = -6 mA;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 1.4 V  | 1.05                   | -                      | 1.05                   | -                      | V    |
|                  |                           | I <sub>O</sub> = -8 mA;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 1.65 V   | 1.2                    | -                      | 1.2                    | -                      | V    |
|                  |                           | I <sub>O</sub> = -9 mA;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 2.3 V  | 1.75                   | -                      | 1.75                   | -                      | V    |
|                  |                           | I <sub>O</sub> = -12 mA;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 3.0 V   | 2.3                    | -                      | 2.3                    | -                      | V    |
| V <sub>OL</sub>  | LOW-level output voltage  | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub>   |                        |                        |                        |                        |      |
|                  |                           | I <sub>O</sub> = 100 μA;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 0.8 V to 3.6 V                                      | -                      | 0.1                    | -                      | 0.1                    | V    |
|                  |                           | I <sub>O</sub> = 3 mA; V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 1.1 V  | -                      | 0.25                   | -                      | 0.25                   | V    |
|                  |                           | I <sub>O</sub> = 6 mA; V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 1.4 V  | -                      | 0.35                   | -                      | 0.35                   | V    |
|                  |                           | I <sub>O</sub> = 8 mA;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 1.65 V  | -                      | 0.45                   | -                      | 0.45                   | V    |
|                  |                           | I <sub>O</sub> = 9 mA; V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 2.3 V  | -                      | 0.55                   | -                      | 0.55                   | V    |
| I <sub>I</sub>   | input leakage current     | I <sub>O</sub> = 12 mA;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 3.0 V  | -                      | 0.7                    | -                      | 0.7                    | V    |
|                  |                           | DIR input; V <sub>I</sub> = 0 V or 3.6 V;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 0.8 V to 3.6 V                     | -                      | ±1                     | -                      | ±1.5                   | μA   |
| I <sub>OZ</sub>  | OFF-state output current  | A or B port; V <sub>O</sub> = 0 V or V <sub>CCO</sub> ;<br>V <sub>CC(A)</sub> = V <sub>CC(B)</sub> = 3.6 V                | -                      | ±5                     | -                      | ±7.5                   | μA   |
| I <sub>OFF</sub> | power-off leakage current | A port; V <sub>I</sub> or V <sub>O</sub> = 0 V to 3.6 V;<br>V <sub>CC(A)</sub> = 0 V; V <sub>CC(B)</sub> = 0.8 V to 3.6 V | -                      | ±5                     | -                      | ±35                    | μA   |
|                  |                           | B port; V <sub>I</sub> or V <sub>O</sub> = 0 V to 3.6 V;<br>V <sub>CC(B)</sub> = 0 V; V <sub>CC(A)</sub> = 0.8 V to 3.6 V | -                      | ±5                     | -                      | ±35                    | μA   |

**Table 8. Static characteristics ...continued**<sup>[1][2]</sup>

At recommended operating conditions; voltages are referenced to GND (ground = 0 V).

| Symbol          | Parameter      | Conditions   | -40 °C to +85 °C |     | -40 °C to +125 °C |      | Unit |
|-----------------|----------------|--|------------------|-----|-------------------|------|------|
|                 |                |  | Min              | Max | Min               | Max  |      |
| I <sub>CC</sub> | supply current | A port; V <sub>I</sub> = 0 V or V <sub>CCI</sub> ; I <sub>O</sub> = 0 A  |                  |     |                   |      |      |
|                 |                | V <sub>CC(A)</sub> = 0.8 V to 3.6 V;<br>V <sub>CC(B)</sub> = 0.8 V to 3.6 V  | -                | 8   | -                 | 11.5 | μA   |
|                 |                | V <sub>CC(A)</sub> = 3.6 V; V <sub>CC(B)</sub> = 0 V   | -                | 8   | -                 | 11.5 | μA   |
|                 |                | V <sub>CC(A)</sub> = 0 V; V <sub>CC(B)</sub> = 3.6 V   | -2               | -   | -8                | -    | μA   |
|                 |                | B port; V <sub>I</sub> = 0 V or V <sub>CCI</sub> ; I <sub>O</sub> = 0 A  |                  |     |                   |      |      |
|                 |                | V <sub>CC(A)</sub> = 0.8 V to 3.6 V;<br>V <sub>CC(B)</sub> = 0.8 V to 3.6 V  | -                | 8   | -                 | 11.5 | μA   |
|                 |                | V <sub>CC(A)</sub> = 3.6 V; V <sub>CC(B)</sub> = 0 V   | -2               | -   | -8                | -    | μA   |
|                 |                | V <sub>CC(A)</sub> = 0 V; V <sub>CC(B)</sub> = 3.6 V   | -                | 8   | -                 | 11.5 | μA   |
|                 |                | A plus B port (I <sub>CC(A)</sub> + I <sub>CC(B)</sub> );<br>I <sub>O</sub> = 0 A; V <sub>I</sub> = 0 V or V <sub>CCI</sub> ;<br>V <sub>CC(A)</sub> = 0.8 V to 3.6 V;<br>V <sub>CC(B)</sub> = 0.8 V to 3.6 V | -                | 16  | -                 | 23   | μA   |

- [1] V<sub>CCO</sub> is the supply voltage associated with the output port.
- [2] V<sub>CCI</sub> is the supply voltage associated with the data input port.
- [3] For I/O ports, the parameter I<sub>OZ</sub> includes the input leakage current.



## 11. Dynamic characteristics

**Table 9. Typical dynamic characteristics at  $V_{CC(A)} = 0.8\text{ V}$  and  $T_{amb} = 25\text{ °C}$  [1]**

Voltages are referenced to GND (ground = 0 V); for test circuit see [Figure 8](#); for wave forms see [Figure 6](#) and [Figure 7](#)

| Symbol    | Parameter         | Conditions | $V_{CC(B)}$ |       |       |       |       |       | Unit |
|-----------|-------------------|------------|-------------|-------|-------|-------|-------|-------|------|
|           |                   |            | 0.8 V       | 1.2 V | 1.5 V | 1.8 V | 2.5 V | 3.3 V |      |
| $t_{pd}$  | propagation delay | A to B     | 15.5        | 8.1   | 7.6   | 7.7   | 8.4   | 9.2   | ns   |
|           |                   | B to A     | 15.5        | 12.7  | 12.3  | 12.2  | 12.0  | 11.8  | ns   |
| $t_{dis}$ | disable time      | DIR to A   | 12.2        | 12.2  | 12.2  | 12.2  | 12.2  | 12.2  | ns   |
|           |                   | DIR to B   | 11.7        | 7.9   | 7.6   | 8.2   | 8.7   | 10.2  | ns   |
| $t_{en}$  | enable time       | DIR to A   | 27.2        | 20.6  | 19.9  | 20.4  | 20.7  | 22.0  | ns   |
|           |                   | DIR to B   | 27.7        | 20.3  | 19.8  | 19.9  | 20.6  | 21.4  | ns   |

- [1]  $t_{pd}$  is the same as  $t_{PLH}$  and  $t_{PHL}$ ;  $t_{dis}$  is the same as  $t_{PLZ}$  and  $t_{PHZ}$ ;  $t_{en}$  is the same as  $t_{PZL}$  and  $t_{PZH}$ .  
 $t_{en}$  is a calculated value using the formula shown in [Section 13.4 "Enable times"](#)

**Table 10. Typical dynamic characteristics at  $V_{CC(B)} = 0.8\text{ V}$  and  $T_{amb} = 25\text{ °C}$  [1]**

Voltages are referenced to GND (ground = 0 V); for test circuit see [Figure 8](#); for wave forms see [Figure 6](#) and [Figure 7](#)

| Symbol    | Parameter         | Conditions | $V_{CC(A)}$ |       |       |       |       |       | Unit |
|-----------|-------------------|------------|-------------|-------|-------|-------|-------|-------|------|
|           |                   |            | 0.8 V       | 1.2 V | 1.5 V | 1.8 V | 2.5 V | 3.3 V |      |
| $t_{pd}$  | propagation delay | A to B     | 15.5        | 12.7  | 12.3  | 12.2  | 12.0  | 11.8  | ns   |
|           |                   | B to A     | 15.5        | 8.1   | 7.6   | 7.7   | 8.4   | 9.2   | ns   |
| $t_{dis}$ | disable time      | DIR to A   | 12.2        | 4.9   | 3.8   | 3.7   | 2.8   | 3.4   | ns   |
|           |                   | DIR to B   | 11.7        | 9.2   | 9.0   | 8.8   | 8.7   | 8.6   | ns   |
| $t_{en}$  | enable time       | DIR to A   | 27.2        | 17.3  | 16.6  | 16.5  | 17.1  | 17.8  | ns   |
|           |                   | DIR to B   | 27.7        | 17.6  | 16.1  | 15.9  | 14.8  | 15.2  | ns   |

- [1]  $t_{pd}$  is the same as  $t_{PLH}$  and  $t_{PHL}$ ;  $t_{dis}$  is the same as  $t_{PLZ}$  and  $t_{PHZ}$ ;  $t_{en}$  is the same as  $t_{PZL}$  and  $t_{PZH}$ .  
 $t_{en}$  is a calculated value using the formula shown in [Section 13.4 "Enable times"](#)

**Table 11. Typical power dissipation capacitance at  $V_{CC(A)} = V_{CC(B)}$  and  $T_{amb} = 25\text{ °C}$  [1][2]**

Voltages are referenced to GND (ground = 0 V).

| Symbol   | Parameter                     | Conditions  | $V_{CC(A)}$ and $V_{CC(B)}$ |       |       |       |       |       | Unit |
|----------|-------------------------------|---|-----------------------------|-------|-------|-------|-------|-------|------|
|          |                               |   | 0.8 V                       | 1.2 V | 1.5 V | 1.8 V | 2.5 V | 3.3 V |      |
| $C_{PD}$ | power dissipation capacitance | A port: (direction A to B);<br>B port: (direction B to A) | 1                           | 2     | 2     | 2     | 2     | 2     | pF   |
|          |                               | A port: (direction B to A);<br>B port: (direction A to B) | 9                           | 11    | 11    | 12    | 14    | 17    | pF   |

- [1]  $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu\text{W}$ ).

$$P_D = C_{PD} \times V_{CC}^2 \times f_i \times N + \sum(C_L \times V_{CC}^2 \times f_o) \text{ where:}$$

$f_i$  = input frequency in MHz;

$f_o$  = output frequency in MHz;

$C_L$  = load capacitance in pF;

$V_{CC}$  = supply voltage in V;

$N$  = number of inputs switching;

$\sum(C_L \times V_{CC}^2 \times f_o)$  = sum of the outputs.

- [2]  $f_i = 10\text{ MHz}$ ;  $V_i = \text{GND to } V_{CC}$ ;  $t_r = t_f = 1\text{ ns}$ ;  $C_L = 0\text{ pF}$ ;  $R_L = \infty\ \Omega$ .

**Table 12. Dynamic characteristics for temperature range -40 °C to +85 °C [1]**

Voltages are referenced to GND (ground = 0 V); for test circuit see [Figure 8](#); for wave forms see [Figure 6](#) and [Figure 7](#).

| Symbol                                      | Parameter         | Conditions | V <sub>CC(B)</sub> |      |               |      |                |      |               |      |               |      | Unit |
|---|-------------------|------------|--------------------|------|---------------|------|----------------|------|---------------|------|---------------|------|------|
|   |                   |            | 1.2 V ± 0.1 V      |      | 1.5 V ± 0.1 V |      | 1.8 V ± 0.15 V |      | 2.5 V ± 0.2 V |      | 3.3 V ± 0.3 V |      |      |
|   |                   |            | Min                | Max  | Min           | Max  | Min            | Max  | Min           | Max  | Min           | Max  |      |
| <b>V<sub>CC(A)</sub> = 1.1 V to 1.3 V</b>   |                   |            |                    |      |               |      |                |      |               |      |               |      |      |
| t <sub>pd</sub>                             | propagation delay | A to B     | 1.0                | 9.0  | 0.7           | 6.8  | 0.6            | 6.1  | 0.5           | 5.7  | 0.5           | 6.1  | ns   |
|   |                   | B to A     | 1.0                | 9.0  | 0.8           | 8.0  | 0.7            | 7.7  | 0.6           | 7.2  | 0.5           | 7.1  | ns   |
| t <sub>dis</sub>                            | disable time      | DIR to A   | 2.2                | 8.8  | 2.2           | 8.8  | 2.2            | 8.8  | 2.2           | 8.8  | 2.2           | 8.8  | ns   |
|   |                   | DIR to B   | 2.2                | 8.4  | 1.8           | 6.7  | 2.0            | 6.9  | 1.7           | 6.2  | 2.4           | 7.2  | ns   |
| t <sub>en</sub>                             | enable time       | DIR to A   | -                  | 17.4 | -             | 14.7 | -              | 14.6 | -             | 13.4 | -             | 14.3 | ns   |
|   |                   | DIR to B   | -                  | 17.8 | -             | 15.6 | -              | 14.9 | -             | 14.5 | -             | 14.9 | ns   |
| <b>V<sub>CC(A)</sub> = 1.4 V to 1.6 V</b>   |                   |            |                    |      |               |      |                |      |               |      |               |      |      |
| t <sub>pd</sub>                             | propagation delay | A to B     | 1.0                | 8.0  | 0.7           | 5.4  | 0.6            | 4.6  | 0.5           | 3.7  | 0.5           | 3.5  | ns   |
|   |                   | B to A     | 1.0                | 6.8  | 0.8           | 5.4  | 0.7            | 5.1  | 0.6           | 4.7  | 0.5           | 4.5  | ns   |
| t <sub>dis</sub>                            | disable time      | DIR to A   | 1.6                | 6.3  | 1.6           | 6.3  | 1.6            | 6.3  | 1.6           | 6.3  | 1.6           | 6.3  | ns   |
|   |                   | DIR to B   | 2.0                | 7.6  | 1.8           | 5.9  | 1.6            | 6.0  | 1.2           | 4.8  | 1.7           | 5.5  | ns   |
| t <sub>en</sub>                             | enable time       | DIR to A   | -                  | 14.4 | -             | 11.3 | -              | 11.1 | -             | 9.5  | -             | 10.0 | ns   |
|   |                   | DIR to B   | -                  | 14.3 | -             | 11.7 | -              | 10.9 | -             | 10.0 | -             | 9.8  | ns   |
| <b>V<sub>CC(A)</sub> = 1.65 V to 1.95 V</b> |                   |            |                    |      |               |      |                |      |               |      |               |      |      |
| t <sub>pd</sub>                             | propagation delay | A to B     | 1.0                | 7.7  | 0.6           | 5.1  | 0.5            | 4.3  | 0.5           | 3.4  | 0.5           | 3.1  | ns   |
|   |                   | B to A     | 1.0                | 6.1  | 0.7           | 4.6  | 0.5            | 4.4  | 0.5           | 3.9  | 0.5           | 3.7  | ns   |
| t <sub>dis</sub>                            | disable time      | DIR to A   | 1.6                | 5.5  | 1.6           | 5.5  | 1.6            | 5.5  | 1.6           | 5.5  | 1.6           | 5.5  | ns   |
|   |                   | DIR to B   | 1.8                | 7.7  | 1.8           | 5.7  | 1.4            | 5.8  | 1.0           | 4.5  | 1.5           | 5.2  | ns   |
| t <sub>en</sub>                             | enable time       | DIR to A   | -                  | 13.8 | -             | 10.3 | -              | 10.2 | -             | 8.4  | -             | 8.9  | ns   |
|   |                   | DIR to B   | -                  | 13.2 | -             | 10.6 | -              | 9.8  | -             | 8.9  | -             | 8.6  | ns   |
| <b>V<sub>CC(A)</sub> = 2.3 V to 2.7 V</b>   |                   |            |                    |      |               |      |                |      |               |      |               |      |      |
| t <sub>pd</sub>                             | propagation delay | A to B     | 1.0                | 7.2  | 0.5           | 4.7  | 0.5            | 3.9  | 0.5           | 3.0  | 0.5           | 2.6  | ns   |
|   |                   | B to A     | 1.0                | 5.7  | 0.6           | 3.8  | 0.5            | 3.4  | 0.5           | 3.0  | 0.5           | 2.8  | ns   |
| t <sub>dis</sub>                            | disable time      | DIR to A   | 1.5                | 4.2  | 1.5           | 4.2  | 1.5            | 4.2  | 1.5           | 4.2  | 1.5           | 4.2  | ns   |
|   |                   | DIR to B   | 1.7                | 7.3  | 2.0           | 5.2  | 1.5            | 5.1  | 0.6           | 4.2  | 1.1           | 4.8  | ns   |
| t <sub>en</sub>                             | enable time       | DIR to A   | -                  | 13.0 | -             | 9.0  | -              | 8.5  | -             | 7.2  | -             | 7.6  | ns   |
|   |                   | DIR to B   | -                  | 11.4 | -             | 8.9  | -              | 8.1  | -             | 7.2  | -             | 6.8  | ns   |
| <b>V<sub>CC(A)</sub> = 3.0 V to 3.6 V</b>   |                   |            |                    |      |               |      |                |      |               |      |               |      |      |
| t <sub>pd</sub>                             | propagation delay | A to B     | 1.0                | 7.1  | 0.5           | 4.5  | 0.5            | 3.7  | 0.5           | 2.8  | 0.5           | 2.4  | ns   |
|   |                   | B to A     | 1.0                | 6.1  | 0.6           | 3.6  | 0.5            | 3.1  | 0.5           | 2.6  | 0.5           | 2.4  | ns   |
| t <sub>dis</sub>                            | disable time      | DIR to A   | 1.5                | 4.7  | 1.5           | 4.7  | 1.5            | 4.7  | 1.5           | 4.7  | 1.5           | 4.7  | ns   |
|   |                   | DIR to B   | 1.7                | 7.2  | 0.7           | 5.5  | 0.6            | 5.5  | 0.7           | 4.1  | 1.7           | 4.7  | ns   |
| t <sub>en</sub>                             | enable time       | DIR to A   | -                  | 13.3 | -             | 9.1  | -              | 8.6  | -             | 6.7  | -             | 7.1  | ns   |
|   |                   | DIR to B   | -                  | 11.8 | -             | 9.2  | -              | 8.4  | -             | 7.5  | -             | 7.1  | ns   |

[1] t<sub>pd</sub> is the same as t<sub>PLH</sub> and t<sub>PHL</sub>; t<sub>dis</sub> is the same as t<sub>PLZ</sub> and t<sub>PHZ</sub>; t<sub>en</sub> is the same as t<sub>PZL</sub> and t<sub>PZH</sub>.  
t<sub>en</sub> is a calculated value using the formula shown in [Section 13.4 "Enable times"](#)


**Table 13. Dynamic characteristics for temperature range  $-40\text{ }^{\circ}\text{C}$  to  $+125\text{ }^{\circ}\text{C}$  [1]**

Voltages are referenced to GND (ground = 0 V); for test circuit see [Figure 8](#); for wave forms see [Figure 6](#) and [Figure 7](#)

| Symbol   | Parameter         | Conditions | $V_{CC(B)}$                     |      |                                 |      |                                  |      |                                 |      |                                 |      | Unit |
|--|-------------------|------------|---------------------------------|------|---------------------------------|------|----------------------------------|------|---------------------------------|------|---------------------------------|------|------|
|  |                   |            | $1.2\text{ V} \pm 0.1\text{ V}$ |      | $1.5\text{ V} \pm 0.1\text{ V}$ |      | $1.8\text{ V} \pm 0.15\text{ V}$ |      | $2.5\text{ V} \pm 0.2\text{ V}$ |      | $3.3\text{ V} \pm 0.3\text{ V}$ |      |      |
|  |                   |            | Min                             | Max  | Min                             | Max  | Min                              | Max  | Min                             | Max  | Min                             | Max  |      |
| <b><math>V_{CC(A)} = 1.1\text{ V to }1.3\text{ V}</math></b>   |                   |            |                                 |      |                                 |      |                                  |      |                                 |      |                                 |      |      |
| $t_{pd}$   | propagation delay | A to B     | 1.0                             | 9.9  | 0.7                             | 7.5  | 0.6                              | 6.8  | 0.5                             | 6.3  | 0.5                             | 6.8  | ns   |
|  |                   | B to A     | 1.0                             | 9.9  | 0.8                             | 8.8  | 0.7                              | 8.5  | 0.6                             | 8.0  | 0.5                             | 7.9  | ns   |
| $t_{dis}$  | disable time      | DIR to A   | 2.2                             | 9.7  | 2.2                             | 9.7  | 2.2                              | 9.7  | 2.2                             | 9.7  | 2.2                             | 9.7  | ns   |
|  |                   | DIR to B   | 2.2                             | 9.2  | 1.8                             | 7.4  | 2.0                              | 7.6  | 1.7                             | 6.9  | 2.4                             | 8.0  | ns   |
| $t_{en}$   | enable time       | DIR to A   | -                               | 19.1 | -                               | 16.2 | -                                | 16.1 | -                               | 14.9 | -                               | 15.9 | ns   |
|  |                   | DIR to B   | -                               | 19.6 | -                               | 17.2 | -                                | 16.5 | -                               | 16.0 | -                               | 16.5 | ns   |
| <b><math>V_{CC(A)} = 1.4\text{ V to }1.6\text{ V}</math></b>   |                   |            |                                 |      |                                 |      |                                  |      |                                 |      |                                 |      |      |
| $t_{pd}$   | propagation delay | A to B     | 1.0                             | 8.8  | 0.7                             | 6.0  | 0.6                              | 5.1  | 0.5                             | 4.1  | 0.5                             | 3.9  | ns   |
|  |                   | B to A     | 1.0                             | 7.5  | 0.8                             | 6.0  | 0.7                              | 5.7  | 0.6                             | 5.2  | 0.5                             | 5.0  | ns   |
| $t_{dis}$  | disable time      | DIR to A   | 1.6                             | 7.0  | 1.6                             | 7.0  | 1.6                              | 7.0  | 1.6                             | 7.0  | 1.6                             | 7.0  | ns   |
|  |                   | DIR to B   | 2.0                             | 8.3  | 1.8                             | 6.5  | 1.6                              | 6.6  | 1.2                             | 5.3  | 1.7                             | 6.1  | ns   |
| $t_{en}$   | enable time       | DIR to A   | -                               | 15.8 | -                               | 12.5 | -                                | 12.3 | -                               | 10.5 | -                               | 11.1 | ns   |
|  |                   | DIR to B   | -                               | 15.8 | -                               | 13.0 | -                                | 12.1 | -                               | 11.1 | -                               | 10.9 | ns   |
| <b><math>V_{CC(A)} = 1.65\text{ V to }1.95\text{ V}</math></b> |                   |            |                                 |      |                                 |      |                                  |      |                                 |      |                                 |      |      |
| $t_{pd}$   | propagation delay | A to B     | 1.0                             | 8.5  | 0.6                             | 5.7  | 0.5                              | 4.8  | 0.5                             | 3.8  | 0.5                             | 3.5  | ns   |
|  |                   | B to A     | 1.0                             | 6.8  | 0.7                             | 5.1  | 0.5                              | 4.9  | 0.5                             | 4.3  | 0.5                             | 4.1  | ns   |
| $t_{dis}$  | disable time      | DIR to A   | 1.6                             | 6.1  | 1.6                             | 6.1  | 1.6                              | 6.1  | 1.6                             | 6.1  | 1.6                             | 6.1  | ns   |
|  |                   | DIR to B   | 1.8                             | 8.5  | 1.8                             | 6.3  | 1.4                              | 6.4  | 1.0                             | 5.0  | 1.5                             | 5.8  | ns   |
| $t_{en}$   | enable time       | DIR to A   | -                               | 15.3 | -                               | 11.4 | -                                | 11.3 | -                               | 9.3  | -                               | 9.9  | ns   |
|  |                   | DIR to B   | -                               | 14.6 | -                               | 11.8 | -                                | 10.9 | -                               | 9.9  | -                               | 9.6  | ns   |
| <b><math>V_{CC(A)} = 2.3\text{ V to }2.7\text{ V}</math></b>   |                   |            |                                 |      |                                 |      |                                  |      |                                 |      |                                 |      |      |
| $t_{pd}$   | propagation delay | A to B     | 1.0                             | 8.0  | 0.5                             | 5.2  | 0.5                              | 4.3  | 0.5                             | 3.3  | 0.5                             | 2.9  | ns   |
|  |                   | B to A     | 1.0                             | 6.3  | 0.6                             | 4.2  | 0.5                              | 3.8  | 0.5                             | 3.3  | 0.5                             | 3.1  | ns   |
| $t_{dis}$  | disable time      | DIR to A   | 1.5                             | 4.7  | 1.5                             | 4.7  | 1.5                              | 4.7  | 1.5                             | 4.7  | 1.5                             | 4.7  | ns   |
|  |                   | DIR to B   | 1.7                             | 8.0  | 2.0                             | 5.8  | 1.5                              | 5.7  | 0.6                             | 4.7  | 1.1                             | 5.3  | ns   |
| $t_{en}$   | enable time       | DIR to A   | -                               | 14.3 | -                               | 10.0 | -                                | 9.5  | -                               | 8.0  | -                               | 8.4  | ns   |
|  |                   | DIR to B   | -                               | 12.7 | -                               | 9.9  | -                                | 9.0  | -                               | 8.0  | -                               | 7.6  | ns   |
| <b><math>V_{CC(A)} = 3.0\text{ V to }3.6\text{ V}</math></b>   |                   |            |                                 |      |                                 |      |                                  |      |                                 |      |                                 |      |      |
| $t_{pd}$   | propagation delay | A to B     | 1.0                             | 7.9  | 0.5                             | 5.0  | 0.5                              | 4.1  | 0.5                             | 3.1  | 0.5                             | 2.7  | ns   |
|  |                   | B to A     | 1.0                             | 6.8  | 0.6                             | 4.0  | 0.5                              | 3.5  | 0.5                             | 2.9  | 0.5                             | 2.7  | ns   |
| $t_{dis}$  | disable time      | DIR to A   | 1.5                             | 5.2  | 1.5                             | 5.2  | 1.5                              | 5.2  | 1.5                             | 5.2  | 1.5                             | 5.2  | ns   |
|  |                   | DIR to B   | 1.7                             | 7.9  | 0.7                             | 6.1  | 0.6                              | 6.1  | 0.7                             | 4.6  | 1.7                             | 5.2  | ns   |
| $t_{en}$   | enable time       | DIR to A   | -                               | 14.7 | -                               | 10.1 | -                                | 9.6  | -                               | 7.5  | -                               | 7.9  | ns   |
|  |                   | DIR to B   | -                               | 13.1 | -                               | 10.2 | -                                | 9.3  | -                               | 8.3  | -                               | 7.9  | ns   |


[1]  $t_{pd}$  is the same as  $t_{PLH}$  and  $t_{PHL}$ ;  $t_{dis}$  is the same as  $t_{PLZ}$  and  $t_{PHZ}$ ;  $t_{en}$  is the same as  $t_{PZL}$  and  $t_{PZH}$ .  
 $t_{en}$  is a calculated value using the formula shown in [Section 13.4 "Enable times"](#)

12. Waveforms



Measurement points are given in [Table 14](#).  
 VOL and VOH are typical output voltage levels that occur with the output load.

**Fig 6. The data input (nA, nB) to output (nB, nA) propagation delay times**



Measurement points are given in [Table 14](#).  
 VOL and VOH are typical output voltage levels that occur with the output load.


**Fig 7. Enable and disable times**

**Table 14. Measurement points**

| Supply voltage  | Input <sup>[1]</sup> | Output <sup>[2]</sup> |              |              |
|-----------------|----------------------|-----------------------|--------------|--------------|
| VCC(A), VCC(B)  | VM                   | VM                    | VX           | VY           |
| 1.1 V to 1.6 V  | 0.5VCCI              | 0.5VCCO               | VOL + 0.1 V  | VOH - 0.1 V  |
| 1.65 V to 2.7 V | 0.5VCCI              | 0.5VCCO               | VOL + 0.15 V | VOH - 0.15 V |
| 3.0 V to 3.6 V  | 0.5VCCI              | 0.5VCCO               | VOL + 0.3 V  | VOH - 0.3 V  |

[1] VCCI is the supply voltage associated with the data input port.

[2] VCCO is the supply voltage associated with the output port.



Test data is given in [Table 15](#).  
 $R_L$  = Load resistance.  
 $C_L$  = Load capacitance including jig and probe capacitance.  
 $R_T$  = Termination resistance.  
 $V_{EXT}$  = External voltage for measuring switching times.

**Fig 8. Test circuit for measuring switching times**

**Table 15. Test data**

| Supply voltage<br>$V_{CC(A)}, V_{CC(B)}$ | Input                |                                    | Load  |              | $V_{EXT}$          |                    |                                   |
|--|----------------------|------------------------------------|-------|--------------|--------------------|--------------------|-----------------------------------|
|  | $V_I$ <sup>[1]</sup> | $\Delta t/\Delta V$ <sup>[2]</sup> | $C_L$ | $R_L$        | $t_{PLH}, t_{PHL}$ | $t_{PZH}, t_{PHZ}$ | $t_{PZL}, t_{PLZ}$ <sup>[3]</sup> |
| 1.1 V to 1.6 V                           | $V_{CCI}$            | $\leq 1.0 \text{ ns/V}$            | 15 pF | 2 k $\Omega$ | open               | GND                | $2V_{CCO}$                        |
| 1.65 V to 2.7 V                          | $V_{CCI}$            | $\leq 1.0 \text{ ns/V}$            | 15 pF | 2 k $\Omega$ | open               | GND                | $2V_{CCO}$                        |
| 3.0 V to 3.6 V                           | $V_{CCI}$            | $\leq 1.0 \text{ ns/V}$            | 15 pF | 2 k $\Omega$ | open               | GND                | $2V_{CCO}$                        |

- [1]  $V_{CCI}$  is the supply voltage associated with the data input port.
- [2]  $dV/dt \geq 1.0 \text{ V/ns}$
- [3]  $V_{CCO}$  is the supply voltage associated with the output port.

### 13. Application information

#### 13.1 Unidirectional logic level-shifting application

The circuit given in [Figure 9](#) is an example of the 74AVC2T45 being used in an unidirectional logic level-shifting application.




Fig 9. Unidirectional logic level-shifting application

Table 16. Unidirectional logic level-shifting application

| Pin | Name               | Function         | Description   |
|-----|--------------------|------------------|---|
| 1   | V <sub>CC(A)</sub> | V <sub>CC1</sub> | supply voltage of system-1 (0.8 V to 3.6 V)               |
| 2   | 1A                 | OUT1             | output level depends on V <sub>CC1</sub> voltage          |
| 3   | 2A                 | OUT2             | output level depends on V <sub>CC1</sub> voltage          |
| 4   | GND                | GND              | device GND  |
| 5   | DIR                | DIR              | the GND (LOW level) determines B port to A port direction |
| 6   | 2B                 | IN2              | input threshold value depends on V <sub>CC2</sub> voltage |
| 7   | 1B                 | IN1              | input threshold value depends on V <sub>CC2</sub> voltage |
| 8   | V <sub>CC(B)</sub> | V <sub>CC2</sub> | supply voltage of system-2 (0.8 V to 3.6 V)               |

13.2 Bidirectional logic level-shifting application

Figure 10 shows the 74AVC2T45 being used in a bidirectional logic level-shifting application. Since the device does not have an output enable (OE) pin, the system designer should take precautions to avoid bus contention between system-1 and system-2 when changing directions.




Fig 10. Bidirectional logic level-shifting application

Table 17 gives a sequence that will illustrate data transmission from system-1 to system-2 and then from system-2 to system-1.

Table 17. Bidirectional logic level-shifting application [1][2]

| State | DIR CTRL | I/O-1  | I/O-2  | Description   |
|-------|----------|--------|--------|---|
| 1     | H        | output | input  | system-1 data to system-2   |
| 2     | H        | Z      | Z      | system-2 is getting ready to send data to system-1. I/O-1 and I/O-2 are disabled. The bus-line state depends on the pull-up or pull-down. |
| 3     | L        | Z      | Z      | DIR bit is set LOW. I/O-1 and I/O-2 still are disabled. The bus-line state depends on the pull-up or pull-down.                           |
| 4     | L        | input  | output | system-2 data to system-1   |

[1] System-1 and system-2 must use the same conditions, i.e., both pull-up or both pull-down.

[2] H = HIGH voltage level;  
 L = LOW voltage level;  
 Z = high-impedance OFF-state.

### 13.3 Power-up considerations

The device is designed such that no special power-up sequence is required other than GND being applied first.

**Table 18. Typical total supply current ( $I_{CC(A)} + I_{CC(B)}$ )**

| $V_{CC(A)}$ | $V_{CC(B)}$ |       |       |       |       |       |       | Unit          |
|-------------|-------------|-------|-------|-------|-------|-------|-------|---------------|
|             | 0 V         | 0.8 V | 1.2 V | 1.5 V | 1.8 V | 2.5 V | 3.3 V |               |
| 0 V         | 0           | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | $\mu\text{A}$ |
| 0.8 V       | 0.1         | 0.1   | 0.1   | 0.1   | 0.1   | 0.7   | 2.3   | $\mu\text{A}$ |
| 1.2 V       | 0.1         | 0.1   | 0.1   | 0.1   | 0.1   | 0.3   | 1.4   | $\mu\text{A}$ |
| 1.5 V       | 0.1         | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.9   | $\mu\text{A}$ |
| 1.8 V       | 0.1         | 0.1   | 0.1   | 0.1   | 0.1   | 0.1   | 0.5   | $\mu\text{A}$ |
| 2.5 V       | 0.1         | 0.7   | 0.3   | 0.1   | 0.1   | 0.1   | 0.1   | $\mu\text{A}$ |
| 3.3 V       | 0.1         | 2.3   | 1.4   | 0.9   | 0.5   | 0.1   | 0.1   | $\mu\text{A}$ |

### 13.4 Enable times

The enable times for the 74AVC2T45 are calculated from the following formulas:

- $t_{en}(\text{DIR to nA}) = t_{dis}(\text{DIR to nB}) + t_{pd}(\text{nB to nA})$
- $t_{en}(\text{DIR to nB}) = t_{dis}(\text{DIR to nA}) + t_{pd}(\text{nA to nB})$

In a bidirectional application, these enable times provide the maximum delay from the time the DIR bit is switched until an output is expected. For example, if the 74AVC2T45 initially is transmitting from A to B, then the DIR bit is switched, the B port of the device must be disabled before presenting it with an input. After the B port has been disabled, an input signal applied to it appears on the corresponding A port after the specified propagation delay.



14. Package outline

TSSOP8: plastic thin shrink small outline package; 8 leads; body width 3 mm; lead length 0.5 mm SOT505-2




Fig 11. Package outline SOT505-2 (TSSOP8)

VSSOP8: plastic very thin shrink small outline package; 8 leads; body width 2.3 mm

SOT765-1




Fig 12. Package outline SOT765-1 (VSSOP8)

XSON8: plastic extremely thin small outline package; no leads; 8 terminals; body 1 x 1.95 x 0.5 mm

SOT833-1





Fig 13. Package outline SOT833-1 (XSON8)

**XSON8: extremely thin small outline package; no leads;  
8 terminals; body 1.35 x 1 x 0.5 mm**

**SOT1089**



**Fig 14. Package outline SOT1089 (XSON8)**

XSON8: plastic extremely thin small outline package; no leads;  
8 terminals; body 3 x 2 x 0.5 mm

SOT996-2




Fig 15. Package outline SOT996-2 (XSON8)

**XSON8: extremely thin small outline package; no leads;  
8 terminals; body 1.2 x 1.0 x 0.35 mm**

SOT1116





Fig 16. Package outline SOT1116 (XSON8)

**XSON8: extremely thin small outline package; no leads;  
8 terminals; body 1.35 x 1.0 x 0.35 mm**

**SOT1203**



**Fig 17. Package outline SOT1203 (XSON8)**

## 15. Abbreviations

Table 19. Abbreviations

| Acronym | Description             |
|---------|-------------------------|
| CDM     | Charged Device Model    |
| DUT     | Device Under Test       |
| ESD     | ElectroStatic Discharge |
| HBM     | Human Body Model        |
| MM      | Machine Model           |

## 16. Revision history

Table 20. Revision history

| Document ID    | Release date   | Data sheet status  | Change notice | Supersedes    |
|----------------|--|--------------------|---------------|---------------|
| 74AVC2T45 v.7  | 20130208   | Product data sheet | -             | 74AVC2T45 v.6 |
| Modifications: | <ul style="list-style-type: none"> <li>For type number 74AVC2T45GD XSON8U has changed to XSON8.</li> </ul> |                    |               |               |
| 74AVC2T45 v.6  | 20111208   | Product data sheet | -             | 74AVC2T45 v.5 |
| 74AVC2T45 v.5  | 20101130   | Product data sheet | -             | 74AVC2T45 v.4 |
| 74AVC2T45 v.4  | 20090505   | Product data sheet | -             | 74AVC2T45 v.3 |
| 74AVC2T45 v.3  | 20090129   | Product data sheet | -             | 74AVC2T45 v.2 |
| 74AVC2T45 v.2  | 20080620   | Product data sheet | -             | 74AVC2T45 v.1 |
| 74AVC2T45 v.1  | 20070703   | Product data sheet | -             | -             |



## 17. Legal information

### 17.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition  |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

### 17.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

**Product specification** — The information and data provided in a Product data sheet shall define the specification of the product as agreed between NXP Semiconductors and its customer, unless NXP Semiconductors and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the NXP Semiconductors product is deemed to offer functions and qualities beyond those described in the Product data sheet.

### 17.3 Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of NXP Semiconductors.

**Right to make changes** — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or

malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Non-automotive qualified products** — Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond

NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

## 17.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 18. Contact information

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

## 19. Contents

|           |   |           |
|-----------|---|-----------|
| <b>1</b>  | <b>General description</b> .....                  | <b>1</b>  |
| <b>2</b>  | <b>Features and benefits</b> .....                | <b>1</b>  |
| <b>3</b>  | <b>Ordering information</b> .....                 | <b>2</b>  |
| <b>4</b>  | <b>Marking</b> .....                              | <b>2</b>  |
| <b>5</b>  | <b>Functional diagram</b> .....                   | <b>3</b>  |
| <b>6</b>  | <b>Pinning information</b> .....                  | <b>3</b>  |
| 6.1       | Pinning .....                                     | 3         |
| 6.2       | Pin description .....                             | 4         |
| <b>7</b>  | <b>Functional description</b> .....               | <b>4</b>  |
| <b>8</b>  | <b>Limiting values</b> .....                      | <b>5</b>  |
| <b>9</b>  | <b>Recommended operating conditions</b> .....     | <b>5</b>  |
| <b>10</b> | <b>Static characteristics</b> .....               | <b>6</b>  |
| <b>11</b> | <b>Dynamic characteristics</b> .....              | <b>9</b>  |
| <b>12</b> | <b>Waveforms</b> .....                            | <b>12</b> |
| <b>13</b> | <b>Application information</b> .....              | <b>14</b> |
| 13.1      | Unidirectional logic level-shifting application . | 14        |
| 13.2      | Bidirectional logic level-shifting application. . | 15        |
| 13.3      | Power-up considerations .....                     | 16        |
| 13.4      | Enable times .....                                | 16        |
| <b>14</b> | <b>Package outline</b> .....                      | <b>17</b> |
| <b>15</b> | <b>Abbreviations</b> .....                        | <b>24</b> |
| <b>16</b> | <b>Revision history</b> .....                     | <b>24</b> |
| <b>17</b> | <b>Legal information</b> .....                    | <b>25</b> |
| 17.1      | Data sheet status .....                           | 25        |
| 17.2      | Definitions .....                                 | 25        |
| 17.3      | Disclaimers .....                                 | 25        |
| 17.4      | Trademarks .....                                  | 26        |
| <b>18</b> | <b>Contact information</b> .....                  | <b>26</b> |
| <b>19</b> | <b>Contents</b> .....                             | <b>27</b> |

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© NXP B.V. 2013.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: [salesaddresses@nxp.com](mailto:salesaddresses@nxp.com)

Date of release: 8 February 2013

Document identifier: 74AVC2T45