

TDA9910

12-bit, up to 80 Msample/s, Analog-to-Digital Converter (ADC) direct/ultra high IF sampling

Rev. 04 — 12 June 2007

Product data sheet

1. General description

The TDA9910 is a 12-bit Analog-to-Digital Converter (ADC) optimized for direct Input Frequency (IF) sampling, and supporting the most demanding use conditions in ultra high IF radio transceivers for cellular infrastructure and other applications such as wireless access system, optical networking and fixed telecommunication. Thanks to its broadband input capabilities, the TDA9910 is ideal for single and multiple carriers data conversion.

Operating at a maximum sampling rate of 80 Msample/s, analog input signals are converted into 12-bit binary coded digital words. All static digital inputs are CMOS compatible. All output signals are LVCMOS compatible. The TDA9910 offers the most possible flexible acquisition control system thanks to its programmable Complete Conversion Signal (CCS) that allows to adjust the delay of the acquisition clock.

Thanks to its internal front-end buffer, the TDA9910 offers the lowest input capacitance (< 1 pF) and therefore the highest flexibility in front-end aliasing filter strategy.

2. Features

- 12-bit resolution
- 90 dB SFDR; 71 dB SNR ($f_i = 225$ MHz; $f_{CLK} = 80$ Msample/s; $B = 5$ MHz)
- High-speed sampling rate up to 80 Msample/s
- Programmable acquisition output clock (complete conversion signal)
- Single 5 V power supply
- Binary or two's-complement LVCMOS outputs
- Only 2 clock cycles latency
- HTQFP48 package
- Differential input with 375 MHz bandwidth
- 70 dB SFDR; 66.5 dB SNR ($f_i = 175$ MHz; $f_{CLK} = 80$ Msample/s; $B = \text{Nyquist}$)
- Internal front-end buffer (input capacitance <1 pF)
- Full-scale controllable from 1.5 V to 2 V (p-p); continuous scale
- 3.3 V LVCMOS compatible digital outputs
- CMOS compatible static digital inputs
- Industrial temperature range from -40 °C to $+85$ °C

3. Applications

- 2.5G and 3G cellular base infrastructure radio transceivers
- Wireless access systems
- Fixed telecommunication
- Optical networking
- Wireless Local Area Network (WLAN) infrastructure

4. Ordering information

Table 1. Ordering information

Type number	Sampling frequency (Msamples)	Package		
		Name	Description	Version
TDA9910HW/8/C1	80	HTQFP48	plastic thermal enhanced thin quad flat package; 48 leads; body 7 × 7 × 1 mm; exposed die pad	SOT545-2

5. Block diagram




Fig 1. Block diagram

6. Pinning information

6.1 Pinning




Fig 2. Pin configuration

6.2 Pin description

Table 2. Pin description

Symbol	Pin	Type ^[1]	Description
n.c.	1	-	not connected
AGND1	2	G	analog ground 1
IN	3	I	analog input voltage
CMADC	4	O	regulator common mode ADC output
INN	5	I	complementary analog input voltage
AGND1	6	G	analog ground 1
DEC	7	I/O	decoupling node
n.c.	8	-	not connected
FSOUT	9	O	full-scale reference voltage output
FSIN	10	I	full-scale reference voltage input
n.c.	11	-	not connected
n.c.	12	-	not connected
n.c.	13	-	not connected
DEL1	14	I	complete conversion signal delay input 1

Table 2. Pin description ...continued

Symbol	Pin	Type ^[1]	Description
DELO	15	I	complete conversion signal delay input 0
V _{CCD2(5V0)}	16	P	digital supply voltage 2 (5.0 V)
DGND2	17	G	digital ground 2
CE_N	18	I	chip enable input (CMOS level; active LOW)
OTC	19	I	control input for two's complement output (active HIGH)
OGND	20	G	data output ground
V _{CCO(3V3)}	21	P	data output supply voltage (3.3 V)
OGND	22	G	data output ground
V _{CCO(3V3)}	23	P	data output supply voltage (3.3 V)
IR	24	O	in-range output
D11	25	O	data output bit 11 (MSB)
D10	26	O	data output bit 10
D9	27	O	data output bit 9
D8	28	O	data output bit 8
D7	29	O	data output bit 7
D6	30	O	data output bit 6
D5	31	O	data output bit 5
D4	32	O	data output bit 4
D3	33	O	data output bit 3
D2	34	O	data output bit 2
D1	35	O	data output bit 1
D0	36	O	data output bit 0 (LSB)
CCS	37	O	complete conversion signal output
DGND1	38	G	digital ground 1
CLKN	39	I	complementary clock input
CLK	40	I	clock input
V _{CCD1(5V0)}	41	P	digital supply voltage 1 (5.0 V)
DGND1	42	G	digital ground 1
AGND2	43	G	analog ground 2
V _{CCA2(5V0)}	44	P	analog supply voltage 2 (5.0 V)
V _{CCA1(5V0)}	45	P	analog supply voltage 1 (5.0 V)
AGND1	46	G	analog ground 1
V _{CCA1(5V0)}	47	P	analog supply voltage 1 (5.0 V)
AGND1	48	G	analog ground 1
DGND	exposed die pad	G	digital ground

[1] P: power supply; G: ground; I: input; O: output.

7. Limiting values

Table 3. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{CCA}	analog supply voltage		[1] -0.5	+7.0	V
V_{CCD}	digital supply voltage		[1] -0.5	+7.0	V
V_{CCO}	output supply voltage		[2] -0.5	+5.0	V
ΔV_{CC}	supply voltage difference				
	$V_{CCA} - V_{CCD}$		-1.0	+1.0	V
	$V_{CCD} - V_{CCO}$		-1.0	+4.0	V
	$V_{CCA} - V_{CCO}$		-1.0	+4.0	V
$V_{i(IN)}, V_{i(INN)}$	input voltage	referenced to AGND	0	$V_{CCA} + 1$	V
V_{CLK}, V_{CLKN}	input voltage for differential clock drive	referenced to DGND	0	$V_{CCD} + 1$	V
I_O	output current		-	10	mA
T_{stg}	storage temperature		-55	+150	°C
T_{amb}	ambient temperature		-40	+85	°C
T_j	junction temperature		-	150	°C

[1] The supply voltages V_{CCA} and V_{CCD} may have any value between -0.5 V and +7.0 V provided that the supply voltage differences ΔV_{CC} are respected.

[2] The supply voltage V_{CCO} may have any value between -0.5 V and +5.0 V provided that the supply voltage differences ΔV_{CC} are respected.

8. Thermal characteristics

Table 4. Thermal characteristics

Symbol	Parameter	Conditions	Typ	Unit
$R_{th(j-a)}$	thermal resistance from junction to ambient		[1] 36.2	K/W
$R_{th(j-c)}$	thermal resistance from junction to case		[1] 14.3	K/W

[1] In compliance with JEDEC test board, in free air.

9. Characteristics

Table 5. Characteristics

$V_{CCA} = 4.75\text{ V to }5.25\text{ V}$; $V_{CCD} = 4.75\text{ V to }5.25\text{ V}$; $V_{CCO} = 2.7\text{ V to }3.6\text{ V}$; AGND and DGND shorted together; $T_{amb} = -40\text{ °C to }+85\text{ °C}$; $V_{i(IN)} - V_{i(INN)} = -0.5\text{ dBFS}$; $V_{FSIN} = V_{CCA} - 1.87\text{ V}$; $V_{i(CM)} = V_{CCA} - 1.95\text{ V}$; typical values measured at $V_{CCA} = V_{CCD} = 5\text{ V}$, $V_{CCO} = 3.3\text{ V}$, $T_{amb} = 25\text{ °C}$ and $C_L = 10\text{ pF}$; unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Supplies						
V_{CCA}	analog supply voltage		4.75	5.0	5.25	V
V_{CCD}	digital supply voltage		4.75	5.0	5.25	V
V_{CCO}	output supply voltage		2.7	3.3	3.6	V
I_{CCA}	analog supply current		-	120	135	mA
I_{CCD}	digital supply current		-	50	65	mA
I_{CCO}	output supply current	$f_{CLK} = 80\text{ Msample/s}$; $f_i = 93\text{ MHz}$	-	10	15	mA
P_{tot}	total power dissipation	$f_{CLK} = 80\text{ Msample/s}$; DC input	-	840	990	mW

Clock inputs: pins CLK and CLKN^[2]

V_{iL}	LOW-level input voltage	referenced to DGND; $V_{CCD} = 5\text{ V}$					
			PECL mode	3.19	-	3.52	V
			TTL mode	DGND	-	0.8	V
V_{iH}	HIGH-level input voltage	referenced to DGND; $V_{CCD} = 5\text{ V}$					
			PECL mode	3.83	-	4.12	V
			TTL mode	2.0	-	V_{CCD}	V
I_{iL}	LOW-level input current	V_{CLK} or $V_{CLKN} = 3.52\text{ V}$	^[1] -	-	28	μA	
		V_{CLK} or $V_{CLKN} = 0.80\text{ V}$	1	-	-	nA	
I_{iH}	HIGH-level input current	V_{CLK} or $V_{CLKN} = 3.83\text{ V}$	-	-	30	μA	
		V_{CLK} or $V_{CLKN} = 2.00\text{ V}$	2	-	-	nA	
ΔV_{CLK}	differential AC input voltage for switching ($V_{CLK} - V_{CLKN}$)	AC mode; DC voltage level is 2.5 V	1.3	1.5	1.7	V	
R_i	input resistance	$f_{CLK} = 80\text{ Msample/s}$	^[1] -	6.3	-	k Ω	
C_i	input capacitance	$f_{CLK} = 80\text{ Msample/s}$	^[1] -	1.1	-	pF	

Analog inputs: pins IN and INN

I_{iL}	LOW-level input current	$V_{FSIN} = V_{CCA} - 1.75\text{ V}$	-	5	-	μA
I_{iH}	HIGH-level input current	$V_{FSIN} = V_{CCA} - 1.75\text{ V}$	-	5	-	μA
R_i	input resistance		^[1] 6.3	-	-	M Ω
C_i	input capacitance		^[1] -	-	700	fF
$V_{i(CM)}$	common mode input voltage	$V_{i(IN)} = V_{i(INN)}$; output code = 2047	$V_{CCA} - 2$	$V_{CCA} - 1.8$	$V_{CCA} - 1.6$	V

Table 5. Characteristics ...continued

$V_{CCA} = 4.75\text{ V to }5.25\text{ V}$; $V_{CCD} = 4.75\text{ V to }5.25\text{ V}$; $V_{CCO} = 2.7\text{ V to }3.6\text{ V}$; AGND and DGND shorted together; $T_{amb} = -40\text{ }^{\circ}\text{C to }+85\text{ }^{\circ}\text{C}$; $V_{i(IN)} - V_{i(INN)} = -0.5\text{ dBFS}$; $V_{FSIN} = V_{CCA} - 1.87\text{ V}$; $V_{i(CM)} = V_{CCA} - 1.95\text{ V}$; typical values measured at $V_{CCA} = V_{CCD} = 5\text{ V}$, $V_{CCO} = 3.3\text{ V}$, $T_{amb} = 25\text{ }^{\circ}\text{C}$ and $C_L = 10\text{ pF}$; unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Digital inputs: pins OTC and CE_N						
V_{IL}	LOW-level input voltage		DGND	-	$0.3 \times V_{CCD}$	V
V_{IH}	HIGH-level input voltage		$0.7 \times V_{CCD}$	-	V_{CCD}	V
I_{IL}	LOW-level input current	$V_{IL} = 0.8\text{ V}$	-	1	-	μA
I_{IH}	HIGH-level input current	$V_{IH} = 2.0\text{ V}$	-	1	-	μA
Digital inputs: pins DEL0 and DEL1						
V_{IL}	LOW-level input voltage		DGND	-	$0.3 \times V_{CCD}$	V
V_{IH}	HIGH-level input voltage		$0.7 \times V_{CCD}$	-	V_{CCD}	V
I_{IL}	LOW-level input current	$V_{IL} = 0.8\text{ V}$	-	8	-	μA
I_{IH}	HIGH-level input current	$V_{IH} = 2.0\text{ V}$	-	20	-	μA
Voltage controlled regulator output: pin CMADC						
$V_{o(CM)}$	common mode output voltage	$I_L = 0\text{ mA}$	-	$V_{CCA} - 1.88$	-	V
		$I_L = 2\text{ mA}$	-	$V_{CCA} - 1.95$	-	V
Reference voltage input: pin FSIN^[3]						
V_{FSIN}	full-scale fixed voltage		-	$V_{CCA} - 1.80$	-	V
I_{FSIN}	input current		-	0.1	-	μA
$V_{i(p-p)}$	peak-to-peak input voltage	see Figure 5 ; $V_i = V_{i(IN)} - V_{i(INN)}$; $V_{i(CM)} = V_{CCA} - 1.95\text{ V}$	-	1.85	-	V
Full-scale voltage controlled regulator output: pin FSOUT						
$V_{o(ref)}$	1.9 V full-scale output voltage	$I_L = I_{FSIN}$	-	$V_{CCA} - 1.80$	-	V
		$I_L = 2\text{ mA}$	-	$V_{CCA} - 1.82$	-	V
Digital outputs: pins D11 to D0, IR and CCS						
Output levels						
V_{OL}	LOW-level output voltage	$I_{OL} = 2\text{ mA}$	DGND	-	DGND + 0.5	V
V_{OH}	HIGH-level output voltage	$I_{OH} = -0.4\text{ mA}$	$V_{CCO} - 0.5$	-	V_{CCO}	V
I_{OZ}	output current in 3-state	output level between 0.5 V and V_{CCO}	-0.1	0	+0.1	μA
Timing^[4]						
$t_{d(s)}$	sampling delay time	$C_L = 10\text{ pF}$	-	0.1	0.24	ns
$t_{h(o)}$	output hold time	$C_L = 10\text{ pF}$	2.6	3.8	-	ns
$t_{d(o)}$	output delay time	$C_L = 10\text{ pF}$	-	4.7	7.8	ns
3-state output delay						
t_{dZH}	enable HIGH		-	3.6	-	ns
t_{dZL}	enable LOW		-	3.9	-	ns
t_{dHZ}	disable HIGH		-	9.2	-	ns
t_{dLZ}	disable LOW		-	7.2	-	ns

Table 5. Characteristics ...continued

$V_{CCA} = 4.75\text{ V to }5.25\text{ V}$; $V_{CCD} = 4.75\text{ V to }5.25\text{ V}$; $V_{CCO} = 2.7\text{ V to }3.6\text{ V}$; AGND and DGND shorted together; $T_{amb} = -40\text{ }^{\circ}\text{C}$ to $+85\text{ }^{\circ}\text{C}$; $V_{i(IN)} - V_{i(INN)} = -0.5\text{ dBFS}$; $V_{FSIN} = V_{CCA} - 1.87\text{ V}$; $V_{i(CM)} = V_{CCA} - 1.95\text{ V}$; typical values measured at $V_{CCA} = V_{CCD} = 5\text{ V}$, $V_{CCO} = 3.3\text{ V}$, $T_{amb} = 25\text{ }^{\circ}\text{C}$ and $C_L = 10\text{ pF}$; unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Clock timing inputs: pins CLK and CLKN						
δ	duty cycle	$f_{CLK} = 80\text{ Msample/s}$; $f_i = 175\text{ MHz}$	45	-	55	%
$f_{CLK(min)}$	minimum clock frequency		-	-	9.5	Msample/s
$f_{CLK(max)}$	maximum clock frequency	$\delta = 45\text{ \% to }55\text{ \%}$	80	-	-	Msample/s
Timing complete conversion signal: pin CCS; see Figure 6						
$t_{cd(o)}$	complete conversion signal delay time	$C_L = 10\text{ pF}$; DELO = LOW; DEL1 = HIGH	-	0.3	-	ns
		$C_L = 10\text{ pF}$; DELO = HIGH; DEL1 = LOW	-	1.3	-	ns
		$C_L = 10\text{ pF}$; DELO = HIGH; DEL1 = HIGH	-	2.3	-	ns
Analog signal processing (clock duty cycle 50 %)						
INL	integral non-linearity	$f_{CLK} = 20\text{ Msample/s}$; $f_i = 21.4\text{ MHz}$	-	± 2.0	-	LSB
DNL	differential non-linearity	$f_{CLK} = 20\text{ Msample/s}$; $f_i = 21.4\text{ MHz}$; no missing code guaranteed	-	± 0.6	-	LSB
E_{offset}	offset error	$V_{CCA} = V_{CCD} = 5\text{ V}$; $V_{CCO} = 3.3\text{ V}$; $T_{amb} = 25\text{ }^{\circ}\text{C}$; output code = 2047	-4	+8	+24	mV
E_G	gain error amplitude (spread from device to device)	$V_{CCA} = V_{CCD} = 5\text{ V}$; $V_{CCO} = 3.3\text{ V}$; $T_{amb} = 25\text{ }^{\circ}\text{C}$	-	2.5	-	%FS
B	analog bandwidth ^[5]	$f_{CLK} = 80\text{ Msample/s}$; -3 dB; full-scale input	320	375	-	MHz
α_{2H}	second harmonic level	$f_i = 21.4\text{ MHz}$	-	-79	-	dBc
		$f_i = 93\text{ MHz}$	-	-78	-	dBc
		$f_i = 175\text{ MHz}$	-	-74	-	dBc
α_{3H}	third harmonic level	$f_i = 21.4\text{ MHz}$	-	-84	-	dBc
		$f_i = 93\text{ MHz}$	-	-80	-	dBc
		$f_i = 175\text{ MHz}$	-	-76	-	dBc
THD	total harmonic distortion ^[6]	$f_i = 21.4\text{ MHz}$	-	-75	-	dBc
		$f_i = 93\text{ MHz}$	-	-73	-	dBc
		$f_i = 175\text{ MHz}$	-	-68	-	dBc
$N_{th(RMS)}$	RMS thermal noise	$V_{i(IN)} = V_{i(INN)}$; $f_{CLK} = 80\text{ Msample/s}$	-	0.45	-	LSB

Table 5. Characteristics ...continued

$V_{CCA} = 4.75\text{ V to }5.25\text{ V}$; $V_{CCD} = 4.75\text{ V to }5.25\text{ V}$; $V_{CCO} = 2.7\text{ V to }3.6\text{ V}$; AGND and DGND shorted together; $T_{amb} = -40\text{ }^{\circ}\text{C to }+85\text{ }^{\circ}\text{C}$; $V_{i(IN)} - V_{i(INN)} = -0.5\text{ dBFS}$; $V_{FSIN} = V_{CCA} - 1.87\text{ V}$; $V_{i(CM)} = V_{CCA} - 1.95\text{ V}$; typical values measured at $V_{CCA} = V_{CCD} = 5\text{ V}$, $V_{CCO} = 3.3\text{ V}$, $T_{amb} = 25\text{ }^{\circ}\text{C}$ and $C_L = 10\text{ pF}$; unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
SNR	signal-to-noise ratio ^[7]	$f_i = 21.4\text{ MHz}$	-	67.4	-	dBc
		$f_i = 93\text{ MHz}$	63	67.2	-	dBc
		$f_i = 175\text{ MHz}$	-	66.5	-	dBc
SFDR	spurious free dynamic range	$f_i = 21.4\text{ MHz}$	-	76	-	dBc
		$f_i = 93\text{ MHz}$	68	78	-	dBc
		$f_i = 175\text{ MHz}$	-	74	-	dBc
ACPR	adjacent channel power rejection	$f_i = 93\text{ MHz}$; 5 MHz channel spacing; B = 3.84 MHz	-	70	-	dB
$d2_{(IM2)}$	second order intermodulation distortion ^[8]	$f_{i1} = 21\text{ MHz}$; $f_{i2} = 22\text{ MHz}$	-	-89	-	dBFS
		$f_{i1} = 91.5\text{ MHz}$; $f_{i2} = 94.5\text{ MHz}$	-	-86	-	dBFS
		$f_{i1} = 174\text{ MHz}$; $f_{i2} = 176\text{ MHz}$	-	-83	-	dBFS
$d3_{(IM3)}$	third order intermodulation distortion ^[8]	$f_{i1} = 21\text{ MHz}$; $f_{i2} = 22\text{ MHz}$	-	-88	-	dBFS
		$f_{i1} = 91.5\text{ MHz}$; $f_{i2} = 93.5\text{ MHz}$	-	-82	-	dBFS
		$f_{i1} = 174\text{ MHz}$; $f_{i2} = 176\text{ MHz}$	-	-83	-	dBFS

- [1] Guaranteed by design.
- [2] The circuit has two clock inputs: CLK and CLKN. There are 5 modes of operation:
 - a) PECL mode 1: (DC levels vary 1:1 with V_{CCD}) CLK and CLKN inputs are at differential PECL levels.
 - b) PECL mode 2: (DC levels vary 1:1 with V_{CCD}) CLK input is at PECL level and sampling is taken on the falling edge of the clock input signal. A DC level of 3.65 V has to be applied on CLKN decoupled to GND via a 100 nF capacitor.
 - c) PECL mode 3: (DC levels vary 1:1 with V_{CCD}) CLKN input is at PECL level and sampling is taken on the rising edge of the clock input signal. A DC level of 3.65 V has to be applied on CLK decoupled to GND via a 100 nF capacitor.
 - d) Differential AC driving mode 4: When driving the CLK input directly and with any AC signal of minimum 1 V (p-p) and with a DC level of 2.5 V, the sampling takes place at the falling edge of the clock signal. When driving the CLKN input with the same signal, sampling takes place at the rising edge of the clock signal. It is recommended to decouple the CLKN or CLK input to DGND via a 100 nF capacitor.
 - e) TTL mode 5: CLK input is at TTL level and sampling is taken on the falling edge of the clock input signal. In that case CLKN pin has to be connected to the ground.
- [3] The ADC input range can be adjusted with an external reference connected to FSIN pin. This voltage has to be referenced to V_{CCA} .
- [4] Output data acquisition: the output data is available after the maximum delay of $t_{d(o)}$.
- [5] The -3 dB analog bandwidth is determined by the 3 dB reduction in the reconstructed output, the input being a full-scale sine wave.
- [6] The total harmonic distortion is obtained with the addition of the first five harmonics.
- [7] The signal-to-noise ratio takes into account all harmonics above five and noise up to Nyquist frequency.
- [8] Intermodulation measured relative to either tone with analog input frequencies f_{i1} and f_{i2} . The two input signals have the same amplitude and the total amplitude of both signals provides full-scale to the converter (-6 dB below full-scale for each input signal). $d3_{(IM3)}$ is the ratio of the RMS value of either input tone to the RMS value of the worst case third order intermodulation product; $d2_{(IM2)}$ is the ratio of the RMS value of either input tone to the RMS value of the worst case second order intermodulation product.

Table 6. Output coding with differential inputs


$V_{i(IN)} - V_{i(INN)} = 1.9\text{ V}$; $V_{FSIN} = V_{CCA1} - 1.87\text{ V}$; typical values to AGND.



Code	$V_{i(IN)}\text{ (V)}$	$V_{i(INN)}\text{ (V)}$	IR	Binary outputs (D11 to D0)	Two's complement outputs (D11 to D0)
Underflow	< 2.675	> 3.625	0	0000 0000 0000	1000 0000 0000
0	2.675	3.625	1	0000 0000 0000	1000 0000 0000
1	-	-	1	0000 0000 0001	1000 0000 0001
...
2047	3.15	3.15	1	0111 1111 1111	1111 1111 1111
...
4094	-	-	1	1111 1111 1110	0111 1111 1110
4095	3.625	2.675	1	1111 1111 1111	0111 1111 1111
Overflow	> 3.625	< 2.675	0	1111 1111 1111	0111 1111 1111

Table 7. Mode selection

Two's complement output (OTC)	Chip enable input (CE_N)	Data output (D0 to D11; IR)
0	0	binary; active
1	0	two's complement; active
X ^[1]	1	high-impedance

[1] X = don't care.





The TDA9910 allows to modify the ADC full-scale. This could be done with FSIN (full-scale input) according to [Figure 5](#).

The TDA9910 generates an adjustable clock output called Complete Conversion Signal (CCS), which can be used to control the acquisition of converted output data by the digital circuit connected to the TDA9910 output data bus. Two logic inputs, DEL0 and DEL1 pins, allow to adjust the delay of the edge of the CCS signal to achieve an optimal position in the stable, usable zone of the data.

Table 8. Complete conversion signal selection

DEL1	DEL0	CCS output
0	0	high-impedance
0	1	active, typical delay 0.3 ns
1	0	active, typical delay 1.3 ns
1	1	active, typical delay 2.3 ns




Fig 6. Complete conversion signal timing diagram

10. Definitions

10.1 Static parameters

10.1.1 INL (integral non-linearity)

It is defined as the deviation of the transfer function from a best fit straight line (linear regression computation). The INL of the code i is obtained from the equation:

$$INL(i) = \frac{V_{in}(i) - V_{in}(ideal)}{S}$$

where: S is corresponding to the slope of the ideal straight line (code width); i is corresponding to the code value; V_{in} is the input voltage.

10.1.2 DNL (differential non-linearity)


It is the deviation in code width from the value of 1 LSB.

$$DNL(i) = \frac{V_{in}(i+1) - V_{in}(i)}{S}$$

where: V_{in} is the input voltage; i from 0 to $(2^n - 2)$.

10.2 Dynamic parameters

[Figure 7](#) shows the spectrum of a single tone full-scale input sine wave with frequency f_t , conforming to coherent sampling ($f_t/f_s = M/N$, with M number of cycles and N number of samples, M and N being relatively prime), and digitized by the ADC under test.



Remark: In the following equations, P_{noise} is the power of the terms which include the effects of random noise, non-linearities, sampling time errors, and 'quantization noise'.

10.2.1 SINAD (signal-to-noise and distortion)

The ratio of the output signal power to the noise plus distortion power for a given sample rate and input frequency, excluding the DC component:

$$SINAD[dB] = 10 \log_{10} \left(\frac{P_{\text{signal}}}{P_{\text{noise} + \text{distortion}}} \right)$$

10.2.2 ENOB (effective number of bits)

It is derived from SINAD and gives the theoretical resolution an ideal ADC would require to obtain the same SINAD measured on the real ADC. A good approximation gives:

$$ENOB = \frac{SINAD - 1.76}{6.02}$$

10.2.3 THD (total harmonic distortion)

The ratio of the power of the harmonics to the power of the fundamental. For $k - 1$ harmonics the THD is:

$$THD[dB] = 10 \log_{10} \left(\frac{P_{\text{harmonics}}}{P_{\text{signal}}} \right)$$

where:

$$P_{\text{harmonics}} = a_2^2 + a_3^2 + \dots + a_k^2$$

$$P_{\text{signal}} = a_1^2$$

The value of k is usually 6 (i.e. calculation of THD is done on the first 5 harmonics).

10.2.4 SNR (signal-to-noise ratio)

The ratio of the output signal power to the noise power, excluding the harmonics and the DC component is:

$$SNR[dB] = 10 \log_{10} \left(\frac{P_{\text{signal}}}{P_{\text{noise}}} \right)$$

10.2.5 SFDR (spurious free dynamic range)

The number SFDR specifies available signal range as the spectral distance between the amplitude of the fundamental and the amplitude of the largest spurious harmonic and non-harmonic, excluding DC component:

$$SFDR[dB] = 20 \log_{10} \left(\frac{a_1}{\max(S)} \right)$$

10.2.6 IMD2 (IMD3)




Fig 8. Spectral of dual tone input sine wave with frequency

From a dual tone input sinusoid (f_{t1} and f_{t2} , these frequencies being chosen according to the coherence criterion), the intermodulation distortion products IMD2 and IMD3 (respectively, 2nd and 3rd order components) are defined, as follows.

The ratio of the RMS value of either tone to the RMS value of the worst second (third) order intermodulation product.

The total InterModulation Distortion (IMD) is given by:

$$IMD[dB] = 10 \log_{10} \left(\frac{P_{intermod}}{P_{signal}} \right)$$

where:

$$P_{intermod} = a_{im(f_{t1} - f_{t2})}^2 - a_{im(f_{t1} + f_{t2})}^2 + a_{im(f_{t1} - 2f_{t2})}^2 + a_{im(f_{t1} + 2f_{t2})}^2 + \dots$$

$$\dots + a_{im(2f_{t1} - f_{t2})}^2 + a_{im(2f_{t1} + f_{t2})}^2$$

with $a_{im(f_{t1})}^2$ corresponding to the power in the intermodulation component at frequency f_t .

$$P_{signal} = a_{f_{t1}}^2 + a_{f_{t2}}^2$$

11. Application information

11.1 TDA9910 in 3G radio receivers

The TDA9910 has been proven in many 3G radio receivers with various operating conditions regarding Input Frequency (IF), signal IF bandwidth and sampling frequency. The TDA9910 provides with a maximum analog input signal frequency of 400 MHz. It allows a significant cost-down of the RF front-end, from two mixers to only one, even in multi-carriers architecture.

[Table 9](#) describes some possible applications with the TDA9910 in high IF sampling mode.

Table 9. Examples of possible f_i , f_{CLK} , IF BW combinations supported

f_i (MHz)	f_{CLK} (Msample/s)	IF BW (MHz) ^[1]	SNR (dB)	SFDR (dBc)
350	80	5.00	65	71
243.95	9.60	0.25	71	80
96	76.80	1.60	72	76
96	76.80	4.80	71	77
96	76.80	20.00	68	76
80	61.44	10.00	70	85
78.4	44.80	3.50	71	76
70	40.00	1.25	72	79

[1] IF bandwidth corresponds to the observed area on the ADC output spectrum.

For a dual carrier W-CDMA receiver, the most important parameters are sensitivity and Adjacent Channel Selectivity (ACS). The sensitivity is defined as the lowest detectable signal level. In W-CDMA, it can be far below the noise floor. This difference, between the sensitivity and the noise floor, is defined by the Sensitivity-to-Noise Ratio (SENr). Its value is negative due to the gain processing. The Adjacent Channel Power Ratio (ACPR) is the difference between the full-scale -3 dB peak and the noise floor. It represents the ratio of the adjacent-channel power and the average power level of the channel. The ACS is defined by the sum of SENr and ACPR.




Fig 9. Adjacent channel sensitivity and ADC sensitivity

12. Package outline

HTQFP48: plastic thermal enhanced thin quad flat package; 48 leads; body 7 x 7 x 1 mm; exposed die pad

SOT545-2




Fig 11. Package outline SOT545-2 (HTQFP48)

13. Revision history

Table 10. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
TDA9910_4	20070612	Product data sheet	-	TDA9910_3
Modifications:		<ul style="list-style-type: none"> The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors. Legal texts have been adapted to the new company name where appropriate. Section 2 "Features": updated second feature Type number TDA9910HW/6 removed from the data sheet Section 7 "Limiting values": output current Max. value updated Section 9 "Characteristics": values updated Figure 4: updated Figure 5: updated 		
TDA9910_3	20060517	Preliminary data sheet	-	TDA9910_2
TDA9910_2 (9397 750 14418)	20041209	Objective data sheet	-	TDA9910_1
TDA9910_1 (9397 750 12905)	20041008	Objective data sheet	-	-

14. Legal information

14.1 Data sheet status

Document status ^{[1][2]}	Product status ^[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

14.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

14.3 Disclaimers

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or

malfunction of a NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

14.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

15. Contact information

For additional information, please visit: <http://www.nxp.com>

For sales office addresses, send an email to: salesaddresses@nxp.com

16. Contents

1	General description	1
2	Features	1
3	Applications	1
4	Ordering information	2
5	Block diagram	2
6	Pinning information	3
6.1	Pinning	3
6.2	Pin description	3
7	Limiting values	5
8	Thermal characteristics	5
9	Characteristics	6
10	Definitions	13
10.1	Static parameters	13
10.1.1	INL (integral non-linearity)	13
10.1.2	DNL (differential non-linearity)	13
10.2	Dynamic parameters	13
10.2.1	SINAD (signal-to-noise and distortion)	14
10.2.2	ENOB (effective number of bits)	14
10.2.3	THD (total harmonic distortion)	14
10.2.4	SNR (signal-to-noise ratio)	14
10.2.5	SFDR (spurious free dynamic range)	14
10.2.6	IMD2 (IMD3)	15
11	Application information	16
11.1	TDA9910 in 3G radio receivers	16
11.2	Application diagram	17
12	Package outline	18
13	Revision history	19
14	Legal information	20
14.1	Data sheet status	20
14.2	Definitions	20
14.3	Disclaimers	20
14.4	Trademarks	20
15	Contact information	20
16	Contents	21

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

founded by

PHILIPS

© NXP B.V. 2007.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 12 June 2007

Document identifier: TDA9910_4