TND306

High-Speed CMOS Product Designation Definitions

Prepared by: Steve West ON Semiconductor



http://onsemi.com

TECHNICAL NOTE

HC vs. HCT

ON Semiconductor's High–Speed CMOS product family, intended to give the designer an alternative to LSTTL. HSCMOS, with the faster speed advantage over metal–gate CMOS (MC14000 series) and the lower power consumption advantage over LSTTL, is an optimum choice for midrange designs. With the availability of high–speed CMOS microprocessors and memories, the ability to design a 100% CMOS system is possible.

HCT devices offer a short–term solution to the TTL/NMOS–to–CMOS interface problem. To achieve this interface capability, some CMOS advantages had to be compromised. These compromises include power consumption, operating voltage range, and noise immunity.

In most cases HCT devices are drop—in replacements of TTL devices with significant advantages over the TTL devices. However, in some cases, an equivalent HCT device may not replace a TTL device without some form of circuit modification.

Designers can use HCT devices to perform logic level conversions only. In newer designs, the designer wants all the advantages of a true CMOS system and designs using only HC devices.

"A" versus "Non-A"

"A" Versus "Non-A" — ON Semiconductor has a device performance enhancement program for the High-Speed CMOS family. This is indicated by an "A" suffix on the device identification. Some of the characteristics of this "A" enhancement program are improved design, a better quality process, faster performing AC propagation delays and enhancements to various DC characteristics.

The old "Non–A" process was a 5 micron process that was modified to run a 3.5 micron family. The new "A" process is a true 3 micron process and gives better process control, with improved performance and quality.

Please see the specific device data sheet for "A" designation parameters.

TND306

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

Literature Fulfillment:

Literature Distribution Center for ON Semiconductor P.O. Box 5163, Denver, Colorado 80217 USA

Phone: 303–675–2175 or 800–344–3860 Toll Free USA/Canada **Fax:** 303–675–2176 or 800–344–3867 Toll Free USA/Canada

Email: ONlit@hibbertco.com

N. American Technical Support: 800–282–9855 Toll Free USA/Canada

JAPAN: ON Semiconductor, Japan Customer Focus Center 4–32–1 Nishi–Gotanda, Shinagawa–ku, Tokyo, Japan 141–0031

Phone: 81–3–5740–2700 Email: r14525@onsemi.com

ON Semiconductor Website: http://onsemi.com

For additional information, please contact your local

Sales Representative.