



2, 4, and 8-Channel Low-Capacitance ESD Protection Array

CM1230

Features

- Two, four, and eight channels of ESD protection
- Provides ESD protection to IEC61000-4-2 Level 4
 - $\pm 8\text{kV}$ contact discharge
 - $\pm 15\text{kV}$ air discharge
- Low loading capacitance of 0.8pF typical
- Minimal capacitance change with temperature and voltage
- Channel I/O to GND capacitance difference of 0.02pF typical is ideal for differential signals
- Channel I/O to I/O capacitance 0.15pF typical
- Zener diode protects supply rail and eliminates the need for external by-pass capacitors
- Each I/O pin can withstand over 1000 ESD strikes*
- Available in 4, 6 and 10 bump Chip Scale Packages (CSP)
- *OptiGuard™* coated for improved reliability at assembly
- RoHS-compliant, lead-free version finishing

Applications




- LCD and camera data lines in wireless handsets that use high-speed serial interfaces.
- I/O port protection for mobile handsets, notebook computers, DSCs, MP3 players, PDAs, etc. including USB, 1394 and serial ATA
- Wireless handsets
- Handheld PCs/PDAs
- LCD and camera modules

Product Description

The CM1230 is a family of 2, 4 and 8 channel, very low capacitance ESD protection diode arrays in a CSP form factor. It is ideal for protecting systems with high data and clock rates or for circuits that need low capacitive loading. Each channel consists of a pair of ESD diodes that act as clamp diodes to steer ESD current pulses to either the positive or negative supply rail. A zener diode is integrated between the positive and negative supply rails. The V_{CC} rail is protected from ESD strikes and eliminates the need for a bypass capacitor to absorb positive ESD strikes to ground. Each channel can safely dissipate ESD strikes of $\pm 8\text{kV}$, meeting the Level 4 requirement of the IEC61000-4-2 international standard as well as $\pm 15\text{kV}$ air discharges per the IEC61000-4-2 specification. Using the MIL-STD-883 (Method 3015) specification for Human Body Model (HBM) ESD, the pins are protected for contact discharges at greater than $\pm 15\text{kV}$.

This device is well-suited for next generation wireless handsets that implement high-speed serial interface solutions for the LCD display and camera interfaces. In these designs, a tolerance above 1.5pF cannot be tolerated when high data rates are transferred between the baseband chipsets and the LCD driver/controller ICs. Higher capacitive loading normally causes the rise and fall times to slow which hampers the functionality of circuit and operation of the wireless handset. The CM1230 incorporates *OptiGuard™* which results in improved reliability at assembly. The CM1230 is available in a space-saving, low profile Chip Scale Package with RoHS-compliant, lead-free finishing.

Electrical Schematic




*Standard test condition is IEC61000-4-2 level 4 test circuit with each (A_{out}/B_{out}) pin subjected to ±12kV contact discharge for 1000 pulses. Discharges are timed at 1 second intervals and all 1000 strikes are completed in one continuous test run.



PACKAGE / PINOUT DIAGRAMS

TOP VIEW
(Bumps Down View)



BOTTOM VIEW
(Bumps Up View)




CM1230-02/J2
4-Bump CSP Package



CM1230-04
6-Bump CSP Package



CM1230-08
10-Bump CSP Package



Notes:
1) These drawings are not to scale.

Ordering Information

PART NUMBERING INFORMATION

# of Channels	Bumps	Package	Ordering Part Number ¹	Part Marking
2	4	CSP-4	CM1230-02CP	L
2	4	CSP-4	CM1230-J2CP	L
4	6	CSP-6	CM1230-04CP	L30
8	10	CSP-10	CM1230-08CP	L308

Note 1: Parts are shipped in Tape and Reel form unless otherwise specified.

Pin Descriptions

2-CHANNEL, 4-BUMP CSP

PI N	NAME	TYPE	DESCRIPTION
A1	V _N	GND	Negative voltage supply rail
B1	CH2	I/O	ESD Channel
A2	CH1	I/O	ESD Channel
B2	V _P	PWR	Positive voltage supply rail

4-CHANNEL, 6-BUMP CSP

PI N	NAME	TYPE	DESCRIPTION
A1	CH1	I/O	ESD Channel
B1	CH2	I/O	ESD Channel
A2	V _P	PWR	Positive voltage supply rail
B2	V _N	GND	Negative voltage supply rail
A3	CH3	I/O	ESD Channel
B3	CH4	I/O	ESD Channel

8-CHANNEL, 10-BUMP CSP

PI N	NAME	TYPE	DESCRIPTION
A1	CH1	I/O	ESD Channel
B1	CH2	I/O	ESD Channel
A2	CH3	I/O	ESD Channel
B2	CH4	I/O	ESD Channel
A3	V _P	PWR	Positive voltage supply rail
B3	V _N	GND	Negative voltage supply rail
A4	CH5	I/O	ESD Channel
B4	CH6	I/O	ESD Channel
A5	CH7	I/O	ESD Channel
B5	CH8	I/O	ESD Channel

Specifications

ABSOLUTE MAXIMUM RATINGS

PARAMETER	RATING	UNITS
Operating Supply Voltage ($V_P - V_N$)	6.0	V
Operating Temperature Range	-40 to +85	°C
Storage Temperature Range	-65 to +150	°C
DC Voltage at any channel input	$(V_N - 0.5)$ to $(V_P + 0.5)$	V

STANDARD OPERATING CONDITIONS

PARAMETER	RATING	UNITS
Operating Temperature Range	-40 to +85	°C

ELECTRICAL OPERATING CHARACTERISTICS (SEE NOTE 1)

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
V_P	Operating Supply Voltage (V_P-V_N)			3.3	5.5	V
I_P	Operating Supply Current	$(V_P-V_N)=3.3V$			8.0	μA
V_F	Diode Forward Voltage Top Diode Bottom Diode	$I_F = 8mA; T_A=25^\circ C$	0.60 0.60	0.80 0.80	0.95 0.95	V V
I_{LEAK}	Channel Leakage Current	$T_A=25^\circ C; V_P=5V, V_N=0V,$ $V_{IN} = 0V \text{ to } 5V$		± 0.1	± 1.0	μA
C_{IN}	Channel Input Capacitance	At 1 MHz, $V_P=3.3V, V_N=0V,$ $V_{IN}=1.65V$		0.8	1.20	pF
ΔC_{IN}	Channel Input Capacitance Matching	At 1 MHz, $V_P=3.3V, V_N=0V,$ $V_{IN}=1.65V$		0.02		pF
C_{MUTUAL}	Mutual Capacitance between signal pin and adjacent signal pin	At 1 MHz, $V_P=3.3V, V_N=0V,$ $V_{IN}=1.65V$		0.15		pF
V_{ESD}	In-system ESD Protection Peak Discharge Voltage at any channel input, in system a) Contact discharge per IEC 61000-4-2 standard b) Human Body Model, MIL-STD-883, Method 3015	Notes 3 and 4; $T_A=25^\circ C$ Notes 2 and 4; $T_A=25^\circ C$	± 8 ± 15			kV kV
V_{CL}	Channel Clamp Voltage Positive Transients Negative Transients	$T_A=25^\circ C, I_{PP} = 1A, t_p = 8/20\mu S;$ Note 4		+9.8 -1.8		V V
R_{DYN}	Dynamic Resistance Positive Transients Negative Transients	$I_{PP} = 1A, t_p = 8/20\mu S$ Any I/O pin to Ground; Note 4		0.76 0.56		Ω Ω

Note 1: All parameters specified at $T_A = -40^\circ C$ to $+85^\circ C$ unless otherwise noted.

Note 2: Human Body Model per MIL-STD-883, Method 3015, $C_{Discharge} = 100pF, R_{Discharge} = 1.5K\Omega, V_P = 3.3V, V_N$ grounded.


Note 3: Standard IEC 61000-4-2 with $C_{Discharge} = 150pF, R_{Discharge} = 330\Omega, V_P = 3.3V, V_N$ grounded.

Note 4: These measurements performed with no external capacitor on V_P .

Note 5: Measured under pulsed conditions, pulse width = 0.7ms, maximum current = 1.5A.


Performance Information

Input Channel Capacitance Performance Curves



Typical Variation of C_{IN} vs. V_{IN}

($f=1\text{MHz}$, $V_P = 3.3\text{V}$, $V_N = 0\text{V}$, $0.1\ \mu\text{F}$ chip capacitor between V_P and V_N , $T_A = 25^\circ\text{C}$)




Typical Variation of C_{IN} vs. Temp


($f=1\text{MHz}$, $V_{IN}=30\text{mV}$, $V_P = 3.3\text{V}$, $V_N = 0\text{V}$, $0.1\ \mu\text{F}$ chip capacitor between V_P and V_N)

Performance Information (Cont'd)

Typical Filter Performance (nominal conditions unless specified otherwise, 50 Ohm Environment)



Insertion Loss VS. Frequency (0V DC Bias, $V_p = 3.3V$)



Insertion Loss VS. Frequency (2.5V DC Bias, $V_p = 3.3V$)

Application Information

PARAMETER	VALUE
Pad Size on PCB	0.240mm
Pad Shape	Round
Pad Definition	Non-Solder Mask defined pads
Solder Mask Opening	0.290mm Round
Solder Stencil Thickness	0.125mm - 0.150mm
Solder Stencil Aperture Opening (laser cut, 5% tapered walls)	0.300mm Round
Solder Flux Ratio	50/50 by volume
Solder Paste Type	No Clean
Pad Protective Finish	OSP (Entek Cu Plus 106A)
Tolerance — Edge To Corner Ball	$\pm 50\mu\text{m}$
Solder Ball Side Coplanarity	$\pm 20\mu\text{m}$
Maximum Dwell Time Above Liquidous	60 seconds
Maximum Soldering Temperature for Lead-free Devices using a Lead-free Solder Paste	260°C




Figure 8. Recommended Non-Solder Mask Defined Pad Illustration




Figure 9. Lead-free (SnAgCu) Solder Ball Reflow Profile


CM1230

Mechanical Details

CSP-4 Mechanical Specifications (CM1230-02CP)

The CM1230-02CP is supplied in a 4 bump Chip Scale Package (CSP). Dimensions are shown below. For complete information on the CSP, see the California Micro Devices CSP Package Information document.

PACKAGE DIMENSIONS						
Package	Custom CSP					
Bumps	4					
Dim	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A1	0.915	0.960	1.005	0.0360	0.0378	0.0396
A2	0.915	0.960	1.005	0.0360	0.0378	0.0396
B1	0.495	0.500	0.505	0.0195	0.0197	0.0199
B2	0.495	0.500	0.505	0.0195	0.0197	0.0199
C1	0.180	0.230	0.280	0.0071	0.0091	0.0110
C2	0.180	0.230	0.280	0.0071	0.0091	0.0110
D1	0.575	0.644	0.714	0.0226	0.0254	0.0281
D2	0.368	0.419	0.470	0.0145	0.0165	0.0185
# per tape and reel	3500 pieces					
Controlling dimension: millimeters						



**Package Dimensions for
CM1230-02CP Chip Scale Package**

CSP Tape and Reel Specifications

PART NUMBER	CHIP SIZE (mm)	POCKET SIZE (mm) $B_0 \times A_0 \times K_0$	TAPE WIDTH W	REEL DIAMETER	QTY PER REEL	P_0	P_1
CM1230-02CP*	0.96 x 0.96 x 0.644	1.14 x 1.00 x 0.70	8mm	178mm (7")	3500	4mm	4mm




Figure 3. Tape and Reel Mechanical Data*

* CM1230-02CP and CM1230-J2CP are the same mechanical package. The only difference is the Pin 1 orientation (red dot) on the tape and reel.


CM1230

Mechanical Details (cont'd)

CSP-4 Mechanical Specifications (CM1230-J2CP)

The CM1230-J2CP is supplied in a 4 bump Chip Scale Package (CSP). Dimensions are shown below. For complete information on the CSP, see the California Micro Devices CSP Package Information document.

PACKAGE DIMENSIONS						
Package	Custom CSP					
Bumps	4					
Dim	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A1	0.915	0.960	1.005	0.0360	0.0378	0.0396
A2	0.915	0.960	1.005	0.0360	0.0378	0.0396
B1	0.495	0.500	0.505	0.0195	0.0197	0.0199
B2	0.495	0.500	0.505	0.0195	0.0197	0.0199
C1	0.180	0.230	0.280	0.0071	0.0091	0.0110
C2	0.180	0.230	0.280	0.0071	0.0091	0.0110
D1	0.575	0.644	0.714	0.0226	0.0254	0.0281
D2	0.368	0.419	0.470	0.0145	0.0165	0.0185
# per tape and reel	3500 pieces					
Controlling dimension: millimeters						



**Package Dimensions for
CM1230-J2CP Chip Scale Package**

CSP Tape and Reel Specifications

PART NUMBER	CHIP SIZE (mm)	POCKET SIZE (mm) $B_0 \times A_0 \times K_0$	TAPE WIDTH W	REEL DIAMETER	QTY PER REEL	P_0	P_1
CM1230-J2CP*	0.96 x 0.96 x 0.644	1.14 x 1.00 x 0.70	8mm	178mm (7")	3500	4mm	4mm




Figure 4. Tape and Reel Mechanical Data*

*CM1230-02CP and CM1230-J2CP are the same mechanical package. Only difference is the Pin 1 orientation (red dot) on the tape and reel.


CM1230

Mechanical Details (cont'd)

CSP-6 Mechanical Specifications

The CM1230-04CP is supplied in a 6 bump Chip Scale Package (CSP). Dimensions are shown below. For complete information on the CSP, see the California Micro Devices CSP Package Information document.

PACKAGE DIMENSIONS						
Package	Custom CSP					
Bumps	6					
Dim	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A1	0.915	0.960	1.005	0.0360	0.0378	0.0396
A2	1.415	1.460	1.505	0.0557	0.0575	0.0593
B1	0.495	0.500	0.505	0.0195	0.0197	0.0199
B2	0.495	0.500	0.505	0.0195	0.0197	0.0199
C1	0.180	0.230	0.280	0.0071	0.0091	0.0110
C2	0.180	0.230	0.280	0.0071	0.0091	0.0110
D1	0.575	0.644	0.714	0.0226	0.0254	0.0281
D2	0.368	0.419	0.470	0.0145	0.0165	0.0185
# per tape and reel	3500 pieces					
Controlling dimension: millimeters						



**Package Dimensions for
CM1230-04CP Chip Scale Package**

CSP Tape and Reel Specifications

PART NUMBER	CHIP SIZE (mm)	POCKET SIZE (mm) $B_0 \times A_0 \times K_0$	TAPE WIDTH W	REEL DIAMETER	QTY PER REEL	P_0	P_1
CM1230-04CP	1.46 x 0.96 x 0.644	1.72 x 1.17 x 0.73	8mm	178mm (7")	3500	4mm	4mm




Figure 5. Tape and Reel Mechanical Data

CM1230


Mechanical Details (cont'd)

CSP-10 Mechanical Specifications

The CM1230-08CP is supplied in a 10 bump Chip Scale Package (CSP). Dimensions are shown below. For complete information on the CSP, see the California Micro Devices CSP Package Information document.

PACKAGE DIMENSIONS						
Package	Custom CSP					
Bumps	10					
Dim	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A1	0.915	0.960	1.005	0.0360	0.0378	0.0396
A2	2.415	2.460	2.505	0.0951	0.0969	0.0986
B1	0.495	0.500	0.505	0.0195	0.0197	0.0199
B2	0.495	0.500	0.505	0.0195	0.0197	0.0199
C1	0.180	0.230	0.280	0.0071	0.0091	0.0110
C2	0.180	0.230	0.280	0.0071	0.0091	0.0110
D1	0.575	0.644	0.714	0.0226	0.0254	0.0281
D2	0.368	0.419	0.470	0.0145	0.0165	0.0185
# per tape and reel	3500 pieces					

Controlling dimension: millimeters



**Package Dimensions for
CM1230-08CP Chip Scale Package**

CSP Tape and Reel Specifications

PART NUMBER	CHIP SIZE (mm)	POCKET SIZE (mm) B ₀ X A ₀ X K ₀	TAPE WIDTH W	REEL DIAMETER	QTY PER REEL	P ₀	P ₁
CM1230-08CP	2.46 x 0.96 x 0.644	2.62 x 1.12 x 0.76	8mm	178mm (7")	3500	4mm	4mm





Figure 6. Tape and Reel Mechanical Data

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855
Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
For additional information, please contact your local Sales Representative