



ON Semiconductor®

www.onsemi.com

NDPL070N10B

Advance Information

Power MOSFET 100V, 10.8mΩ, 70A, N-Channel

Features

- Low On-Resistance
- Low Gate Charge
- High Speed Switching
- 100% Avalanche Tested
- Pb-Free and RoHS Compliance

Applications

Specifications

Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Value	Unit
Drain to Source Voltage	V _{DSS}	100	V
Gate to Source Voltage	V _{GSS}	±20	V
Drain Current (DC)	I _D	70	A
Drain Current (Pulse) PW≤10μs, duty cycle≤1%	I _{DP}	280	A
Power Dissipation Tc=25°C	P _D	2.1 72	W
Junction Temperature	T _J	175	°C
Storage Temperature	T _{stg}	-55 to +175	°C
Source Current (Body Diode)	I _S	70	A
Avalanche Energy (Single Pulse) *1	E _{AS}	82	mJ
Lead Temperature for Soldering Purposes, 3mm from Case for 10 Seconds	T _L	260	°C

Thermal Resistance Ratings

Parameter	Symbol	Value	Unit
Junction to Case Steady State	R _{θJC}	2.08	°C/W
Junction to Ambient *2	R _{θJA}	71.4	


Note : *1 V_{DD}=48V, L=100μH, I_{AV}=30A (Fig.1)

*2 Insertion mounted


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

V _{DSS}	R _{DSON} Max	I _D Max
100V	10.8 mΩ@15V	70A
	12.8 mΩ@10V	


Electrical Connection N-Channel



Marking



TO-220-3L



This document contains information on a new product. Specifications and information herein are subject to change without notice.

ORDERING INFORMATION

See detailed ordering and shipping information on page 5 of this data sheet.

NDPL070N10B

Electrical Characteristics at Ta = 25°C

Parameter	Symbol	Conditions	Value			Unit
			min	typ	max	
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	$I_D=10mA, V_{GS}=0V$	100			V
Zero-Gate Voltage Drain Current	I_{DSS}	$V_{DS}=100V, V_{GS}=0V$			10	μA
Gate to Source Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$			± 100	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=10V, I_D=1mA$	2		4	V
Forward Transconductance	g_{FS}	$V_{DS}=10V, I_D=35A$		50		S
Static Drain to Source On-State Resistance	$R_{DS(on)1}$	$I_D=35A, V_{GS}=15V$		9.0	10.8	m Ω
	$R_{DS(on)2}$	$I_D=35A, V_{GS}=10V$		9.8	12.8	m Ω
Input Capacitance	C_{iss}	$V_{DS}=50V, f=1MHz$		2,010		pF
Output Capacitance	C_{oss}			840		pF
Reverse Transfer Capacitance	C_{rss}			21		pF
Turn-ON Delay Time	$t_{d(on)}$			30		ns
Rise Time	t_r	See Fig.2		180		ns
Turn-OFF Delay Time	$t_{d(off)}$			55		ns
Fall Time	t_f			40		ns
Total Gate Charge	Q_g	$V_{DS}=48V, V_{GS}=10V, I_D=70A$		26		nC
Gate to Source Charge	Q_{gs}			9		nC
Gate to Drain "Miller" Charge	Q_{gd}			8		nC
Forward Diode Voltage	V_{SD}	$I_S=70A, V_{GS}=0V$		1.1	1.5	V
Reverse Recovery Time	t_{rr}	See Fig.3		95		ns
Reverse Recovery Charge	Q_{rr}	$I_S=70A, V_{GS}=0V, di/dt=100A/\mu s$		240		nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Fig.1 Unclamped Inductive Switching Test Circuit




Fig.2 Switching Time Test Circuit


















Fig.3 Reverse Recovery Time Test Circuit



NDPL070N10B



NDPL070N10B



NDPL070N10B

Package Dimensions

NDPL070N10BG


TO-220, 3-Lead/TO-220-3L

CASE 221AU

ISSUE O

unit : mm

- 1:Gate
- 2:Drain
- 3:Source



ORDERING INFORMATION

Device	Package	Shipping	note
NDPL070N10BG	TO-220-3L SC-46, TO-220AB	50 pcs. / tube	Pb-Free

Note on usage : Since the NDPL070N10B is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.