

NST3946DXV6T1G, NST3946DXV6T5G

Dual General Purpose Transistor

The NST3946DXV6T1 device is a spin-off of our popular SOT-23/SOT-323 three-leaded device. It is designed for general purpose amplifier applications and is housed in the SOT-563 six-leaded surface mount package. By putting two discrete devices in one package, this device is ideal for low-power surface mount applications where board space is at a premium.

- h_{FE} , 100–300
- Low $V_{CE(sat)}$, ≤ 0.4 V
- Simplifies Circuit Design
- Reduces Board Space
- Reduces Component Count
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector – Emitter Voltage (NPN) (PNP)	V_{CEO}	40 -40	Vdc
Collector – Base Voltage (NPN) (PNP)	V_{CBO}	60 -40	Vdc
Emitter – Base Voltage (NPN) (PNP)	V_{EBO}	6.0 -5.0	Vdc
Collector Current – Continuous (NPN) (PNP)	I_C	200 -200	mAdc
Electrostatic Discharge	ESD	HBM>16000, MM>2000	V

THERMAL CHARACTERISTICS


Characteristic (One Junction Heated)	Symbol	Max	Unit
Total Device Dissipation $T_A = 25^\circ\text{C}$	P_D	357 (Note 1) 2.9 (Note 1)	mW $\text{mW}/^\circ\text{C}$
Thermal Resistance Junction-to-Ambient	$R_{\theta JA}$	350 (Note 1)	$^\circ\text{C}/\text{W}$
Characteristic (Both Junctions Heated)	Symbol	Max	Unit
Total Device Dissipation $T_A = 25^\circ\text{C}$	P_D	500 (Note 1) 4.0 (Note 1)	mW $\text{mW}/^\circ\text{C}$

1. FR-4 @ Minimum Pad



ON Semiconductor®

<http://onsemi.com>



NST3946DXV6T1*

*Q1 PNP
Q2 NPN



SOT-563
CASE 463A
PLASTIC

MARKING DIAGRAM



46 = Specific Device Code
M = Date Code
▪ = Pb-Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
NST3946DXV6T1G	SOT-563 (Pb-Free)	4000/Tape & Reel
NST3946DXV6T5G	SOT-563 (Pb-Free)	8000/Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

NST3946DXV6T1G, NST3946DXV6T5G

Characteristic (Both Junctions Heated)	Symbol	Max	Unit
Thermal Resistance Junction-to-Ambient	$R_{\theta JA}$	250 (Note 1)	°C/W
Junction and Storage Temperature Range	T_J, T_{stg}	-55 to +150	°C

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ C$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS				
Collector – Emitter Breakdown Voltage (Note 2) ($I_C = 1.0 \text{ mA}_\text{dc}, I_B = 0$) ($I_C = -1.0 \text{ mA}_\text{dc}, I_B = 0$)	$V_{(\text{BR})\text{CEO}}$ (NPN) (PNP)	40 -40	— —	Vdc
Collector – Base Breakdown Voltage ($I_C = 10 \mu\text{A}_\text{dc}, I_E = 0$) ($I_C = -10 \mu\text{A}_\text{dc}, I_E = 0$)	$V_{(\text{BR})\text{CBO}}$ (NPN) (PNP)	60 -40	— —	Vdc
Emitter – Base Breakdown Voltage ($I_E = 10 \mu\text{A}_\text{dc}, I_C = 0$) ($I_E = -10 \mu\text{A}_\text{dc}, I_C = 0$)	$V_{(\text{BR})\text{EBO}}$ (NPN) (PNP)	6.0 -5.0	— —	Vdc
Base Cutoff Current ($V_{CE} = 30 \text{ Vdc}, V_{EB} = 3.0 \text{ Vdc}$) ($V_{CE} = -30 \text{ Vdc}, V_{EB} = -3.0 \text{ Vdc}$)	I_{BL} (NPN) (PNP)	— —	50 -50	nAdc
Collector Cutoff Current ($V_{CE} = 30 \text{ Vdc}, V_{EB} = 3.0 \text{ Vdc}$) ($V_{CE} = -30 \text{ Vdc}, V_{EB} = -3.0 \text{ Vdc}$)	I_{CEX} (NPN) (PNP)	— —	50 -50	nAdc

ON CHARACTERISTICS (Note 2)

DC Current Gain ($I_C = 0.1 \text{ mA}_\text{dc}, V_{CE} = 1.0 \text{ Vdc}$) ($I_C = 1.0 \text{ mA}_\text{dc}, V_{CE} = 1.0 \text{ Vdc}$) ($I_C = 10 \text{ mA}_\text{dc}, V_{CE} = 1.0 \text{ Vdc}$) ($I_C = 50 \text{ mA}_\text{dc}, V_{CE} = 1.0 \text{ Vdc}$) ($I_C = 100 \text{ mA}_\text{dc}, V_{CE} = 1.0 \text{ Vdc}$) ($I_C = -0.1 \text{ mA}_\text{dc}, V_{CE} = -1.0 \text{ Vdc}$) ($I_C = -1.0 \text{ mA}_\text{dc}, V_{CE} = -1.0 \text{ Vdc}$) ($I_C = -10 \text{ mA}_\text{dc}, V_{CE} = -1.0 \text{ Vdc}$) ($I_C = -50 \text{ mA}_\text{dc}, V_{CE} = -1.0 \text{ Vdc}$) ($I_C = -100 \text{ mA}_\text{dc}, V_{CE} = -1.0 \text{ Vdc}$)	h_{FE} (NPN) (PNP)	40 70 100 60 30 60 80 100 60 30	— — 300 — — — — 300 — —	— — — — — — — — — —
Collector – Emitter Saturation Voltage ($I_C = 10 \text{ mA}_\text{dc}, I_B = 1.0 \text{ mA}_\text{dc}$) ($I_C = 50 \text{ mA}_\text{dc}, I_B = 5.0 \text{ mA}_\text{dc}$) ($I_C = -10 \text{ mA}_\text{dc}, I_B = -1.0 \text{ mA}_\text{dc}$) ($I_C = -50 \text{ mA}_\text{dc}, I_B = -5.0 \text{ mA}_\text{dc}$)	$V_{CE(\text{sat})}$ (NPN) (PNP)	— — — —	0.2 0.3 -0.25 -0.4	Vdc
Base – Emitter Saturation Voltage ($I_C = 10 \text{ mA}_\text{dc}, I_B = 1.0 \text{ mA}_\text{dc}$) ($I_C = 50 \text{ mA}_\text{dc}, I_B = 5.0 \text{ mA}_\text{dc}$) ($I_C = -10 \text{ mA}_\text{dc}, I_B = -1.0 \text{ mA}_\text{dc}$) ($I_C = -50 \text{ mA}_\text{dc}, I_B = -5.0 \text{ mA}_\text{dc}$)	$V_{BE(\text{sat})}$ (NPN) (PNP)	0.65 — -0.65 —	0.85 0.95 -0.85 -0.95	Vdc

2. Pulse Test: Pulse Width $\leq 300 \mu\text{s}$; Duty Cycle $\leq 2.0\%$.

NST3946DXV6T1G, NST3946DXV6T5G

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted) (Continued)



Characteristic	Symbol	Min	Max	Unit
SMALL-SIGNAL CHARACTERISTICS				
Current-Gain – Bandwidth Product ($I_C = 10 \text{ mA}_\text{dc}$, $V_{CE} = 20 \text{ V}_\text{dc}$, $f = 100 \text{ MHz}$) ($I_C = -10 \text{ mA}_\text{dc}$, $V_{CE} = -20 \text{ V}_\text{dc}$, $f = 100 \text{ MHz}$)	f_T (NPN) (PNP)	300 250	– –	MHz
Output Capacitance ($V_{CB} = 5.0 \text{ V}_\text{dc}$, $I_E = 0$, $f = 1.0 \text{ MHz}$) ($V_{CB} = -5.0 \text{ V}_\text{dc}$, $I_E = 0$, $f = 1.0 \text{ MHz}$)	C_{obo} (NPN) (PNP)	– –	4.0 4.5	pF
Input Capacitance ($V_{EB} = 0.5 \text{ V}_\text{dc}$, $I_C = 0$, $f = 1.0 \text{ MHz}$) ($V_{EB} = -0.5 \text{ V}_\text{dc}$, $I_C = 0$, $f = 1.0 \text{ MHz}$)	C_{ibo} (NPN) (PNP)	– –	8.0 10.0	pF
Input Impedance ($V_{CE} = 10 \text{ V}_\text{dc}$, $I_C = 1.0 \text{ mA}_\text{dc}$, $f = 1.0 \text{ kHz}$) ($V_{CE} = -10 \text{ V}_\text{dc}$, $I_C = -1.0 \text{ mA}_\text{dc}$, $f = 1.0 \text{ kHz}$)	h_{ie} (NPN) (PNP)	1.0 2.0	10 12	k Ω
Voltage Feedback Ratio ($V_{CE} = 10 \text{ V}_\text{dc}$, $I_C = 1.0 \text{ mA}_\text{dc}$, $f = 1.0 \text{ kHz}$) ($V_{CE} = -10 \text{ V}_\text{dc}$, $I_C = -1.0 \text{ mA}_\text{dc}$, $f = 1.0 \text{ kHz}$)	h_{re} (NPN) (PNP)	0.5 0.1	8.0 10	$\times 10^{-4}$
Small-Signal Current Gain ($V_{CE} = 10 \text{ V}_\text{dc}$, $I_C = 1.0 \text{ mA}_\text{dc}$, $f = 1.0 \text{ kHz}$) ($V_{CE} = -10 \text{ V}_\text{dc}$, $I_C = -1.0 \text{ mA}_\text{dc}$, $f = 1.0 \text{ kHz}$)	h_{fe} (NPN) (PNP)	100 100	400 400	–
Output Admittance ($V_{CE} = 10 \text{ V}_\text{dc}$, $I_C = 1.0 \text{ mA}_\text{dc}$, $f = 1.0 \text{ kHz}$) ($V_{CE} = -10 \text{ V}_\text{dc}$, $I_C = -1.0 \text{ mA}_\text{dc}$, $f = 1.0 \text{ kHz}$)	h_{oe} (NPN) (PNP)	1.0 3.0	40 60	μmhos
Noise Figure ($V_{CE} = 5.0 \text{ V}_\text{dc}$, $I_C = 100 \mu\text{A}_\text{dc}$, $R_S = 1.0 \text{ k}\Omega$, $f = 1.0 \text{ kHz}$) ($V_{CE} = -5.0 \text{ V}_\text{dc}$, $I_C = -100 \mu\text{A}_\text{dc}$, $R_S = 1.0 \text{ k}\Omega$, $f = 1.0 \text{ kHz}$)	NF (NPN) (PNP)	– –	5.0 4.0	dB

SWITCHING CHARACTERISTICS

Delay Time	($V_{CC} = 3.0 \text{ V}_\text{dc}$, $V_{BE} = -0.5 \text{ V}_\text{dc}$) ($V_{CC} = -3.0 \text{ V}_\text{dc}$, $V_{BE} = 0.5 \text{ V}_\text{dc}$)	(NPN) (PNP)	t_d	– –	35 35	ns
Rise Time	($I_C = 10 \text{ mA}_\text{dc}$, $I_{B1} = 1.0 \text{ mA}_\text{dc}$) ($I_C = -10 \text{ mA}_\text{dc}$, $I_{B1} = -1.0 \text{ mA}_\text{dc}$)	(NPN) (PNP)	t_r	– –	35 35	
Storage Time	($V_{CC} = 3.0 \text{ V}_\text{dc}$, $I_C = 10 \text{ mA}_\text{dc}$) ($V_{CC} = -3.0 \text{ V}_\text{dc}$, $I_C = -10 \text{ mA}_\text{dc}$)	(NPN) (PNP)	t_s	– –	200 225	ns
Fall Time	($I_{B1} = I_{B2} = 1.0 \text{ mA}_\text{dc}$) ($I_{B1} = I_{B2} = -1.0 \text{ mA}_\text{dc}$)	(NPN) (PNP)	t_f	– –	50 75	

NST3946DXV6T1G, NST3946DXV6T5G

(NPN)



* Total shunt capacitance of test jig and connectors

**Figure 1. Delay and Rise Time
Equivalent Test Circuit**

**Figure 2. Storage and Fall Time
Equivalent Test Circuit**

TYPICAL TRANSIENT CHARACTERISTICS




Figure 3. Capacitance

NST3946DXV6T1G, NST3946DXV6T5G

(NPN)




Figure 4. Turn-On Time




Figure 5. Rise Time




Figure 6. Storage Time




Figure 7. Fall Time

TYPICAL AUDIO SMALL-SIGNAL CHARACTERISTICS NOISE FIGURE VARIATIONS

($V_{CE} = 5.0 \text{ Vdc}$, $T_A = 25^\circ\text{C}$, Bandwidth = 1.0 Hz)




Figure 8. Noise Figure




Figure 9. Noise Figure

NST3946DXV6T1G, NST3946DXV6T5G

(NPN)

h PARAMETERS

($V_{CE} = 10$ Vdc, $f = 1.0$ kHz, $T_A = 25^\circ\text{C}$)




Figure 10. Current Gain




Figure 11. Output Admittance




Figure 12. Input Impedance




Figure 13. Voltage Feedback Ratio

NST3946DXV6T1G, NST3946DXV6T5G

(NPN)

TYPICAL STATIC CHARACTERISTICS




Figure 14. DC Current Gain




Figure 15. Collector Saturation Region




Figure 16. "ON" Voltages





Figure 17. Temperature Coefficients

NST3946DXV6T1G, NST3946DXV6T5G

(PNP)



* Total shunt capacitance of test jig and connectors

TYPICAL TRANSIENT CHARACTERISTICS




Figure 20. Capacitance

— $T_J = 25^\circ\text{C}$
- - $T_J = 125^\circ\text{C}$





Figure 21. Turn-On Time

Figure 22. Fall Time

NST3946DXV6T1G, NST3946DXV6T5G

(PNP)

TYPICAL AUDIO SMALL-SIGNAL CHARACTERISTICS NOISE FIGURE VARIATIONS

($V_{CE} = -5.0$ Vdc, $T_A = 25^\circ\text{C}$, Bandwidth = 1.0 Hz)




Figure 23.




Figure 24.

h PARAMETERS

($V_{CE} = -10$ Vdc, $f = 1.0$ kHz, $T_A = 25^\circ\text{C}$)




Figure 25. Current Gain




Figure 26. Output Admittance




Figure 27. Input Impedance




Figure 28. Voltage Feedback Ratio

NST3946DXV6T1G, NST3946DXV6T5G

(PNP)

TYPICAL STATIC CHARACTERISTICS




Figure 29. DC Current Gain




Figure 30. Collector Saturation Region




Figure 31. "ON" Voltages





Figure 32. Temperature Coefficients

NST3946DXV6T1G, NST3946DXV6T5G

PACKAGE DIMENSIONS


SOT-563, 6 LEAD CASE 463A-01 ISSUE F



NOTES:
 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: MILLIMETERS
 3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.50	0.55	0.60	0.020	0.021	0.023
b	0.17	0.22	0.27	0.007	0.009	0.011
C	0.08	0.12	0.18	0.003	0.005	0.007
D	1.50	1.60	1.70	0.059	0.062	0.066
E	1.10	1.20	1.30	0.043	0.047	0.051
e	0.5 BSC			0.02 BSC		
L	0.10	0.20	0.30	0.004	0.008	0.012
H _E	1.50	1.60	1.70	0.059	0.062	0.066

SOLDERING FOOTPRINT*



*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and **ON** are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free

USA/Canada

Europe, Middle East and Africa Technical Support:

Phone: 421 33 790 2910

Japan Customer Focus Center

Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative