

Variable Capacitors

1998/1999

Data Handbook PA04



PHILIPS

Let's make things better.

QUALITY ASSURED

Our quality system focuses on the continuing high quality of our components and the best possible service for our customers. We have a three-sided quality strategy: we apply a system of total quality control and assurance; we operate customer-oriented dynamic improvement programmes; and we promote a partnering relationship with our customers and suppliers.

PRODUCT SAFETY

In striving for state-of-the-art perfection, we continuously improve components and processes with respect to environmental demands. Our components offer no hazard to the environment in normal use when operated or stored within the limits specified in the data sheet.

Some components unavoidably contain substances that, if exposed by accident or misuse, are potentially hazardous to health. Users of these components are informed of the danger by warning notices in the data sheets supporting the components. Where necessary the warning notices also indicate safety precautions to be taken and disposal instructions to be followed. Obviously users of these components, in general the set-making industry, assume responsibility towards the consumer with respect to safety matters and environmental demands.

All used or obsolete components should be disposed of according to the regulations applying at the disposal location. Depending on the location, electronic components are considered to be 'chemical', 'special' or sometimes 'industrial' waste. Disposal as domestic waste is usually not permitted.

Variable Capacitors

CONTENTS

	Page
SELECTION GUIDE	3
PRODUCT DATA	
2222 808 Ø5 mm	6
2222 808 Ø7.5 mm	14
2222 808 Ø10 mm	22
2222 809 05...	31
2222 809 07...	38
2222 809 080..	43
2222 809 090..	49
DATA HANDBOOK SYSTEM	57

DEFINITIONS

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Application information	
Where application information is given, it is advisory and does not form part of the specification.	








LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.

Variable Capacitors

Selection guide

FILM DIELECTRIC TRIMMERS

HOUSING DIMENSIONS (mm)	C_{min}/C_{max} (pF)	RATED VOLTAGE (V)	TEMP. COEFF. ($10^{-6}/K$)	DIELECTRIC/ TEMP. RANGE (°C)	CATALOGUE NUMBER	PAGE
General purpose						
Ø5 	0.35/1.5 to 4/27	150	-450 ±550 to -200 ±550	PP: -40 to +70 PC, PTFE: -40 to +85	2222 808	6
Ø7.5 	1.4/5.5 to 3/50	250	-250 ±800 to -50 ±500	PP: -40 to +70 PE, PC, PTFE, PET: -40 to +85	2222 808	14
Ø10 	2.5/15 to 7/105	150	-200 ±700 to -50 ±400	PP: -40 to +70 PC, PTFE: -40 to +85	2222 808	22
Professional purpose						
6 × 8 × 9 	0.5/2 to 2/18	300	-250 ±350	-40 to +125	2222 809 05...	31
11 × 14 × 9 	2/12 to 7/150	200	0 ±200	-40 to +125	2222 809 07...	38
10 × 11 × 11 	4/38 and 5/57	250	-200 ±250	-40 to +125	2222 809 080..	43
8 × 9 × 10 	1.4/5.5 to 3/18	250	-250 ±350	-40 to +125	2222 809 090..	49

PRODUCT DATA

Film dielectric trimmers

2222 808

Ø5 mm

FEATURES

- Housing diameter 5 mm
- Top and bottom or top adjustment
- Round or hexagonal head
- Vertical version.

APPLICATIONS

- For consumer and industrial equipment.

DESCRIPTION

The vanes of the trimmer are stacked on a sturdy plastic base. The colour of the base indicates the maximum capacitance (see Tables 4, 5 and 6). The dielectric is a film of polypropylene (PP) or polytetrafluorethylene (PTFE) for the standard versions and polycarbonate (PC) for the economic and hexagonal head versions. The dielectric supports the vanes in such a way that good stability is ensured and no microphony can occur.

Flux absorption between the vanes is prevented.

Cleaning with solvents is not advised.

For outline drawings and dimensions see Figs 1 and 2.

QUALITY LEVEL

Sampling and data evaluation for quality level in accordance with "MIL-STD-105D" and "IEC 60410":

<0.15% major defects

<0.65% minor defects.

Each capacitor is tested for minimum C_{\max} and is also subjected to the full test voltage.

QUICK REFERENCE DATA

DESCRIPTION	VALUE
C_{\min}/C_{\max}	0.35/1.5 to 4/27 pF
Rated voltage (DC)	150 V
Test voltage (DC) for 1 minute	300 V
Maximum contact resistance	10 mΩ
Minimum insulation resistance	10000 MΩ
Tan δ at C_{\max} , 1 MHz:	
PC	$\leq 70 \times 10^{-4}$
PP, PTFE	$\leq 10 \times 10^{-4}$
Category temperature range:	
PP	-40 to +70 °C
PC, PTFE	-40 to +85 °C
Climatic category (IEC 60068):	
PP	40/070/21
PC, PTFE	40/085/21
Minimum storage temperature	-55 °C
Related specification	IEC 60418-1 and 4


MECHANICAL DATA

DESCRIPTION	VALUE
Effective angle of rotation	180°
Operating torque:	
$C_{\max} < 20$ pF	1 to 15 mNm
$C_{\max} \geq 20$ pF	1 to 25 mNm
Maximum axial thrust	2 N


Film dielectric trimmers

2222 808

Ø5 mm



a. Dimensional outlines.



b. Hole pattern.

Dimensions in mm.

For dimensions H, W and L, see Tables 1 and 2.

For dimension P, see Table 3.


(1) The position of the shaft is not relative to the position of the vanes.

Fig.1 Trimmers 2222 808 series, with round head.


Film dielectric trimmers

2222 808

Ø5 mm



a. Dimensional outlines.



b. Hole pattern.

Dimensions in mm.

For dimensions H, W and L, see Table 2.

For dimension P, see Table 3.

Fig.2 Trimmers 2222 808 series, with hexagonal head.

Film dielectric trimmers

2222 808

Ø5 mm

Table 1 Standard versions; capacitance and relevant physical dimensions; see Fig.1

C_{\min}/C_{\max} (pF)	H_{\max} (mm)	W_{\max} (mm)	L_{\max} (mm)
0.35/1.5	7.0	5.5	7.3
1.5/5	7.0	5.5	7.3
3/10	7.0	5.5	7.3
3/15	8.8	5.5	7.3
4/20	8.8	5.5	7.3
4/27	9.0	6.2	7.8

Table 2 Hexagonal and economic versions; relevant physical dimensions; see Fig.2

TYPE OF HEAD	H_{\max} (mm)	W_{\max} (mm)	L_{\max} (mm)
Hexagonal	9.7	5.5	7.3
Round	7.7	5.5	7.3

MOUNTING

The trimmer has a lead pitch of 5.08 mm or 5.6 mm and can be mounted on printed-circuit boards with a minimum hole diameter of 1.25 mm.

PACKAGING

Bulk packaged in cardboard boxes lined with expanded plastic, 1000 units per box.

Film dielectric trimmers

2222 808

Ø5 mm

ORDERING INFORMATION

Table 3 Selection chart; see Figs 1 and 2

C_{\min}/C_{\max} (pF)	CATALOGUE NUMBER 2222 808		
	TOP AND BOTTOM ADJUSTMENT (P = 5.6 mm)	TOP ADJUSTMENT ONLY (P = 5.6 mm)	TOP ADJUSTMENT ONLY (P = 5.08 mm)
Standard versions: polytetrafluorethylene, round head			
0.35/1.5	22158	–	–
Standard versions: polypropylene, round head			
1.5/5	23508	–	20508
3/10	23109	–	20109
3/15	23159	–	20159
4/20	23209	–	20209
4/27	23279	–	20279
Economic versions: polycarbonate, round head			
1.5/7	–	20126	–
1.6/15	–	20127	–
3/20	–	20123	–
3.5/27	–	20128	–
Economic versions: polycarbonate, hexagonal head			
1.5/7	–	21708	–
1.6/15	–	21159	–
3/20	–	21209	–
3.5/27	–	21279	–

Film dielectric trimmers

2222 808

Ø5 mm

ELECTRICAL DATA

Table 4 Standard versions with round head

GUARANTEED MAX. C_{min} / MIN. C_{max} at 200 kHz (pF)	$\tan \delta$ at $C_{max} \times 10^{-4}$		TEMP. COEFF. ⁽¹⁾ ($10^{-6}/K$)	MIN. f_{res} at C_{max} (MHz)	COLOUR OF BASE	SMALLEST PACKAGING QUANTITY	CATALOGUE NUMBER
	1 MHz	100 MHz					
0.35/1.5	≤ 10	—	-450 ± 550	—	—	1000	2222 808 22158
1.5/5	≤ 10	≤ 25	-200 ± 550	700	grey	1000	2222 808 20508
							2222 808 23508
3/10	≤ 10	≤ 25	-250 ± 550	500	yellow	1000	2222 808 20109
							2222 808 23109
3/15	≤ 10	≤ 25	-250 ± 550	400	blue	1000	2222 808 20159
							2222 808 23159
4/20	≤ 10	≤ 25	-250 ± 400	300	green	1000	2222 808 20209
							2222 808 23209
4/27	≤ 10	≤ 25	-250 ± 400	300	red	1000	2222 808 20279
							2222 808 23279

Note

1. C: 60% to 80% of C_{max} ; T_{amb} : from +20 °C to +70 °C.

Table 5 Economic versions with round head

REFERENCE C_{min}/C_{max} (pF)	$\tan \delta$ at $C_{max} \times 10^{-4}$ (1 MHz)	TEMP. COEFF. ($10^{-6}/K$)	COLOUR OF BASE	SMALLEST PACKAGING QUANTITY	CATALOGUE NUMBER
1.5/7	≤ 70	-50 ± 550	grey	1000	2222 808 20126
1.6/15	≤ 70	-50 ± 550	blue	1000	2222 808 20127
3/20	≤ 70	-50 ± 550	green	1000	2222 808 20123
3.5/27	≤ 70	-100 ± 400	red	1000	2222 808 20128

Table 6 Versions with hexagonal head

REFERENCE C_{min}/C_{max} (pF)	$\tan \delta$ at $C_{max} \times 10^{-4}$ (1 MHz)	TEMP. COEFF. ($10^{-6}/K$)	COLOUR OF BASE	SMALLEST PACKAGING QUANTITY	CATALOGUE NUMBER
1.5/7	≤ 70	-50 ± 550	grey	1000	2222 808 21708
1.6/15	≤ 70	-50 ± 550	blue	1000	2222 808 21159
3/20	≤ 70	-50 ± 550	green	1000	2222 808 21209
3.5/27	≤ 70	-100 ± 400	red	1000	2222 808 21279

Film dielectric trimmers

2222 808

Ø5 mm

TESTS AND REQUIREMENTS

Table 7 Test procedures and requirements

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
4.2		method of mounting	method A	
14		capacitance drift	after TC measurement	$\Delta C/C: \leq 3\%$ for $C_{\max} \leq 10$ pF $\Delta C/C: \leq 2\%$ for $C_{\max} > 10$ pF
19		thrust	axial thrust of 2 N	$\Delta C/C: \leq 0.4\%$
21		robustness of terminations:		
21.1	Ua	tensile	1 N	no damage
21.2	Ub	bending	1 cycle	no damage
22	Na	rapid change of temperature	1 cycle; 0.5 hours at lower and 0.5 hours at upper category temperature	$\Delta C/C: \leq 2.5\%$
23	T	soldering:		
	Ta	solderability	solder bath immersion 3 mm; 235 °C; 2 s	good wetting no mechanical damage
	Tb	resistance to heat	solder bath: 260 °C; 10 s	no mechanical damage
24	Eb	impact bump	4000 ±10 bumps; 40 g; 6 ms	$\Delta C/C: \leq 1\%$; no mechanical damage
25	Fc	vibration	frequency 10 to 55 Hz; amplitude 0.75 mm; 1.5 hours	$\Delta C/C: \leq 1\%$; no mechanical damage
26		climatic sequence:		
26.1	B	dry heat	16 hours at upper category temperature	$\Delta C/C: \leq 4\%$ tan δ for PP and PTFE foil: $\leq 15 \times 10^{-4}$ tan δ for PC foil: $\leq 80 \times 10^{-4}$ $R_{\text{ins}}: \geq 10000$ M Ω rotor contact R: ≤ 10 m Ω
26.2	D	damp heat accelerated, first cycle	1 cycle; 24 hours; +40 °C; 95 to 100% RH	voltage proof: 300 V for 1 minute
26.3	Aa	cold	16 hours; -40 °C	visual examination: no mechanical damage
26.5		damp heat accelerated, remaining cycles	1 cycle; 24 hours; +40 °C; 95 to 100% RH	operating torque: 1 to 20 mNm for $C_{\max} < 20$ pF; 1 to 30 mNm for $C_{\max} \geq 20$ pF

Film dielectric trimmers

2222 808

Ø5 mm

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
27	Ca	damp heat steady state	21 days; +40 °C; 90 to 95% RH	$\Delta C/C: \leq 3\%$ $\tan \delta$ for PP and PTFE foil: $\leq 15 \times 10^{-4}$; $\tan \delta$ for PC foil: $\leq 80 \times 10^{-4}$ $R_{ins}: \geq 10000 \text{ M}\Omega$; rotor contact R: $\leq 10 \text{ m}\Omega$ voltage proof: 300 V for 1 minute visual examination: no mechanical damage operating torque: 1 to 20 mNm for $C_{max} < 20 \text{ pF}$; 1 to 30 mNm for $C_{max} \geq 20 \text{ pF}$
29		mechanical endurance	10 cycles	$\Delta C/C: \leq 3\%$ $\Delta C/C$ after axial thrust: $\leq 0.3\%$; rotor contact R: $\leq 10 \text{ m}\Omega$ voltage proof: 300 V for 1 minute visual examination: no mechanical damage operating torque: 0.5 to 22.5 mNm for $C_{max} < 20 \text{ pF}$; 0.5 to 30 mNm for $C_{max} \geq 20 \text{ pF}$

Film dielectric trimmers

2222 808

Ø7.5 mm

FEATURES

- Housing diameter 7.5 mm
- For a basic grid of 2.54 mm (0.1") or 2.50 mm
- Top and bottom or top adjustment
- Vertical and horizontal versions
- Round or hexagonal head.

APPLICATIONS

- For consumer and industrial equipment.

DESCRIPTION

The vanes of the trimmer are stacked on a sturdy plastic base. The colour of the base indicates the maximum capacitance (see Table 2). The dielectric is a film of polypropylene (PP), polyethylene (PE), polycarbonate (PC), polytetrafluorethylene (PTFE), or polyethyleneterephthalate (PET) which supports the vanes in such a way that good stability is ensured and no microphony can occur.

Flux absorption between the vanes is prevented.

Cleaning with solvents is not advised.

Versions are available with either a vertical spindle (see Fig.1), or a horizontal spindle (see Fig.2). Both versions have top adjustment by means of a screwdriver or trimming key and bottom adjustment by means of a key as shown in Fig.5.

For outline drawings and dimensions see Figs 1 and 2.

QUICK REFERENCE DATA

DESCRIPTION	VALUE
C_{min}/C_{max}	1.4/5.5 to 3/50 pF
Rated voltage (DC)	250 V
Test voltage (DC) for 1 minute	500 V
Maximum contact resistance	10 mΩ
Minimum insulation resistance	10000 MΩ
Category temperature range:	
PP	-40 to +70 °C
PE, PC, PTFE, PET	-40 to +85 °C
Climatic category (IEC 60068):	
PP	40/070/21
PE, PC, PTFE, PET	40/085/21
Minimum storage temperature	-55 °C
Related specification	IEC 60418-1 and 4

MECHANICAL DATA

DESCRIPTION	VALUE
Effective angle of rotation	180°
Operating torque:	
$C_{max} < 33$ pF	1 to 15 mNm
$C_{max} \geq 33$ pF	1 to 25 mNm
Maximum axial thrust	2 N

QUALITY LEVEL

Sampling and data evaluation for quality level in accordance with "MIL-STD-105D" and "IEC 60410":

<0.15% major defects


<0.65% minor defects.

Each capacitor is tested for minimum C_{max} and is also subjected to the full test voltage.

Film dielectric trimmers

2222 808

Ø7.5 mm



Dimensions in mm.


For hole pattern see Fig.3.

(1) 11 max. for C_{max} = 40 pF and 50 pF.

Fig.1 Trimmers 2222 808 series, vertical version.

Film dielectric trimmers

2222 808
 $\varnothing 7.5$ mm



Dimensions in mm.

For hole pattern see Fig.4.



(1) 11 max. for $C_{max} = 40$ pF and 50 pF.

Fig.2 Trimmers 2222 808 series, horizontal version.

Film dielectric trimmers


2222 808

Ø7.5 mm



Adjustment

For top adjustment a screwdriver or trimming key can be used; for bottom adjustment a key is required as shown in Fig.5.



Film dielectric trimmers

2222 808

Ø7.5 mm

ORDERING INFORMATION

Table 1 Selection chart

C_{\min}/C_{\max} (pF)	CATALOGUE NUMBER 2222 808			
	VERTICAL VERSION			HORIZONTAL VERSION
	ROUND HEAD		HEXAGONAL HEAD	ROUND HEAD
	TOP AND BOTTOM ADJUSTMENT	TOP ADJUSTMENT ONLY	TOP AND BOTTOM ADJUSTMENT	TOP AND BOTTOM ADJUSTMENT
1.4/5.5	11558	00004	–	51558
2/9	00018	–	–	–
2/10	11109	00005	17109	51109
2/10	–	11004	–	–
2/15	11159	–	–	–
2/18	00016	–	–	–
2.5/20	–	11006	–	–
2.5/22	11229	00006	17229	51229
2.5/27	11279	–	–	51279
3/33	11339	–	–	–
3/40	11409	–	17409	51409
3/50	11509	–	17509	51509

MOUNTING

The trimmer can be mounted on printed-circuit boards with a grid of 2.50 mm or 2.54 mm and a minimum hole diameter of 1.25 mm. For hole patterns see Figs 3 and 4.

PACKAGING

Bulk packaged in cardboard boxes lined with expanded plastic. For smallest packaging quantity (SPQ) see Table 2.

Film dielectric trimmers

2222 808

Ø7.5 mm

ELECTRICAL DATA

Table 2 Electrical characteristics, smallest packaging quantities and catalogue numbers

GUARANTEED MAX. C_{\min} / MIN. C_{\max} at 200 kHz (pF)	SPINDLE SHAPE OF HEAD	FIG.	ADJ. MODE	DIEL.	$\tan \delta$ at $C_{\max} \times 10^{-4}$		TEMP. COEFF. ($10^{-6}/K$)	MIN. f_{res} at C_{\max} (MHz)	COL. OF BASE	SPQ	CATALOGUE NUMBER
					1 MHz	100 MHz					
1.4/5.5	vertical	1	top + bottom	PE	≤ 10	≤ 25	-250 ± 350	850	grey	1400	2222 808 11558
	horizontal	1	top							1400	2222 808 00004
2/9	round	2	top + bottom	PTFE	≤ 10	≤ 15	-150 ± 800	400	yellow	1200	2222 808 51558
	vertical	1	top + bottom							1400	2222 808 00018
2/10	round	1	top + bottom	PP	≤ 10	≤ 25	-250 ± 800	480	yellow	1400	2222 808 11109
	hexag.	1	top							1400	2222 808 00005
	round	2	top + bottom							1400	2222 808 17109
	vertical	1	top							1200	2222 808 51109
2/15	round	1	top	PC	≤ 70	≤ 100	-150 ± 800	250	yellow	1000	2222 808 11004
	vertical	1	top + bottom							1400	2222 808 11159
2/18	round	1	top + bottom	PTFE	≤ 10	≤ 15	-250 ± 600	450	blue	1400	2222 808 11159
	vertical	1	top + bottom							1400	2222 808 00016
2.5/20	round	1	top	PET	≤ 160	-	0 ± 1100	250	green	1000	2222 808 11006
	vertical	1	top + bottom							1400	2222 808 11229
2.5/22	round	1	top	PP	≤ 10	≤ 25	-200 ± 500	350	green	1400	2222 808 00006
	hexag.	1	top							1400	2222 808 17229
	round	2	top + bottom							1200	2222 808 51229
2.5/27	round	1	top + bottom	PC	≤ 70	-	-50 ± 500	350	red	1400	2222 808 11279
	horizontal	2	top + bottom							1200	2222 808 51279
3/33	round	1	top + bottom	PP	≤ 10	-	-250 ± 350	300	brown	1400	2222 808 11339
	vertical	1	top + bottom							1400	2222 808 11409
3/40	hexag.	1	top	PC	≤ 70	-	-50 ± 400	300	violet	1400	2222 808 17409
	round	2	top + bottom							1200	2222 808 51409
	vertical	1	top + bottom							1400	2222 808 11509
3/50	hexag.	1	top	PC	≤ 70	-	-50 ± 500	250	black	1400	2222 808 17509
	round	1	top + bottom							1400	2222 808 17509
	horizontal	2	top + bottom							1200	2222 808 51509

Film dielectric trimmers

2222 808

Ø7.5 mm

TESTS AND REQUIREMENTS

Table 3 Test procedures and requirements

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
4.2		method of mounting	method A	
14		capacitance drift	after TC measurement	$\Delta C/C: \leq 1\%$ for $C_{\max} < 40$ pF; $\Delta C/C: \leq 2.5\%$ for $C_{\max} \geq 40$ pF
19		thrust	axial thrust of 2 N	$\Delta C/C: \leq 0.3\%$
21		robustness of terminations:		
21.1	Ua	tensile	1 N	no damage
21.2	Ub	bending	1 cycle	no damage
22	Na	rapid change of temperature	1 cycle; 0.5 hours at lower and 0.5 hours at upper category temperature	$\Delta C/C: \leq 2\%$
23	T	soldering:		
	Ta	solderability	solder bath immersion 3 mm; 235 °C; 2 s	good wetting no mechanical damage
	Tb	resistance to heat	solder bath: 260 °C; 10 s	no mechanical damage
24	Eb	impact bump	4000 ±10 bumps; 40 g; 6 ms	$\Delta C/C: \leq 0.6\%$; no mechanical damage
25	Fc	vibration	frequency 10 to 55 Hz; amplitude 0.35 mm; 1.5 hours	$\Delta C/C: \leq 0.6\%$; no mechanical damage
26		climatic sequence:		$\Delta C/C: \leq 4$
26.1	B	dry heat	16 hours at upper category temperature	$\tan \delta: \leq 10 \times 10^{-4}$ for $C_{\max} < 27$ pF; $\tan \delta: \leq 70 \times 10^{-4}$ for $C_{\max} \geq 27$ pF; $\tan \delta: \leq 80 \times 10^{-4}$ for $C_{\max} \geq 40$ pF $R_{\text{ins}}: \geq 10000$ MΩ; rotor contact R: ≤ 10 mΩ
26.2	D	damp heat accelerated, first cycle	1 cycle; 24 hours; +40 °C; 95 to 100% RH	voltage proof: 500 V for 1 minute
26.3	Aa	cold	16 hours; -40 °C	visual examination: no mechanical damage
26.5		damp heat accelerated, remaining cycles	1 cycle; 24 hours; +40 °C; 95 to 100% RH	operating torque: 1 to 15 mNm for $C_{\max} < 33$ pF; 1 to 25 mNm for $C_{\max} \geq 33$ pF

Film dielectric trimmers

2222 808

Ø7.5 mm

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
27	Ca	damp heat steady state	21 days; +40 °C; 90 to 95% RH	$\Delta C/C: \leq 5\%$ $\tan \delta: \leq 30 \times 10^{-4}$ for $C_{\max} < 27$ pF; $\tan \delta: \leq 70 \times 10^{-4}$ for $C_{\max} \geq 27$ pF; $\tan \delta: \leq 80 \times 10^{-4}$ for $C_{\max} \geq 40$ pF $R_{\text{ins}}: \geq 10000$ M Ω ; rotor contact R: ≤ 10 m Ω voltage proof: 500 V for 1 minute visual examination: no mechanical damage operating torque: 1 to 15 mNm for $C_{\max} < 33$ pF; 1 to 25 mNm for $C_{\max} \geq 33$ pF
29		mechanical endurance	10 cycles	$\Delta C/C: \leq 1.5\%$ $\Delta C/C$ after axial thrust: $\leq 0.3\%$; rotor contact R: ≤ 10 m Ω voltage proof: 500 V for 1 minute visual examination: no mechanical damage operating torque: 1 to 15 mNm for $C_{\max} < 33$ pF; 1 to 25 mNm for $C_{\max} \geq 33$ pF

Film dielectric trimmers

2222 808

Ø10 mm

FEATURES

- Housing diameter 10 mm
- For a basic grid of 2.54 mm (0.1") or 2.50 mm
- Top and bottom or top adjustment
- Vertical and horizontal versions
- Round or hexagonal head.

APPLICATIONS

- For consumer and industrial equipment.

DESCRIPTION

The vanes of the trimmer are stacked on a sturdy plastic base. The colour of the base indicates the maximum capacitance (see Table 2). The dielectric is a film of polypropylene (PP), polycarbonate (PC) or polytetrafluorethylene (PTFE), which supports the vanes in such a way that good stability is ensured and no microphony can occur.

Flux absorption between the vanes is prevented.

Cleaning with solvents is not advised.

Versions are available with either a vertical spindle (see Figs 1 and 2), or a horizontal spindle (see Fig.3). Both versions have top adjustment by means of a screwdriver or trimming key and bottom adjustment by means of a key as shown in Fig.7.

For outline drawings and dimensions see Figs 1, 2 and 3.

QUICK REFERENCE DATA

DESCRIPTION	VALUE
C_{min}/C_{max}	2.5/15 to 7/105 pF
Rated voltage (DC)	150 V
Test voltage (DC) for 1 minute	300 V
Maximum contact resistance	10 mΩ
Minimum insulation resistance	10000 MΩ
Category temperature range:	
PP	-40 to +70 °C
PC, PTFE	-40 to +85 °C
Climatic category (IEC 60068):	
PP	40/070/21
PC, PTFE	40/085/21
Minimum storage temperature	-55 °C
Related specification	IEC 60418-1 and 4

MECHANICAL DATA

DESCRIPTION	VALUE
Effective angle of rotation	180°
Operating torque	2 to 25 mNm
Maximum axial thrust	2 N

QUALITY LEVEL

Sampling and data evaluation for quality level in accordance with "MIL-STD-105D" and "IEC 60410":

<0.15% major defects


<0.65% minor defects.

Each capacitor is tested for minimum C_{max} and is also subjected to the full test voltage.

Film dielectric trimmers

2222 808

Ø10 mm




Dimensions in mm.
Hole pattern 5 mm x 10 mm; see Fig.4.

Fig.1 Trimmers 2222 808 series, vertical version.

Film dielectric trimmers

2222 808

Ø10 mm




Dimensions in mm.
Hole pattern 7.5 mm x 5 mm; see Fig.5.

Fig.2 Trimmers 2222 808 series, vertical version.

Film dielectric trimmers

2222 808

Ø10 mm






Dimensions in mm.
Hole pattern 5 mm x 10 mm; see Fig.6.

Fig.3 Trimmers 2222 808 series, horizontal version.

Film dielectric trimmers


2222 808

Ø10 mm



Adjustment

For top adjustment a screwdriver or trimming key can be used; for bottom adjustment a key is required as shown in Fig.7.



Film dielectric trimmers

2222 808

Ø10 mm

ORDERING INFORMATION

Table 1 Selection chart

C_{\min}/C_{\max} (pF)	CATALOGUE NUMBER 2222 808						
	HORIZONTAL VERSION		VERTICAL VERSION				
	HOLE PATTERN 5 mm × 10 mm		HOLE PATTERN 5 mm × 10 mm		HOLE PATTERN 7.5 mm × 5 mm		
	ROUND HEAD	HEX HEAD	ROUND HEAD	HEX. HEAD	ROUND HEAD	HEX. HEAD	ROUND HEAD
	TOP AND BOTTOM ADJUSTMENT		TOP AND BOTTOM ADJUSTMENT				TOP ADJUSTMENT
2.5/15	61159	–	31159	–	32159	–	–
3/22.5	61229	–	31229	–	32229	–	–
5.5/40	61409	–	31409	–	32409	–	–
5.5/50	–	–	01029	–	01006	–	–
5.5/65	61659	64659	31659	34659	32659	–	01001
6/80	61809	64809	31809	34809	32809	35809	–
7/105	61101	64101	31101	–	32101	–	–
6/120	–	–	31121	–	–	–	–

MOUNTING

The trimmer can be mounted on printed-circuit boards with a grid of 2.50 mm or 2.54 mm and a minimum hole diameter of 1.25 mm. For hole patterns see Figs 4, 5 and 6.

PACKAGING

Bulk packaged in cardboard boxes lined with expanded plastic. For smallest packaging quantities (SPQ) see Table 2.

Film dielectric trimmers

2222 808

Ø10 mm

ELECTRICAL DATA
Table 2 Electrical characteristics and catalogue numbers

GUARANTEED MAX. C_{min} / MIN. C_{max} at 200 kHz (pF)	SPINDLE	SHAPE OF HEAD	FIG.	ADJ. MODE	DIEL.	$\tan \delta$ at $C_{max} \times 10^{-4}$		TEMP. COEFF. ($10^{-6}/K$)	MIN. f_{res} at C_{max} (MHz)	COL. OF BASE	SPQ	CATALOGUE NUMBER		
						1 MHz	100 MHz							
2.5/15	vertical	round	1	top + bottom	PP	≤ 10	≤ 25	-200 ± 700	420	blue	800	2222 808 31159		
	horizontal		2										800	2222 808 32159
	3		700										2222 808 61159	
3/22.5	vertical	round	1	top + bottom	PP	≤ 10	≤ 25	-200 ± 700	200	green	800	2222 808 31229		
	horizontal		2										800	2222 808 32229
	3		700										2222 808 61229	
5.5/40	vertical	round	1	top + bottom	PP	≤ 10	≤ 25	-200 ± 400	200	grey	800	2222 808 31409		
	horizontal		2										800	2222 808 32409
	3		700										2222 808 61409	
5.5/50	vertical	round	1	top + bottom	PTFE	≤ 10	≤ 25	-200 ± 400	170	yellow	800	2222 808 01029		
	2		800										2222 808 01006	
5.5/65	vertical	round	2	top							800	2222 808 01001		
		hexag.	1										800	2222 808 31659
		3	800										2222 808 32659	
	horizontal	hexag.	1	top + bottom	PP	≤ 10	≤ 25	-200 ± 500	170	yellow	700	2222 808 34659		
	round	3	700										2222 808 61659	
	hexag.	3	600										2222 808 64659	
6/80	vertical	round	1	top + bottom	PC	≤ 70	-	-50 ± 400	170	red	800	2222 808 31809		
		hexag.	1										700	2222 808 34809
		3	800										2222 808 32809	
	horizontal	hexag.	1	top + bottom	PC	≤ 70	-	-50 ± 400	170	red	700	2222 808 35809		
	round	3	700										2222 808 61809	
	hexag.	3	600										2222 808 64809	
7/105	vertical	round	1	top + bottom	PC	≤ 70	-	-50 ± 400	170	violet	800	2222 808 31101		
		hexag.	2										800	2222 808 32101
	horizontal	3	700										2222 808 61101	
	hexag.	3	600										2222 808 64101	
6/120	vertical	round	2	top + bottom	PC	≤ 70	-	-50 ± 400	170	violet	800	2222 808 31121		

Film dielectric trimmers

2222 808

Ø10 mm

TESTS AND REQUIREMENTS

Table 3 Test procedures and requirements

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
4.2		method of mounting	method A	
14		capacitance drift	after TC measurement	$\Delta C/C: \leq 4.5\%$ for $C_{\max} < 40$ pF; $\Delta C/C: \leq 2.5\%$ for $C_{\max} \geq 40$ pF
19		thrust	axial thrust of 2 N	$\Delta C/C: \leq 0.3\%$
21		robustness of terminations:		
21.1	Ua	tensile	1 N	no damage
21.2	Ub	bending	1 cycle	no damage
22	Na	rapid change of temperature	1 cycle; 0.5 hours at lower and 0.5 hours at upper category temperature	$\Delta C/C: \leq 1.5\%$
23	T	soldering:		
	Ta	solderability	solder bath immersion 3 mm; 235 °C; 2 s	good wetting no mechanical damage
	Tb	resistance to heat	solder bath: 260 °C; 10 s	no mechanical damage
24	Eb	impact bump	4000 ±10 bumps; 40 g; 6 ms	$\Delta C/C: \leq 0.4\%$; no mechanical damage
25	Fc	vibration	frequency 10 to 55 Hz; amplitude 0.35 mm; 1.5 hours	$\Delta C/C: \leq 0.8\%$; no mechanical damage
26		climatic sequence:		$\Delta C/C: \leq 3\%$ for $C_{\max} < 80$ pF; $\Delta C/C: \leq 6\%$ for $C_{\max} \geq 80$ pF
26.1	B	dry heat	16 hours at upper category temperature	$\tan \delta: \leq 15 \times 10^{-4}$ for $C_{\max} < 80$ pF; $\tan \delta: \leq 80 \times 10^{-4}$ for $C_{\max} \geq 80$ pF $R_{\text{ins}}: \geq 10000$ M Ω ; rotor contact R: ≤ 10 m Ω
26.2	D	damp heat accelerated, first cycle	1 cycle; 24 hours; +40 °C; 95 to 100% RH	voltage proof: 300 V for 1 minute
26.3	Aa	cold	16 hours; -40 °C	visual examination: no mechanical damage
26.5		damp heat accelerated, remaining cycles	1 cycle; 24 hours; +40 °C; 95 to 100% RH	operating torque: 2 to 35 mNm

Film dielectric trimmers

2222 808

Ø10 mm

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
27	Ca	damp heat steady state	21 days; +40 °C; 90 to 95% RH	ΔC/C: ≤3% for $C_{max} < 100 \text{ pF}$; ≤3.5% for $C_{max} \geq 100 \text{ pF}$ tan δ : ≤ 20×10^{-4} for $C_{max} < 80 \text{ pF}$; tan δ : ≤ 80×10^{-4} for $C_{max} \geq 80 \text{ pF}$ R _{ins} : ≥10000 MΩ; rotor contact R: ≤10 mΩ voltage proof: 300 V for 1 minute visual examination: no mechanical damage operating torque: 2 to 35 mNm
29		mechanical endurance	10 cycles	ΔC/C: ≤1% ΔC/C after axial thrust: ≤0.4%; rotor contact R: ≤10 mΩ voltage proof: 300 V for 1 minute visual examination: no mechanical damage operating torque: 1.5 to 37 mNm

Film dielectric trimmers

2222 809 05...

FEATURES

- High temperature type
- Housing dimensions:
6 mm × 8 mm × 9 mm
- For a basic grid of 2.54 mm
- Top and bottom adjustment
- Round or hexagonal head
- Vertical version.

APPLICATIONS

- For fine adjustment in professional applications.

DESCRIPTION

The trimmers consist of a polysulphone housing, brass rotor and plated brass stator with PTFE film as the dielectric. The stator plate tags are heat sealed to the housing.

The rotor contact surfaces are plated to ensure a long life and a stable contact even under severe climatic conditions. A coloured dot indicates the maximum capacitance.

Cleaning with solvents is not advised.

Versions are available with either a round head or hexagonal head. Both versions have top adjustment by means of a screwdriver or trimming key and bottom adjustment by means of a key as shown in Fig.4.

For outline drawings and dimensions see Figs 1 and 2.

QUICK REFERENCE DATA

DESCRIPTION	VALUE
C_{\min}/C_{\max}	0.5/2 to 2/18 pF
Rated voltage (DC)	300 V
Test voltage (DC) for 1 minute	600 V
Maximum contact resistance	5 mΩ
Minimum insulation resistance between stator and rotor	10000 MΩ
Category temperature range	-40 to +125 °C
Climatic category (IEC 60068)	40/125/21
Related specification	IEC 60418-1 and 4
Minimum storage temperature	-55 °C

MECHANICAL DATA

DESCRIPTION	VALUE
Effective angle of rotation	180°
Operating torque:	
$C_{\max} \leq 3.5$ pF	1 to 15 mNm
$C_{\max} > 3.5$ pF	1 to 20 mNm
Maximum axial thrust	2 N

QUALITY LEVEL


Sampling and data evaluation for quality level in accordance with "MIL-STD-105D" and "IEC 60410":

- <0.15% major defects
- <0.65% minor defects.

Each capacitor is tested for minimum C_{\max} and is also subjected to the full test voltage.

Film dielectric trimmers

2222 809 05...



Dimensions in mm.

For hole pattern see Fig.3.


Version with flux guard available; see Table 1.

(1) For colour of dot see Table 2.

Fig.1 Trimmers 2222 809 05... series, with round heads.

Film dielectric trimmers

2222 809 05...




CCB148

Dimensions in mm.
For hole pattern see Fig.3.

Fig.2 Trimmers 2222 809 05... series, with hexagonal heads.


Film dielectric trimmers

2222 809 05...



Adjustment

For top adjustment a screwdriver or trimming key can be used; for bottom adjustment a key is required as shown in Fig.4.



MOUNTING

The trimmer can be mounted on printed-circuit boards with a minimum hole diameter of 2.54 mm. For hole pattern see Fig.3.

PACKAGING

Blister packs of 70 units each. For smallest packaging quantities (SPQ) see Table 2.

Film dielectric trimmers

2222 809 05...

ORDERING INFORMATION

Table 1 Selection chart

C_{\min}/C_{\max} (pF)	CATALOGUE NUMBER 2222 809 05...		
	TOP AND BOTTOM ADJUSTMENT		
	ROUND HEAD	ROUND HEAD AND FLUX GUARD	HEXAGONAL HEAD
0.5/2	011	–	021
1.2/3.5	215	001	225
1.8/10	216	–	226
2/18	217	–	227

ELECTRICAL DATA

Table 2 Electrical characteristics and catalogue numbers

GUARANTEED MAX. $C_{\min}/$ MIN. C_{\max} at 200 kHz (pF)	SHAPE OF HEAD	FIG.	$\tan \delta$ at $C_{\max} \times 10^{-4}$		TEMP. COEFF. ⁽¹⁾ ($10^{-6}/K$)	MIN. f_{res} at C_{\max} (MHz)	COL. OF DOT	SPQ	CATALOGUE NUMBER
			1 MHz	100 MHz					
0.5/2	round	1	≤ 10	≤ 20	-250 ± 350	1200	none	700	2222 809 05011
	hexag.	2						700	2222 809 05021
1.2/3.5	round	1	≤ 10	≤ 20	-250 ± 350	850	orange	700	2222 809 05001
	round	1						700	2222 809 05215
	hexag.	2						700	2222 809 05225
	hexag.	2						700	2222 809 05225
1.8/10	round	1	≤ 10	≤ 20	-250 ± 350	580	white	700	2222 809 05216
	hexag.	2						700	2222 809 05226
2/18	round	1	≤ 10	≤ 25	-250 ± 350	360	red	700	2222 809 05217
	hexag.	2						700	2222 808 05227

Note

1. C: 60% to 80% of C_{\max} ; T_{amb} : from +20 °C to +125 °C.

Film dielectric trimmers

2222 809 05...

TESTS AND REQUIREMENTS

Table 3 Test procedures and requirements

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
4.2		method of mounting	method A	
14		capacitance drift	after TC measurement	$\Delta C/C: \leq 2.5\%$; 4% for 2 pF
19		thrust	axial thrust of 2 N	$\Delta C/C: \leq 0.3\%$
21		robustness of terminations:		
21.1	Ua	tensile	1 N	no damage
21.2	Ub	bending	1 cycle	no damage
22	Na	rapid change of temperature	1 cycle; 0.5 hours at lower and 0.5 hours at upper category temperature	$\Delta C/C: \leq 2.5\%$
23	T	soldering:		
	Ta	solderability	solder bath immersion 3 mm; 235 °C; 2 s	good wetting no mechanical damage
	Tb	resistance to heat	solder bath: 260 °C; 10 s	no mechanical damage
24	Eb	impact bump	4000 \pm 10 bumps; 40 g; 6 ms	$\Delta C/C: \leq 0.6\%$; no mechanical damage
25	Fc	vibration	frequency 10 to 55 Hz; amplitude 0.35 mm; 1.5 hours	$\Delta C/C: \leq 0.2\%$; no mechanical damage
26		climatic sequence:		$\Delta C/C: \leq 2.5\%$
26.1	B	dry heat	16 hours at upper category temperature	$\tan \delta: \leq 10 \times 10^{-4}$ for $C_{\max} < 18$ pF; $\tan \delta: \leq 40 \times 10^{-4}$ for $C_{\max} \geq 18$ pF $R_{\text{ins}}: \geq 10000$ M Ω ; rotor contact R: ≤ 5 m Ω
26.2	D	damp heat accelerated, first cycle	1 cycle; 24 hours; +40 °C; 95 to 100% RH	voltage proof: 600 V for 1 minute
26.3	Aa	cold	16 hours; -40 °C	visual examination: no mechanical damage
26.5		damp heat accelerated, remaining cycles	1 cycle; 24 hours; +40 °C; 95 to 100% RH	operating torque: 1 to 20 mNm

Film dielectric trimmers

2222 809 05...

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
27	Ca	damp heat steady state	21 days; +40 °C; 90 to 95% RH	$\Delta C/C: \leq 2.5\%$ $\tan \delta: \leq 10 \times 10^{-4}$ for $C_{\max} < 18 \text{ pF}$; $\tan \delta: \leq 25 \times 10^{-4}$ for $C_{\max} \geq 18 \text{ pF}$ $R_{\text{ins}}: \geq 10000 \text{ M}\Omega$; rotor contact R: $\leq 5 \text{ m}\Omega$ voltage proof: 600 V for 1 minute visual examination: no mechanical damage operating torque: 1 to 20 mNm
29		mechanical endurance	25 cycles	$\Delta C/C: \leq 0.3\%; \leq 2.5\%$ for 2 pF $\Delta C/C$ after axial thrust: $\leq 0.3\%$; rotor contact R: $\leq 5 \text{ m}\Omega$ voltage proof: 600 V for 1 minute visual examination: no mechanical damage operating torque: 1 to 20 mNm

Film dielectric trimmers

2222 809 07...

FEATURES

- High temperature type
- Housing dimensions:
11 mm × 14 mm × 9 mm
- For a basic grid of 2.54 mm
- Top adjustment
- Vertical version.

APPLICATIONS

- For fine adjustment in professional applications.

DESCRIPTION

The trimmers consist of a glass reinforced polysulphone frame with a polysulphone dust cover, brass rotor and stator with PTFE or polycarbonate film as the dielectric. The stator plates are stacked on pins and separated by rings, so that it is possible to produce a single stator or a differential type.

The rotor contact surfaces are plated to ensure a long life and a stable contact even under severe climatic conditions.

For outline drawing and dimensions see Fig. 1a.

QUICK REFERENCE DATA

DESCRIPTION	VALUE
C_{\min}/C_{\max} :	
single stator type	2.5/20 to 7/100 pF
differential type	2/12 to 7/150 pF
Rated voltage (DC)	200 V
Test voltage (DC) for 1 minute	400 V
Maximum contact resistance	5 mΩ
Minimum insulation resistance between stator and rotor	10000 MΩ
Category temperature range	-40 to +125 °C
Climatic category (IEC 60068)	40/125/21
Related specification	IEC 60418-1 and 4
Minimum storage temperature	-55 °C

MECHANICAL DATA

DESCRIPTION	VALUE
Effective angle of rotation	180°
Operating torque	1.5 to 25 mNm
Maximum axial thrust	2 N

QUALITY LEVEL


Sampling and data evaluation for quality level in accordance with "MIL-STD-105D" and "IEC 60410":

- <0.15% major defects
- <0.65% minor defects.

Each capacitor is tested for minimum C_{\max} and is also subjected to the full test voltage.

Film dielectric trimmers

2222 809 07...



Adjustment

The trimmers can be adjusted with a screwdriver or trimming key. Capacitance increase is obtained with clockwise rotation.

MARKING

The trimmers are marked with the capacitance value in pF, followed by the letter 'E' (single-stator type) or the letter 'D' (differential type).

MOUNTING

The trimmer can be mounted on printed-circuit boards with a grid of 2.54 mm and a minimum hole diameter of 1.25 mm. For hole pattern see Fig.1b.

PACKAGING

Blister packs of 70 units each. For smallest packaging quantities (SPQ) see Table 2.

Film dielectric trimmers

2222 809 07...

ORDERING INFORMATION

Table 1 Selection chart

C_{\min}/C_{\max} (pF)	CATALOGUE NUMBER 2222 809 07...	
	TOP AND BOTTOM ADJUSTMENT	
	SINGLE STATOR TYPE	DIFFERENTIAL TYPE
2/12	–	018
2.5/20	004	006
4/40	008	009
5/60	011	012
6/80	013	014
7/100	015	016
7/150	–	107

ELECTRICAL DATA

Table 2 Electrical characteristics and catalogue numbers

GUARANTEED MAX. $C_{\min}/$ MIN. C_{\max} at 200 kHz (pF)	TYPE	DIEL.	$\tan \delta$ at $C_{\max} \times 10^{-4}$		TEMP. COEFF. ⁽³⁾ ($10^{-6}/K$)	SPQ	CATALOGUE NUMBER
			1 MHz	100 MHz			
2/12	differential	PTFE ⁽¹⁾	≤ 10	≤ 17	0 ± 200	350	2222 809 07018
2.5/20	single stator	PTFE	≤ 10	≤ 17	0 ± 200	350	2222 809 07004
	differential					350	2222 809 07006
4/40	single stator	PTFE	≤ 10	≤ 17	0 ± 200	350	2222 809 07008
	differential					350	2222 809 07009
5/60	single stator	PTFE	≤ 10	≤ 25	0 ± 200	350	2222 809 07011
	differential					350	2222 809 07012
6/80	single stator	PTFE	≤ 10	≤ 25	0 ± 200	350	2222 809 07013
	differential					350	2222 809 07014
7/100	single stator	PTFE	≤ 10	≤ 25	0 ± 200	350	2222 809 07015
	differential					350	2222 809 07016
7/150	differential	PC ⁽²⁾	≤ 50	–	0 ± 200	350	2222 809 07107

Notes

1. PTFE = polytetrafluorethylene.
2. PC = polycarbonate.
3. C: 60% to 80% of C_{\max} ; T_{amb} : from +20 °C to +125 °C.

Film dielectric trimmers

2222 809 07...

TESTS AND REQUIREMENTS

Table 3 Test procedures and requirements

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
4.2		method of mounting	method A	
14		capacitance drift	after TC measurement	$\Delta C/C: \leq 1\%$
19		thrust	axial thrust of 2 N	$\Delta C/C: \leq 0.3\%$
21		robustness of terminations:		
21.1	Ua	tensile	1 N	no damage
21.2	Ub	bending		bending not allowed
22	Na	rapid change of temperature	1 cycle; 0.5 hours at lower and 0.5 hours at upper category temperature	$\Delta C/C: \leq 1\%$
23	T	soldering:		
	Ta	solderability	solder bath immersion 3 mm; 235 °C; 2 s	good wetting no mechanical damage
	Tb	resistance to heat	solder bath: 260 °C; 10 s	no mechanical damage
24	Eb	impact bump	4000 ±10 bumps; 40 g; 6 ms	$\Delta C/C: \leq 0.2\%$; no mechanical damage
25	Fc	vibration	frequency 10 to 55 Hz; amplitude 0.35 mm; 1.5 hours	$\Delta C/C: \leq 0.25\%$; no mechanical damage
26		climatic sequence:		
26.1	B	dry heat	16 hours at upper category temperature	$\Delta C/C: \leq 3\%$ $\tan \delta: \leq 10 \times 10^{-4}$ $R_{ins}: \geq 10000 \text{ M}\Omega$; rotor contact R: $\leq 10 \text{ m}\Omega$
26.2	D	damp heat accelerated, first cycle	1 cycle; 24 hours; +40 °C; 95 to 100% RH	voltage proof: 400 V for 1 minute
26.3	Aa	cold	16 hours; -40 °C	visual examination: no mechanical damage
26.5		damp heat accelerated, remaining cycles	1 cycle; 24 hours; +40 °C; 95 to 100% RH	operating torque: 1.5 to 35 mNm

Film dielectric trimmers

2222 809 07...

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
27	Ca	damp heat steady state	21 days; +40 °C; 90 to 95% RH	$\Delta C/C: \leq 3\%$ $\tan \delta: \leq 10 \times 10^{-4}$ $R_{ins}: \geq 10000 \text{ M}\Omega$; rotor contact R: $\leq 10 \text{ m}\Omega$ voltage proof: 400 V for 1 minute visual examination: no mechanical damage operating torque: 1.5 to 35 mNm
29		mechanical endurance	25 cycles	$\Delta C/C: \leq 0.3\%$ $\Delta C/C$ after axial thrust: $\leq 0.3\%$; rotor contact R: $\leq 10 \text{ m}\Omega$ voltage proof: 400 V for 1 minute visual examination: no mechanical damage operating torque: 1 to 50 mNm

Film dielectric trimmers

2222 809 080..

FEATURES

- High temperature type
- Housing dimensions:
10 mm × 11 mm × 11 mm
- For a basic grid of 2.54 mm
- Vertical version with a round head
- Top and bottom adjustment.

APPLICATIONS

- For fine adjustment in professional applications.

DESCRIPTION

The trimmers consist of a polysulphone housing, brass rotor and plated brass stator with PTFE film as the dielectric. The stator plate tags are heat sealed to the housing.

The rotor contact surfaces are plated to ensure a long life and a stable contact even under severe climatic conditions. A coloured dot indicates the maximum capacitance.

Flux absorption between the vanes is prevented.

Cleaning with solvents is not advised.

For outline drawing and dimensions see Fig.1.

QUICK REFERENCE DATA

DESCRIPTION	VALUE
C_{\min}/C_{\max}	4/38 to 5/57 pF
Rated voltage (DC)	250 V
Test voltage (DC) for 1 minute	500 V
Maximum contact resistance	5 mΩ
Minimum insulation resistance	10000 MΩ
Category temperature range	-40 to +125 °C
Climatic category (IEC 60068)	40/125/21
Related specification	IEC 60418-1 and 4
Minimum storage temperature	-55 °C

MECHANICAL DATA

DESCRIPTION	VALUE
Effective angle of rotation	180°
Operating torque	2 to 25 mNm
Maximum axial thrust	2 N

QUALITY LEVEL

Sampling and data evaluation for quality level in accordance with "MIL-STD-105D" and "IEC 60410":


<0.15% major defects

<0.65% minor defects.

Each capacitor is tested for minimum C_{\max} and is also subjected to the full test voltage.

Film dielectric trimmers

2222 809 080..




CCB154

Dimensions in mm.
 For hole pattern see Fig.2.
 (1) For colour of dot see Table 2.


Fig.1 Trimmers 2222 809 080.. series, with round heads.

Film dielectric trimmers

2222 809 080..

**Adjustment**

For top adjustment a screwdriver or trimming key can be used; for bottom adjustment a key is required as shown in Fig.3.

**MOUNTING**

The trimmer can be mounted on printed-circuit boards with a grid of 2.54 mm and a minimum hole diameter of 1.25 mm. For hole pattern see Fig.2.

PACKAGING

Blister packs of 70 units each. For smallest packaging quantities (SPQ) see Table 2.

Film dielectric trimmers

2222 809 080..

ORDERING INFORMATION

Table 1 Selection chart

C _{min} /C _{max} (pF)	CATALOGUE NUMBER 2222 809 080..	
	TOP AND BOTTOM ADJUSTMENT	
4/38	02	
5/57	03	

ELECTRICAL DATA

Table 2 Electrical characteristics and catalogue numbers

GUARANTEED MAX. C _{min} / MIN. C _{max} at 200 kHz (pF)	SHAPE OF HEAD	DIEL.	tan δ at C _{max} × 10 ⁻⁴		TEMP. COEFF. ⁽²⁾ (10 ⁻⁶ /K)	MIN. f _{res} at C _{max} (MHz)	COL. OF DOT	SPQ	CATALOGUE NUMBER
			1 MHz	100 MHz					
4/38	round	PTFE ⁽¹⁾	≤10	≤25	-200 ±250	170	yellow	350	2222 809 08002
5/57	round		≤10	≤25		150	blue	350	2222 809 08003

Notes

1. PTFE = polytetrafluorethylene.
2. C: 60% to 80% of C_{max}; T_{amb}: from +20 °C to +125 °C.

Film dielectric trimmers

2222 809 080..

TESTS AND REQUIREMENTS

Table 3 Test procedures and requirements

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
4.2		method of mounting	method A	
14		capacitance drift	after TC measurement	$\Delta C/C: \leq 2.0\%$
19		thrust	axial thrust of 2 N	$\Delta C/C: \leq 0.2\%$
21		robustness of terminations:		
21.1	Ua	tensile	1 N	no damage
21.2	Ub	bending	1 cycle	no damage
22	Na	rapid change of temperature	1 cycle; 0.5 hours at lower and 0.5 hours at upper category temperature	$\Delta C/C: \leq 2.5\%$
23	T	soldering:		
	Ta	solderability	solder bath immersion 3 mm; 235 °C; 2 s	good wetting no mechanical damage
	Tb	resistance to heat	solder bath: 260 °C; 10 s	no mechanical damage
24	Eb	impact bump	4000 \pm 10 bumps; 40 g; 6 ms	$\Delta C/C: \leq 0.5\%$; no mechanical damage
25	Fc	vibration	frequency 10 to 55 Hz; amplitude 0.35 mm; 1.5 hours	$\Delta C/C: \leq 0.2\%$; no mechanical damage
26		climatic sequence:		
26.1	B	dry heat	16 hours at upper category temperature	$\Delta C/C: \leq 2.5\%$ $\tan \delta: \leq 10 \times 10^{-4}$ $R_{ins}: \geq 10000 \text{ M}\Omega$; rotor contact R: $\leq 5 \text{ m}\Omega$
26.2	D	damp heat accelerated, first cycle	1 cycle; 24 hours; +40 °C; 95 to 100% RH	voltage proof: 500 V for 1 minute
26.3	Aa	cold	16 hours; -40 °C	visual examination: no mechanical damage
26.5		damp heat accelerated, remaining cycles	1 cycle; 24 hours; +40 °C; 95 to 100% RH	operating torque: 1 to 25 mNm

Film dielectric trimmers

2222 809 080..

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
27	Ca	damp heat steady state	21 days; +40 °C; 90 to 95% RH	$\Delta C/C: \leq 2.5\%$ $\tan \delta: \leq 10 \times 10^{-4}$ $R_{ins}: \geq 10000 \text{ M}\Omega$; rotor contact R: $\leq 5 \text{ m}\Omega$ voltage proof: 500 V for 1 minute visual examination: no mechanical damage operating torque: 1 to 25 mNm
29		mechanical endurance	25 cycles	$\Delta C/C: \leq 0.3\%$ $\Delta C/C$ after axial thrust: $\leq 0.3\%$; rotor contact R: $\leq 5 \text{ m}\Omega$ voltage proof: 500 V for 1 minute visual examination: no mechanical damage operating torque: 1 to 25 mNm

Film dielectric trimmers

2222 809 090..

FEATURES

- High temperature type
- Housing dimensions:
8 mm × 9 mm × 10 mm
- For a basic grid of 2.54 mm
- Versions available
with 1 or 2 rotor contacts
- Top and bottom adjustment
- Vertical version.

APPLICATIONS

- For fine adjustment professional applications.

DESCRIPTION

The trimmers consist of a polysulphone housing, brass rotor and plated brass stator with PTFE film as the dielectric. The stator plate tags are heat sealed to the housing.

The rotor contact surfaces are plated to ensure a long life and a stable contact even under severe climatic conditions. A coloured dot indicates the maximum capacitance.

Flux absorption between the vanes is prevented.

Cleaning with solvents is not advised.

For outline drawings and dimensions see Figs 1 and 2.

QUICK REFERENCE DATA

DESCRIPTION	VALUE
C_{min}/C_{max}	1.4/5.5 to 3/18 pF
Rated voltage (DC)	250 V
Test voltage (DC) for 1 minute	500 V
Maximum contact resistance	5 mΩ
Minimum insulation resistance	10000 MΩ
Category temperature range	-40 to +125 °C
Climatic category (IEC 60068)	40/125/21
Related specification	IEC 60418-1 and 4
Minimum storage temperature	-55 °C

MECHANICAL DATA

DESCRIPTION	VALUE
Effective angle of rotation	180°
Operating torque:	
$C_{max} = 5.5$ pF	1 to 15 mNm
$C_{max} = 9$ and 18 pF	1 to 20 mNm
Maximum axial thrust	2 N

QUALITY LEVEL

Sampling and data evaluation for quality level in accordance with "MIL-STD-105D" and "IEC 60410".


<0.15% major defects

<0.65% minor defects.

Each capacitor is tested for minimum C_{max} and is also subjected to the full test voltage.

Film dielectric trimmers

2222 809 090..




Dimensions in mm.
 For hole pattern see Fig.3.
 (1) For colour of dot see Table 2.

Fig.1 Trimmers 2222 809 090.. series, with one rotor contact.

Film dielectric trimmers

2222 809 090..



Dimensions in mm.



For hole pattern see Fig.4.

(1) For colour of dot see Table 2.

Fig.2 Trimmers 2222 809 090.. series, with two rotor contacts.

Film dielectric trimmers

2222 809 090..




Adjustment

For top adjustment a screwdriver or trimming key can be used; for bottom adjustment a key is required as shown in Fig.5.

MOUNTING

The trimmer can be mounted on printed-circuit boards with a basic grid of 2.54 mm and a minimum hole diameter of 1.25 mm. For hole patterns see Figs 3 and 4.



PACKAGING

Blister packs of 105 units each. For smallest packaging quantities (SPQ) see Table 2.

Film dielectric trimmers

2222 809 090..

ORDERING INFORMATION

Table 1 Selection chart

C_{\min}/C_{\max} (pF)	CATALOGUE NUMBER 2222 809 090..	
	ROUND HEAD TOP AND BOTTOM ADJUSTMENT	
	VERSION WITH 1 ROTOR CONTACT	VERSION WITH 2 ROTOR CONTACTS
1.4/5.5	04	01
2/9	05	02
3/18	06	03

ELECTRICAL DATA

Table 2 Electrical characteristics and catalogue numbers

GUARANTEED MAX. $C_{\min}/$ MIN. C_{\max} at 200 kHz (pF)	SHAPE OF HEAD	DIEL.	$\tan \delta$ at $C_{\max} \times 10^{-4}$		TEMP. COEFF. ⁽²⁾ ($10^{-6}/K$)	MIN. f_{res} at C_{\max} (MHz)	COL. OF DOT	SPQ	CATALOGUE NUMBER
			1 MHz	100 MHz					
1.4/5.5	round	PTFE ⁽¹⁾	≤ 10	≤ 15	-250 ± 350	850	green	525	2222 809 09004 ⁽³⁾
	round							525	2222 809 09001 ⁽⁴⁾
2/9	round					580	white	525	2222 809 09005 ⁽³⁾
	round							525	2222 809 09002 ⁽⁴⁾
3/18	round					360	red	525	2222 809 09006 ⁽³⁾
	round							525	2222 809 09003 ⁽⁴⁾

Notes

1. PTFE = polytetrafluorethylene.
2. C: 60% to 80% of C_{\max} ; T_{amb} : from +20 °C to +125 °C.
3. Version with one rotor contact.
4. Version with two rotor contacts.

Film dielectric trimmers

2222 809 090..

TESTS AND REQUIREMENTS

Table 3 Test procedures and requirements

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
4.2		method of mounting	method A	
14		capacitance drift	after TC measurement	$\Delta C/C: \leq 2.0\%; \leq 3.0\%$ for 9 pF
19		thrust	axial thrust of 2 N	$\Delta C/C: \leq 0.3\%$
21		robustness of terminations:		
21.1	Ua	tensile	1 N	no damage
21.2	Ub	bending	1 cycle	no damage
22	Na	rapid change of temperature	1 cycle; 0.5 hours at lower and 0.5 hours at upper category temperature	$\Delta C/C: \leq 3\%$
23	T	soldering:		
	Ta	solderability	solder bath immersion 3 mm; 235 °C; 2 s	good wetting no mechanical damage
	Tb	resistance to heat	solder bath: 260 °C; 10 s	no mechanical damage
24	Eb	impact bump	4000 \pm 10 bumps; 40 g; 6 ms	$\Delta C/C: \leq 0.5\%$; no mechanical damage
25	Fc	vibration	frequency 10 to 55 Hz; amplitude 0.35 mm; 1.5 hours	$\Delta C/C: \leq 0.3\%$; no mechanical damage
26		climatic sequence:		$\Delta C/C: \leq 2.5\%$
26.1	B	dry heat	16 hours at upper category temperature	$\tan \delta: \leq 10 \times 10^{-4}$ $R_{ins}: \geq 10000 \text{ M}\Omega$; rotor contact R: $\leq 5 \text{ m}\Omega$
26.2	D	damp heat accelerated, first cycle	1 cycle; 24 hours; +40 °C; 95 to 100% RH	voltage proof: 500 V for 1 minute
26.3	Aa	cold	16 hours; -40 °C	visual examination: no mechanical damage
26.5		damp heat accelerated, remaining cycles	1 cycle; 24 hours; +40 °C; 95 to 100% RH	operating torque: 1 to 20 mNm

Film dielectric trimmers

2222 809 090..

IEC 60418-1 CLAUSE	IEC 60068 TEST METHOD	TEST	PROCEDURE	REQUIREMENTS
27	Ca	damp heat steady state	21 days; +40 °C; 90 to 95% RH	$\Delta C/C: \leq 3\%$ $\tan \delta: \leq 10 \times 10^{-4}$ $R_{ins}: \geq 10000 \text{ M}\Omega$; rotor contact R: $\leq 5 \text{ m}\Omega$ voltage proof: 500 V for 1 minute visual examination: no mechanical damage operating torque: 1 to 20 mNm
29		mechanical endurance	25 cycles	$\Delta C/C: \leq 3\%$ $\Delta C/C$ after axial thrust: $\leq 0.3\%$; rotor contact R: $\leq 5 \text{ m}\Omega$ voltage proof: 500 V for 1 minute visual examination: no mechanical damage operating torque: 1 to 20 mNm

DATA HANDBOOK SYSTEM

DATA HANDBOOK SYSTEM

Philips Components data handbooks are available for selected product ranges and contain all relevant data available at the time of publication and each is revised and updated regularly.

Loose data sheets are sent to subscribers to keep them up-to-date on additions or alterations made during the lifetime of each edition.

Our data handbook titles are listed here.

Display components

Book Title

DC01	Colour Television Tubes
DC02	Monochrome Monitor Tubes and Deflection Units
DC03	Television Tuners, Coaxial Aerial Input Assemblies
DC04	Colour Monitor and Multimedia Tubes
DC05	Wire Wound Components

Magnetic products

MA01	Soft Ferrites
MA03	Piezoelectric Ceramics and Specialty Ferrites
MA04	Dry-reed Switches

Passive components

PA01	Electrolytic Capacitors
PA02	Varistors, Thermistors and Sensors
PA03	Potentiometers
PA04	Variable Capacitors
PA05	Film Capacitors
PA06	Ceramic Capacitors
PA06a	Surface Mounted Ceramic Multilayer Capacitors
PA06b	Leaded Ceramic Capacitors
PA08	Fixed Resistors
PA10	Quartz Crystals
PA11	Quartz Oscillators

MORE INFORMATION FROM PHILIPS COMPONENTS?

For more information about Philips Components data handbooks, catalogues and subscriptions, please contact your nearest Philips Components sales organization **(see address list on the back cover of this handbook).**

OVERVIEW OF PHILIPS SEMICONDUCTORS DATA HANDBOOKS

Our sister product division, Philips Semiconductors, also has a comprehensive data handbook system to support their products. Their data handbook titles are listed here.

Integrated circuits

Book	Title
IC01	Semiconductors for Radio, Audio and CD/DVD Systems
IC02	Semiconductors for Television and Video Systems
IC03	Semiconductors for Wired Telecom Systems
IC04	HE4000B Logic Family CMOS
IC05	Advanced Low-power Schottky (ALS) Logic
IC06	High-speed CMOS Logic Family
IC11	General-purpose/Linear ICs
IC12	I ² C Peripherals
IC13	Programmable Logic Devices (PLD)
IC14	8048-based 8-bit Microcontrollers
IC15	FAST TTL Logic Series
IC16	CMOS ICs for Clocks, Watches and Real Time Clocks
IC17	Semiconductors for Wireless Communications
IC18	Semiconductors for In-Car Electronics
IC19	ICs for Data Communications
IC20	80C51-based 8-bit Microcontrollers
IC22	Multimedia ICs
IC23	BiCMOS Bus Interface Logic
IC24	Low Voltage CMOS & BiCMOS Logic
IC25	16-bit 80C51XA Microcontrollers (eXtended Architecture)
IC26	IC Circuit Packages
IC27	Complex Programmable Logic Devices

Discrete semiconductors

SC01	Small-signal and Medium-power Diodes
SC02	Power Diodes
SC03	Power Thyristors and Triacs
SC04	Small-signal Transistors
SC05	Video Transistors and Modules for Monitors
SC06	High-voltage and Switching NPN Power Transistors
SC07	Small-signal Field-effect Transistors
SC13a	PowerMOS Transistors including TOPFETs and IGBTs
SC13b	Small-signal and Medium-power MOS Transistors
SC14	RF Wideband Transistors
SC16	Wideband Hybrid Amplifier Modules for CATV
SC17	Semiconductor Sensors
SC18	Discrete Semiconductor Packages
SC19	RF & Microwave Power Transistors, RF Power Modules and Circulators/Isolators

MORE INFORMATION FROM PHILIPS SEMICONDUCTORS?

For more information contact your nearest Philips Semiconductors national organization shown in the following list.

Argentina: see South America
Australia: NORTH RYDE, Tel. +61 2 9805 4455 Fax. +61 2 9805 4466
Austria: WIEN, Tel. +43 1 60 101, Fax. +43 1 60 101 1210
Belarus: MINSK, Tel. +375 172 200 733, Fax. +375 172 200 773
Belgium: see The Netherlands
Brazil: see South America
Bulgaria: SOFIA, Tel. +359 2 689 211, Fax. +359 2 689 102
Canada: SCARBOROUGH, Tel. +1 800 234 7381
Chile: see South America
China/Hong Kong: HONG KONG, Tel. +852 2319 7888, Fax. +852 2319 7700
Colombia: see South America
Czech Republic: see Austria
Denmark: COPENHAGEN, Tel. +45 32 88 2636, Fax. +45 31 57 0044
Finland: ESPOO, Tel. +358 9 615800, Fax. +358 9 61580920
France: SURESNES, Tel. +33 1 40 99 6161, Fax. +33 1 40 99 6427
Germany: HAMBURG, Tel. +49 40 23 53 60, Fax. +49 40 23 536 300
Greece: TAVROS/ATHENS, Tel. +30 1 4894 339/239, Fax. +30 1 4814 240
Hungary: see Austria
India: BOMBAY, Tel. +91 22 4938 541, Fax. +91 22 4938 722
Indonesia: JAKARTA, Tel. +62 21 794 0040 ext. 2501, Fax. +62 21 794 0080
Ireland: DUBLIN, Tel. +353 1 7640 000, Fax. +353 1 7640 200
Israel: TEL AVIV, Tel. +972 3 645 0444, Fax. +972 3 649 1007
Italy: MILANO, Tel. +39 2 6752 2531, Fax. +39 2 6752 2557
Japan: TOKIO, Tel. +81 3 3740 5130, Fax. +81 3 3740 5077
Korea: SEOUL, Tel. +82 2 709 1412, Fax. +82 2 709 1415
Malaysia: SELANGOR, Tel. +60 3 750 5214, Fax. +60 3 757 4880
Mexico: EL PASO, TEXAS, Tel. +9-5 800 234 7381
Middle East: see Italy
Netherlands: EINDHOVEN, Tel. +31 40 27 82785, Fax. +31 40 27 88399
New Zealand: AUCKLAND, Tel. +64 9 849 4160, Fax. +64 9 849 7811
Norway: OSLO, Tel. +47 22 74 8000, Fax. +47 22 74 8341
Pakistan: see Singapore
Philippines: MANILA, Tel. +63 2 816 6380, Fax. +63 2 817 3474
Poland: WARSZAWA, Tel. +48 22 612 2831, Fax. +48 22 612 2327
Portugal: see Spain
Romania: see Italy
Russia: MOSCOW, Tel. +7 095 755 6918, Fax. +7 095 755 6919
Singapore: SINGAPORE, Tel. +65 350 2538, Fax. +65 251 6500
Slovakia: see Austria
Slovenia: see Italy
South Africa: JOHANNESBURG, Tel. +27 11 470 5911, Fax. +27 11 470 5494
South America: SÃO PAULO, Tel. +55 11 821 2333, Fax. +55 11 821 2382
Spain: BARCELONA, Tel. +34 3 301 6312, Fax. +34 3 301 4107
Sweden: STOCKHOLM, Tel. +46 8 5985 2000, Fax. +46 8 5985 2745
Switzerland: ZÜRICH, Tel. +41 1 488 2741, Fax. +41 1 488 3263
Taiwan: TAIPEI, Tel. +886 2 2134 2865, Fax. +886 2 2134 2874
Thailand: BANGKOK, Tel. +66 2 745 4090, Fax. +66 2 398 0793
Turkey: ISTANBUL, Tel. +90 212 279 2770, Fax. +90 212 282 6707
Ukraine: KIEV, Tel. +380 44 264 2776, Fax. +380 44 268 0461
United Kingdom: HAYES, Tel. +44 181 730 5000, Fax. +44 181 754 8421
United States: SUNNYVALE, Tel. +1 800 234 7381
Uruguay: see South America
Vietnam: see Singapore
Yugoslavia: BEOGRAD, Tel. +381 11 625 344, Fax. +381 11 635 777

Internet: <http://www.semiconductors.philips.com>

For all other countries apply to:

Philips Semiconductors,
International Marketing & Sales Communications, Building BE-p,
P.O. Box 218, 5600 MD EINDHOVEN, The Netherlands,
Fax. +31-40-2724825

NOTES

Philips Components – a worldwide company

Australia: Philips Components Pty Ltd., NORTH RYDE,
Tel. (02) 9805 4455, Fax. (02) 9805 4466.

Austria: Österreichische Philips Industrie GmbH, WIEN,
Tel. (01) 601 01 12 41, Fax. (01) 60 101 12 11.

Belarus: Philips Office Belarus, MINSK,
Tel. (5172) 200 924/733, Fax. (5172) 200 773.

Benelux: Philips Nederland B.V., EINDHOVEN, NL,
Tel. (+31 40) 2783 749, Fax. (+31 40) 2788 399.

Brazil: Philips Components, SÃO PAULO,
Tel. (011) 821 2333, Fax. (011) 829 1849.

Canada: Philips Electronics Ltd., SCARBOROUGH,
Tel. (0416) 292 5161, Fax. (0416) 754 6248.

China: Philips Company, SHANGHAI,
Tel. (021) 6354 1088, Fax. (021) 6354 1060.

Denmark: Philips Components A/S, COPENHAGEN S,
Tel. (32) 883 333, Fax. (31) 571 949.

Finland: Philips Components, ESPOO,
Tel. (0) 9 615 800, Fax. (0) 9 615 80510.

France: Philips Composants, SURESNES,
Tel. (01) 4099 6161, Fax. (01) 4099 6493.

Germany: Philips Components GmbH, HAMBURG,
Tel. (040) 2489-0, Fax. (040) 2489 1400.

Greece: Philips Hellas S.A., TAVROS,
Tel. (01) 4894 339/(01) 4894 239, Fax. (01) 4814 240.

Hong Kong: Philips Hong Kong, KOWLOON,
Tel. 2784 3000, Fax. 2784 3003.

India: Philips India Ltd., MUMBAI,
Tel. (022) 4930 311, Fax. (022) 4930 966/4950 304.

Indonesia: P.T. Philips Development Corp., JAKARTA,
Tel. (021) 794 0040, Fax. (021) 794 0080.

Ireland: Philips Electronics (Ireland) Ltd., DUBLIN,
Tel. (01) 76 40 203, Fax. (01) 76 40 210.

Israel: Rapac Electronics Ltd., TEL AVIV,
Tel. (03) 6450 444, Fax. (03) 6491 007.

Italy: Philips Components S.r.l., MILANO,
Tel. (02) 6752 2531, Fax. (02) 6752 2557.

Japan: Philips Japan Ltd., TOKYO,
Tel. (0) 3 3740 5135, Fax. (0) 3 3740 5035.

Korea (Republic of): Philips Electronics (Korea) Ltd., SEOUL,
Tel. (02) 709 -1472, Fax. (02) 709 1480.

Malaysia: Philips Malaysia SDN Berhad
Components Division, PULAU PINANG,
Tel. (03) 750 5213, Fax. (03) 757 4880.

Mexico: Philips Components, EL PASO, U.S.A.,
Tel. (915) 772 4020, Fax. (915) 772 4332.

New Zealand: Philips New Zealand Ltd., AUCKLAND,
Tel. (09) 815 4000, Fax. (09) 849 7811.

Norway: Norsk A/S Philips, OSLO,
Tel. (22) 74 8000, Fax. (22) 74 8341.

Pakistan: Philips Electrical Industries of Pakistan Ltd., KARACHI,
Tel. (021) 587 4641-49, Fax. (021) 577 035/587 4546.

Philippines: Philips Semiconductors Philippines Inc.,
METRO MANILA, Tel. (02) 816 6345, Fax. (02) 817 3474.

Poland: Philips Poland Sp. z o.o., WARSZAWA,
Tel. (022) 612 2594, Fax. (022) 612 2327.

Portugal: Philips Portuguesa S.A.,
Philips Components: LINDA-A-VELHA,
Tel. (01) 416 3160/416 3333, Fax. (01) 416 3174/416 3366.

Russia: Philips Russia, MOSCOW,
Tel. (095) 755 6918, Fax. (095) 755 6919.

Singapore: Philips Singapore Pte Ltd., SINGAPORE,
Tel. 350 2000, Fax. 355 1758.

South Africa: S.A. Philips Pty Ltd., JOHANNESBURG,
Tel. (011) 470 5911, Fax. (011) 470 5494.

Spain: Philips Components, BARCELONA,
Tel. (93) 301 63 12, Fax. (93) 301 42 43.

Sweden: Philips Components AB, STOCKHOLM,
Tel. (+46) 8 5985 2000, Fax. (+46) 8 5985 2745.

Switzerland: Philips Components AG, ZÜRICH,
Tel. (01) 488 22 11, Fax. (01) 481 77 30.

Taiwan: Philips Taiwan Ltd., TAIPEI,
Tel. (02) 2134 2900, Fax. (02) 2134 2929.

Thailand: Philips Electronics (Thailand) Ltd., BANGKOK,
Tel. (02) 745 4090, Fax. (02) 398 0793.

Turkey: Türk Philips Ticaret A.S., GÜLTEPE/ISTANBUL,
Tel. (0212) 279 2770, Fax. (0212) 282 6707.

United Kingdom: Philips Components Ltd., DORKING,
Tel. (01306) 512 000, Fax. (01306) 512 345.

United States:

- Display Components, ANN ARBOR, MI,
Tel. (734) 996 9400, Fax. (734) 761 2776.
- Magnetic Products, SAUGERTIES, NY,
Tel. (914) 246 2811, Fax. (914) 246 0487.
- Passive Components, SAN JOSE, CA,
Tel. (408) 570 5600, Fax. (408) 570 5700.

Yugoslavia (Federal Republic of): Philips Components, BELGRADE,
Tel. (0) 11 625 344/373, Fax. (0) 11 635 777.

Internet:

- Passive Components: www.passives.comp.philips.com

For all other countries apply to:

Philips Components, Building BF-1, P.O. Box 218, 5600 MD
EINDHOVEN,
The Netherlands, Fax. +31-40-27 23 903.

COD17

© Philips Electronics N.V. 1998

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or

Printed in The Netherlands

532310/7000/02/pp64
Document order number:

Date of release: May 1998
9398 184 19011



PHILIPS

Let's make things better.