

PHN103T

N-channel enhancement mode field-effect transistor

Rev. 02 — 28 April 2004

Product data

1. Product profile

1.1 Description

N-channel enhancement mode field-effect transistor in a plastic package using TrenchMOS™ technology.

1.2 Features

- TrenchMOS™ technology
- Low on-state resistance
- Fast switching
- Logic level compatible.

1.3 Applications

- Motor driver
- Battery management
- Actuator driver
- High speed, low resistance switch.



1.4 Quick reference data

Table 1: Quick reference data

Symbol	Parameter	Conditions	Typ	Max	Unit
V_{DS}	drain-source voltage (DC)	$25^{\circ}\text{C} \leq T_j \leq 150^{\circ}\text{C}$	-	30	V
I_D	drain current (DC)	$T_{sp} = 25^{\circ}\text{C}; V_{GS} = 4.5\text{ V}$	-	8.6	A
P_{tot}	total power dissipation	$T_{sp} = 25^{\circ}\text{C}$	-	6.25	W
T_j	junction temperature		-	150	$^{\circ}\text{C}$
R_{DSon}	drain-source on-state resistance	$V_{GS} = 10\text{ V}; I_D = 5\text{ A}$	20	30	$\text{m}\Omega$
		$V_{GS} = 4.5\text{ V}; I_D = 2.5\text{ A}$	30	50	$\text{m}\Omega$

2. Pinning information

Table 2: Pinning - SOT96-1 (SO8), simplified outline and symbol

Pin	Description	Simplified outline	Symbol
1,2,3	source (s)		
4	gate (g)		
5,6,7,8	drain (d)	 Top view MBK187	 MBB076



PHILIPS

3. Ordering information

Table 3: Ordering information


Type number	Package		Version
	Name	Description	
PHN103T	SO8	Plastic small outline package; 8 leads	SOT96-1

4. Limiting values

Table 4: Limiting values


In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	drain-source voltage (DC)	$25^{\circ}\text{C} \leq T_j \leq 150^{\circ}\text{C}$	-	30	V
V_{DGR}	drain-gate voltage (DC)	$25^{\circ}\text{C} \leq T_j \leq 150^{\circ}\text{C}; R_{GS} = 20\text{ k}\Omega$	-	30	V
V_{GS}	gate-source voltage (DC)		-	± 20	V
I_D	drain current (DC)	$T_{sp} = 25^{\circ}\text{C}; V_{GS} = 4.5\text{ V}$; Figure 2 and 3	-	8.6	A
		$T_{sp} = 100^{\circ}\text{C}; V_{GS} = 4.5\text{ V}$; Figure 2	-	5.4	A
I_{DM}	peak drain current	$T_{sp} = 25^{\circ}\text{C}$; pulsed; $t_p \leq 10\text{ }\mu\text{s}$; Figure 3	-	34	A
P_{tot}	total power dissipation	$T_{sp} = 25^{\circ}\text{C}$; Figure 1	-	6.25	W
T_{stg}	storage temperature		-65	+150	$^{\circ}\text{C}$
T_j	junction temperature		-65	+150	$^{\circ}\text{C}$
Source-drain diode					
I_S	source (diode forward) current (DC)	$T_{sp} = 25^{\circ}\text{C}$	-	7	A
I_{SM}	peak source (diode forward) current	$T_{sp} = 25^{\circ}\text{C}$; pulsed; $t_p \leq 10\text{ }\mu\text{s}$	-	34	A




$$P_{der} = \frac{P_{tot}}{P_{tot}(25^{\circ}C)} \times 100\%$$

Fig 1. Normalized total power dissipation as a function of solder point temperature.



$$I_{der} = \frac{I_D}{I_{D(25^{\circ}C)}} \times 100\%$$

Fig 2. Normalized continuous drain current as a function of solder point temperature.



$T_{sp} = 25^{\circ}C$; I_{DM} is single pulse.

Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage.

5. Thermal characteristics

Table 5: Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j-sp)}$	thermal resistance from junction to solder point	Figure 4	-	-	20	K/W
$R_{th(j-a)}$	thermal resistance from junction to ambient	mounted on a printed-circuit board; minimum footprint	-	150	-	K/W

5.1 Transient thermal impedance




Fig 4. Transient thermal impedance from junction to solder point as a function of pulse duration.

6. Characteristics

Table 6: Characteristics $T_j = 25^\circ\text{C}$ unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static characteristics						
$V_{(\text{BR})\text{DSS}}$	drain-source breakdown voltage	$I_D = 10 \mu\text{A}; V_{GS} = 0 \text{ V}$				
		$T_j = 25^\circ\text{C}$	30	43	-	V
		$T_j = -55^\circ\text{C}$	27	-	-	V
$V_{GS(\text{th})}$	gate-source threshold voltage	$I_D = 1 \text{ mA}; V_{DS} = V_{GS}$; Figure 9				
		$T_j = 25^\circ\text{C}$	1	2	2.8	V
		$T_j = 150^\circ\text{C}$	0.6	-	-	V
		$T_j = -55^\circ\text{C}$	-	-	3.5	V
I_{DSS}	drain-source leakage current	$V_{DS} = 24 \text{ V}; V_{GS} = 0 \text{ V}$				
		$T_j = 25^\circ\text{C}$	-	10	100	nA
		$T_j = 150^\circ\text{C}$	-	-	10	μA
I_{GSS}	gate-source leakage current	$V_{GS} = \pm 20 \text{ V}; V_{DS} = 0 \text{ V}$	-	10	100	nA
$R_{DS\text{on}}$	drain-source on-state resistance	$V_{GS} = 10 \text{ V}; I_D = 5 \text{ A}$; Figure 7 and 8				
		$T_j = 25^\circ\text{C}$	-	20	30	$\text{m}\Omega$
		$V_{GS} = 4.5 \text{ V}; I_D = 2.5 \text{ A}$; Figure 8				
		$T_j = 25^\circ\text{C}$	-	30	50	$\text{m}\Omega$
		$T_j = 150^\circ\text{C}$	-	-	85	$\text{m}\Omega$
Dynamic characteristics						
g_{fs}	forward transconductance	$V_{DS} = 5 \text{ V}; I_D = 5.5 \text{ A}$; Figure 11	-	12	-	S
$Q_{g(\text{tot})}$	total gate charge	$I_D = 5 \text{ A}; V_{DS} = 15 \text{ V}; V_{GS} = 10 \text{ V}$; Figure 14	-	24	40	nC
Q_{gs}	gate-source charge		-	3.3	-	nC
Q_{gd}	gate-drain (Miller) charge		-	7.4	-	nC
C_{iss}	input capacitance	$V_{GS} = 0 \text{ V}; V_{DS} = 24 \text{ V}; f = 1 \text{ MHz}$; Figure 12	-	770	-	pF
C_{oss}	output capacitance		-	265	-	pF
C_{rss}	reverse transfer capacitance		-	180	-	pF
$t_{d(\text{on})}$	turn-on delay time	$V_{DD} = 15 \text{ V}; R_D = 15 \Omega$	-	8	-	ns
t_r	rise time	$V_{GS} = 10 \text{ V}; R_G = 6 \Omega$	-	10	-	ns
t_{on}	turn-on time		-	18	35	ns
$t_{d(\text{off})}$	turn-off delay time		-	24	-	ns
t_f	fall time		-	20	-	ns
t_{off}	turn-off time		-	44	150	ns
Source-drain diode						
V_{SD}	source-drain (diode forward) voltage	$I_S = 1.25 \text{ A}; V_{GS} = 0 \text{ V}$; Figure 13	-	0.73	1.0	V
t_{rr}	reverse recovery time	$I_S = 1.25 \text{ A}; dI_S/dt = -100 \text{ A}/\mu\text{s}$	-	120	-	ns
Q_r	recovered charge	$V_{GS} = 0 \text{ V}; V_{DS} = 25 \text{ V}$	-	150	-	nC




Fig 5. Output characteristics: drain current as a function of drain-source voltage; typical values.




Fig 6. Transfer characteristics: drain current as a function of gate-source voltage; typical values.






Fig 7. Drain-source on-state resistance as a function of drain current; typical values.




$$a = \frac{R_{DSon}}{R_{DSon}(25^\circ\text{C})}$$

Fig 8. Normalized drain-source on-state resistance factor as a function of junction temperature.




$I_D = 1 \text{ mA}$; $V_{DS} = V_{GS}$

Fig 9. Gate-source threshold voltage as a function of junction temperature.




$T_j = 25^\circ\text{C}$; $V_{DS} = 5 \text{ V}$

Fig 10. Sub-threshold drain current as a function of gate-source voltage.




$T_j = 25^\circ\text{C}$ and 150°C ; $V_{DS} > I_D \times R_{DSon}$

Fig 11. Forward transconductance as a function of drain current; typical values.




$V_{GS} = 0 \text{ V}$; $f = 1 \text{ MHz}$

Fig 12. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values.



$T_j = 25^\circ\text{C}$ and 150°C ; $V_{GS} = 0 \text{ V}$

Fig 13. Source (diode forward) current as a function of source-drain (diode forward) voltage; typical values.




$I_D = 5 \text{ A}; V_{DS} = 15 \text{ V}$

Fig 14. Gate-source voltage as a function of gate charge; typical values.

7. Package outline

SO8: plastic small outline package; 8 leads; body width 3.9 mm

SOT96-1



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

UNIT	A max.	A ₁	A ₂	A ₃	b _p	c	D ⁽¹⁾	E ⁽²⁾	e	H _E	L	L _p	Q	v	w	y	z ⁽¹⁾	θ
mm	1.75 0.10	0.25 1.25	1.45	0.25	0.49 0.36	0.25 0.19	5.0 4.8	4.0 3.8	1.27	6.2 5.8	1.05	1.0 0.4	0.7 0.6	0.25	0.25	0.1	0.7 0.3	8° 0°
inches	0.069 0.004	0.010 0.049	0.057	0.01	0.019 0.014	0.0100 0.0075	0.20 0.19	0.16 0.15	0.05	0.244 0.228	0.041	0.039 0.016	0.028 0.024	0.01	0.01	0.004	0.028 0.012	

Notes

- Plastic or metal protrusions of 0.15 mm (0.006 inch) maximum per side are not included.
- Plastic or metal protrusions of 0.25 mm (0.01 inch) maximum per side are not included.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT96-1	076E03	MS-012				99-12-27 03-02-18

Fig 15. SOT96-1 (SO8).

8. Revision history

Table 7: Revision history

Rev	Date	CPCN	Description
02	20040428	-	Product data (9397 750 13185) Modifications <ul style="list-style-type: none">• Updated to latest standard.• Section 3 "Ordering information" added.• Section 6 "Characteristics" R_{DSon} conditions corrected.
01	20000828	HZG336	Product specification (9397 750 07304) Converted from VDMOS (Nijmegen) to TrenchMOS™ technology (Hazel Grove).

9. Data sheet status

Level	Data sheet status ^[1]	Product status ^{[2][3]}	Definition
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

10. Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

12. Trademarks

TrenchMOS — is a trademark of Koninklijke Philips Electronics N.V.

11. Disclaimers

Life support — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors

Contact information

For additional information, please visit <http://www.semiconductors.philips.com>.

For sales office addresses, send e-mail to: sales.addresses@www.semiconductors.philips.com.

Fax: +31 40 27 24825

9397 750 13185

© Koninklijke Philips Electronics N.V. 2004. All rights reserved.

Contents

1	Product profile	1
1.1	Description	1
1.2	Features	1
1.3	Applications	1
1.4	Quick reference data	1
2	Pinning information	1
3	Ordering information	2
4	Limiting values	2
5	Thermal characteristics	4
5.1	Transient thermal impedance	4
6	Characteristics	5
7	Package outline	9
8	Revision history	10
9	Data sheet status	11
10	Definitions	11
11	Disclaimers	11
12	Trademarks	11

© Koninklijke Philips Electronics N.V. 2004.

Printed in The Netherlands

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: 28 April 2004

Document order number: 9397 750 13185



PHILIPS

Let's make things better.