

1. Design





You are in: Design | Embedded Systems

SIGN UP TO

- [Email Newsletters](#)
- [RSS Feeds](#)
- [Digital Magazine](#)
- [Print Magazine](#)
- [Technical Papers](#)
- [Events](#)
- [Media Centre](#)

WORK BREAK

- [Photo Stories](#)
- [Blogs](#)
- [Video](#)
- [Sudoku](#)
- [Dilbert](#)
- [Gadget Master](#)
- [Made By Monkeys](#)

DATA MODUL

Embedded Solutions



DATA MODUL

data-modul.com

Chip firms target consumer priced ECG body monitors

Richard Wilson
Thursday 13 October 2011 00:01

Within a few years we could all be wearing wireless heart-rate monitors that transfer data to be stored on our mobile phones.



Analog Devices and Texas Instruments can offer the low power electrocardiogram (ECG) front-end devices which would make consumer-priced, battery-powered heart-rate and blood pressure monitors possible. They have now been joined by Plessey Semiconductor with its first 'electric potential' ECG sensor IC.

Imec and Holst Centre have gone one step further and integrated its low power ECG chip with a Bluetooth Low Energy radio.

The aim of all these suppliers is to tap into the potential market for personal body health monitors, and for that a low-power radio link seems necessary.

Imec said the low-power design means that when transmitting heart rate data, for example, the system will consume 280µA at 2.1V, running continuously for one month on a 200mAh Li-Po battery.

When transmitting accelerometer data (at 32Hz) on top of the heart rate, the power consumption remains below 1mA in continuous operation, giving about a week of autonomy.

The big prize for wireless monitors is the mobile phone market. It is expected that Bluetooth Low Energy (Bluetooth 4.0) will be integrated as standard in smartphones from next year, which could open the way for new healthcare monitoring applications.

At the heart of the Imec patch is an ECG system-on-chip (SoC), a mixed signal Asic.

Next to monitoring 1- to 3-lead ECG, the ECG SoC also monitors the contact impedance, providing real-time information on the electrode contact quality. This can be used to evaluate the quality of the ECG measurement and to filter motion artifacts. The ECG SoC has been designed to run algorithms for motion artifact reduction (based on adaptive filtering or principal component analysis) and beat-to-beat heart rate computation (based on discrete or continuous wavelet transforms).

It has additional computation power to run application-specific algorithms such as epileptic seizure detection, energy expenditure estimation or arrhythmia monitoring. The built-in 12-bit ADC is capable of adaptive sampling – sampling QRS waves at high frequency, and the other waves at a lower frequency – achieving a compression ratio of up to five.

The monitor is part of the Human++ program being carried out at Imec and Holst Centre addressing healthcare technology.

Plessey Semiconductors is sampling its Electric Potential Integrated Circuit (EPIC) sensors targeting ECG applications.

"The first EPIC products are designed for ECG applications for health and patient monitoring as well as fitness and wellness applications," said Derek Rye, Plessey's marketing manager.

The EPIC sensor measures changes in an electric field in a similar way to a magnetometer detecting changes in a magnetic field. The technology works at normal room temperatures and functions as an ultra-high, input impedance sensor that acts as a highly stable, extremely sensitive, contactless digital voltmeter to measure tiny changes in the electric field, down to millivolts.

"The next release products available later in this quarter will be optimised for movement sensing where applications range from security, to automotive, to safety through to gesture recognition applications," said Rye.

"We are working on end applications where the potential volumes are in millions per month. This is all very exciting for the company," said Rye.

A feature of the EPIC sensors are that they are dry contact so that no gels or similar fluids are required to make contact. The sensors can be cleaned between uses – unlike conventional ECG sensors that have to be disposed of after every use at a cost of \$2 a set. The supplier also claims that fewer sensors are required to monitor the body while the patient lies down.



Making a Green Society in Full Bloom

RENESAS Renesas Electronics

Share the content

[ShareThis](#)

Related Jobs

Most Viewed

- SEMICON Europa: Discrepancies in 450mm timing**
Posted: 16:58 11 Oct 2011
- IEF2011: HP to replace flash and SSD in 2013**
Posted: 12:17 06 Oct 2011
- Honeywell gets ovation from FAA, major movie studios - NBAA**
Posted: 09:50 10 Oct 2011
- Altera goes system-on-chip with dual-core Cortex**
Posted: 13:13 11 Oct 2011
- Freescale unveils 'most powerful' automotive MCU**
Posted: 16:38 12 Oct 2011

Resources

Stay a step ahead with **Electronics Weekly.com** Industry Resources

[Learn More](#)

Products

SUPPLIER ECOSYSTEM

- » [MAIN INDEX](#)
- » [Acal](#)
- » [Anglia](#)
- » [Arrow Electronics](#)
- » [Avnet Memec](#)
- » [Avnet Silica](#)
- » [Digi Key](#)
- » [EBV Elektronik](#)
- » [Farnell](#)
- » [Future](#)
- » [Mouser](#)
- » [MSC Gleichmann UK](#)
- » [RS](#)

Read The Magazine

Latest Issue: 12 - 18 Oct, 2011



LED Lighting Guides

Electronics Weekly's key LED technology articles covering white LEDs, colour LEDs, OLEDs and interior lighting...



"Most places on Earth have a vertical electric field of about 100 Volts per metre. The human body is mostly water and this interacts with the electric field. EPIC technology is so sensitive that it can detect these changes at a distance and even through a solid wall," said the supplier.

The EPIC sensor is being offered in two package formats. The PS25101 is supplied in the same custom engineered, metal or plastic disc style, probe assembly that was used for the first prototype sensors and demonstration systems. This comes complete with a connecting lead and DIN plug termination.


Analog Devices has ECG front-end chips, which incorporate pacemaker pulse detection and respiration measurement. The ADAS1000 is intended for the design of a five-electrode ECG system.


It uses a DC-coupled channel implementation that offers simplified input switching and reduced power. It will operate five ECG electrode measurements from as low as 19mW.

Texas Instruments also has ECG front ends, designed to be sufficiently low power for portable patient monitoring and consumer medical applications. The eight-channel, 24-bit ADS1298 has a specified power efficiency of 1 mW/channel.

- www.analog.com
- www.imec.be
- www.plesseysemi.com
- www.ti.com

The True Low Power MCU Platform




Renesas Electronics

Like

Add New Comment

[Login](#)



Type your comment here.

Showing 0 comments

Sort by popular now

[Subscribe by email](#) [RSS](#)

Reactions



Comments powered by DISQUS

Related Articles

Latest Blog posts

Interview: Touch technology brings industrial benefits - Zytronic
12 Oct 2011

Plessey samples ECG medical sensors
10 Oct 2011

ST and MIT claim ultra low power microcontroller breakthrough
06 Oct 2011

ARM Cortex-M4 MCU from ST gets IAR tool support
28 Sep 2011

[View all news](#)

Unconnected Among The Connected
13 Oct 2011

Arrow works with Freescale and Altera for Ethernet Powerlink
12 Oct 2011

Artificial Blood Vessels Made By Printer
12 Oct 2011

RoHS Recast CE - important to note
12 Oct 2011

[View all blogs](#)

Sign-up for the ElectronicsWeekly.com newsletters:



1. Design





Products & Services

- [Email Newsletters](#)
- [RSS](#)
- [Blogs](#)
- [Photo Stories](#)
- [Company Directory](#)
- [Digital Magazine](#)
- [Videos](#)

The Latest Electronics News

Design

Communications, EDA and IP, Embedded Systems, Legislation, Power

Components

Analogue & Discretes, Displays and Opto, Memory, Micros & DSP, Passives, FPGAs & Asics

Research

Materials R & D, Process R & D, Device R & D

Business

Distribution, Viewpoints, IT, Market Research

Production

Manufacturing, Test & Measurement

Products

Analogue ICs, Bus Systems & SBCs, Emecch & Enclosures, Memory, Passives, Connectors, Digital ICs, Discretes, Displays, DSPs, FPGA/PLD, Asics, Micros, Power Supplies, RF & Opto, Sensors, Software, Test & Measurement

Events

Diary Dates, Electronica, Elekras