


BUS-CONTROLLED AUDIO MATRIX

- 6 STEREO INPUTS
- 3 STEREO OUTPUTS
- GAIN CONTROL 0dB/MUTE FOR EACH OUTPUT
- CASCADABLE (2 DIFFERENT ADDRESSES)
- SERIAL BUS CONTROLLED
- VERY LOW NOISE
- VERY LOW DISTORSION
- FULLY ESD PROTECTED


DESCRIPTION

The TEA6422 switches 6 stereo audio inputs on 3 stereo outputs.
All the switching possibilities are changed through the I²C BUS.



SHRINK 24
(Plastic Package)


ORDER CODE : TEA6422



SO28
(Plastic Micropackage)


ORDER CODE : TEA6422D

PIN CONNECTIONS



6422-01.EPS / 6422-02.EPS

BLOCK DIAGRAM



ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V _{CC}	Supply Voltage	12	V
T _{oper}	Operating Temperature	0, + 70	°C
T _{stg}	Storage Temperature	- 20, + 150	°C

THERMAL DATA

Symbol	Parameter	Value	Unit
R _{th(j-a)}	Junction - ambient Thermal Resistance	SDIP24	75
		SO28	75

ELECTRICAL CHARACTERISTICS

$T_A = 25^{\circ}\text{C}$, $V_S = 9\text{V}$, $R_L = 10\text{k}\Omega$, $R_G = 600\Omega$, $f = 1\text{kHz}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
--------	-----------	-----------------	------	------	------	------

SUPPLY

V_S	Supply Voltage		8	9	10.2	V
I_S	Supply Current			3	8	mA
SVR	Ripple Rejection	$V_{IN} = 500\text{mV}_{\text{RMS}}$, $f = 1\text{kHz}$	70	80		dB

MATRIX

V_{IN}	Input DC Level			4.5		V
R_I	Input Resistance		30	50	100	$\text{k}\Omega$
C_S	Channel Separation	$V_{IN} = 2V_{\text{RMS}}$, $f = 1\text{kHz}$	80	90		dB

OUTPUT BUFFER

V_{OUT}	Output DC Level		4.2	4.5	4.8	V
R_{OUT}	Output Resistance			50	100	Ω
e_{NI}	Input Noise	$\text{BW} = 20 - 20\text{kHz}$, flat		3		μV
S/N	Signal to Noise Ratio	$V_{IN} = V_{OUT} = 1V_{\text{RMS}}$		110		dB
G	Gain		-1	0	+ 1	dB
d	Distortion	$V_{IN} = V_{OUT} = 1V_{\text{RMS}}$		0.01	0.05	%
V_{CL}	Clipping Level	$d = 0.3\%$	2	2.5		V_{RMS}
R_L	Output Load Resistance		2			$\text{k}\Omega$

6422-03.TBL

I²C BUS CHARACTERISTICS

Symbol	Parameter	Test Conditions	Min.	Max.	Unit
SCL					
V _{IL}	Low Level Input Voltage		- 0.3	+ 1.5	V
V _{IH}	High Level Input Voltage		3.0	V _{CC} + 0.5	V
I _{LI}	Input Leakage Current	V _I = 0 to V _{CC}	- 10	+ 10	μA
f _{SCL}	Clock Frequency		0	100	kHz
t _R	Input Rise Time	1.5V to 3V		1000	ns
t _F	Input Fall Time	1.5V to 3V		300	ns
C _I	Input Capacitance			10	pF

SDA


V _{IL}	Low Level Input Voltage		- 0.3	+ 1.5	V
V _{IH}	High Level Input Voltage		3.0	V _{CC} + 0.5	V
I _{LI}	Input Leakage Current	V _I = 0 to V _{CC}	- 10	+ 10	μA
C _I	Input Capacitance			10	pF
t _R	Input Rise Time	1.5V to 3V		1000	ns
t _F	Input Fall Time	1.5V to 3V		300	ns
V _{OL}	Low Level Output Voltage	I _{OL} = 3mA		0.4	V
t _F	Output Fall Time	3V to 1.5V		250	ns
C _L	Load Capacitance			400	pF

TIMING

t _{LOW}	Clock Low Period		4.7		μs
t _{HIGH}	Clock High Period		4.0		μs
t _{SU, DAT}	Data Set-up Time		250		ns
t _{HD, DAT}	Data Hold Time		0	340	ns
t _{SU, STO}	Set-up Time from Clock High to Stop		4.0		μs
t _{BUF}	Start Set-up Time following a Stop		4.7		μs
t _{HD, STA}	Start Hold Time		4.0		μs
t _{SU, STA}	Start Set-up Time following Clock Low-to High Transition		4.7		μs

6422-04.TBL

Figure 1 : I²C Bus Timing



6422-04.LFS

POWER ON RESET

After power-on reset all outputs are in mute mode

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
Reset	Start of Reset	Incr. V_{CC}	4.5		2.5	V
	End of Reset	Decr. V_{CC}			4.2	V
		Incr. V_{CC}				V

6422-05.TBL

SOFTWARE SPECIFICATION**1. Chip address**

Address	HEX	ADDR
1001 1000	98	0
1001 1010	9A	1

2. Data bytes

Output select

X	0 0 1	0 1 0	X	X	l_2	l_1	l_0	Output 1 Output 2 Output 3

Input select

X	Q_1	Q_0	X	X	0 0 0 0 1 1 1	0 0 1 1 0 0 1	0 1 0 1 0 1 0	Input 1 Input 2 Input 3 Input 4 Input 5 Input 6 Mute

6422-06.TBL

X = don't care - MSB is transmitted first

Example : 0 10 XX 10Q connects outputs 3 with input 5.

Figure 2 : Distorsion Level versus Input Voltage




Figure 3 : Clipping Level versus Supply Voltage





Figure 4 : Supply Voltage Rejection versus frequency ($V_{IN} = 500mV_{RMS}$)



PIN CONFIGURATIONS (SDIP24 Package)

Figure 5 : Audio IN




Figure 6 : Audio OUT




Figure 7 : ADDR







Figure 8 : Bus Inputs (SDA, SCL)



TYPICAL APPLICATION (SDIP24 Package)



PACKAGE MECHANICAL DATA
24 PINS - PLASTIC SHRINK




PMSDIP24.EPS

Dimensions	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			5.08			0.20
A1	0.51			0.020		
A2	3.05	3.30	4.57	0.120	0.130	0.180
B	0.36	0.46	0.56	0.0142	0.0181	0.0220
B1	0.76	1.02	1.14	0.030	0.040	0.045
C	0.23	0.25	0.38	0.0090	0.0098	0.0150
D	22.61	22.86	23.11	0.890	0.90	0.910
E	7.62		8.64	0.30		0.340
E1	6.10	6.40	6.86	0.240	0.252	0.270
e		1.778			0.070	
e1		7.62			0.30	
e2			10.92			0.430
e3			1.52			0.060
L	2.54	3.30	3.81	0.10	0.130	0.150

SDIP24.TBL

PACKAGE MECHANICAL DATA

28 PINS - PLASTIC MICROPACKAGE (SO)



PM-SO28-EPS

Dimensions	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			2.65			0.104
a1	0.1		0.3	0.004		0.012
b	0.35		0.49	0.014		0.019
b1	0.23		0.32	0.009		0.013
C		0.5			0.020	
c1	45° (Typ.)					
D	17.7		18.1	0.697		0.713
E	10		10.65	0.394		0.419
e		1.27			0.050	
e3		16.51			0.65	
F	7.4		7.6	0.291		0.299
L	0.4		1.27	0.016		0.050
S	8° (Max.)					

SO28-TBL

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No licence is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1996 SGS-THOMSON Microelectronics - All Rights Reserved

Purchase of μ C Components of SGS-THOMSON Microelectronics, conveys a license under the Philips μ C Patent. Rights to use these components in a μ C system, is granted provided that the system conforms to the μ C Standard Specifications as defined by Philips.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco
The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.