

**PACKET SWITCHING/CCS#7**

Type	Description	Package
MK5025	X 25 LAPB/ISDN LAPD/HDLC CMOS Hi-Speed Link Level Controller with DMA	DIP48, PLCC52
MK50H25Q	X 25 Link Level Controller	PLCC52
MK50H25N	X 25 Link Level Controller	DIP48
MK5027Q	CCS#7 Controller	PLCC52
MK5027N	CCS#7 Controller	DIP48
MK50H28Q	Multi Logical Link Frame Relay Controller	PLCC52
MK50H28N	Multi Logical Link Frame Relay Controller	DIP48
MK5029	CCITT, Bellcore CCS#7	PLCC52

**SERIAL COMMUNICATIONS CONTROL**

Type	Description	Package
MK5021	7MB/Sec. Full Duplex With Memory Management	PLCC52

**DC/DC CONVERTER MODULES**

ECL APPLICATIONS (-5.2 V <sub>DC</sub> output)					
Single Output Type	Output Power (W)	Input Voltage Range (V <sub>DC</sub> )	Output Volt/mA	Dimensions L . W . H (mm)	Package
GS3T5-5.2	3	4.75 ÷ 5.25	- 5.2 / 600	33 . 33 . 16.5	C
GS15T5-5.2	15	4.65 ÷ 5.35	- 5.2 / 3000	50.8 . 50.8 . 14.7	G
LAN APPLICATIONS (-9 V <sub>DC</sub> output)					
Single Output Type	Output Power (W)	Input Voltage Range (V <sub>DC</sub> )	Output Volt/mA	Dimensions L . W . H (mm)	Package
GS2T5-9	2	4.50 ÷ 5.50	- 9 / 250	35.6 . 21.6 . 14	B
GS2T12-9A	2	9.50 ÷ 15.75	- 9 / 250	35.6 . 21.6 . 14	B
GS2T12-9	2	11.28 ÷ 15.75	- 9 / 250	33 . 33 . 12.7	A
GS2T12-9S	2	9.50 ÷ 15.75	- 9 / 250	35.6 . 21.6 . 14	B
GS2TX-9	2	4.50 ÷ 15.75	- 9 / 250	35.6 . 21.6 . 14	B

\* Common features: 2500V Isolation Voltage