


## SMALL SIGNAL SCHOTTKY DIODES

### DESCRIPTION

General purpose, metal to silicon diodes featuring very low turn-on voltage and fast switching.

These devices have integrated protection against excessive voltage such as electrostatic discharges.



### ABSOLUTE RATINGS (limiting values)

Symbol	Parameter	BAT47	BAT48	Unit
$V_{RRM}$	Repetitive Peak Reverse Voltage	20	40	V
$I_F$	Forward Continuous Current*	$T_a = 25^\circ\text{C}$	350	mA
$I_{FRM}$	Repetitive Peak Forward Current*	$t_p \leq 1\text{s}$ $\delta \leq 0.5$	1	A
$I_{FSM}$	Surge non Repetitive Forward Current*	$t_p = 10\text{ms}$	7.5	A
		$t_p = 1\text{s}$	1.5	
$P_{tot}$	Power Dissipation*	$T_a = 25^\circ\text{C}$	330	mW
$T_{stg}$ $T_j$	Storage and Junction Temperature Range	- 65 to + 150 - 65 to + 125		$^\circ\text{C}$ $^\circ\text{C}$
$T_L$	Maximum Temperature for Soldering during 10s at 4mm from Case	230		$^\circ\text{C}$

### THERMAL RESISTANCE

Symbol	Test Conditions	Value	Unit
$R_{th(j-l)}$	Junction-ambient*	300	$^\circ\text{C/W}$

\* On infinite heatsink with 4mm lead length

## BAT 47/BAT 48

---

### ELECTRICAL CHARACTERISTICS

#### STATIC CHARACTERISTICS


Symbol	Test Conditions		Min.	Typ.	Max.	Unit	
$V_{BR}$	$I_R = 10\mu A$	BAT47	20			V	
	$I_R = 25\mu A$	BAT48	40				
$V_F^*$	$T_j = 25^\circ C \quad I_F = 0.1mA$	All Types		0.25		V	
	$T_j = 25^\circ C \quad I_F = 1mA$			0.3			
	$T_j = 25^\circ C \quad I_F = 10mA$			0.4			
	$T_j = 25^\circ C \quad I_F = 30mA$	BAT47		0.5			
	$T_j = 25^\circ C \quad I_F = 150mA$			0.8			
	$T_j = 25^\circ C \quad I_F = 300mA$			1			
	$T_j = 25^\circ C \quad I_F = 50mA$	BAT48		0.5			
	$T_j = 25^\circ C \quad I_F = 200mA$			0.75			
	$T_j = 25^\circ C \quad I_F = 500mA$			0.9			
$I_R^*$	$T_j = 25^\circ C$	$V_R = 1.5V$	All Types		1	$\mu A$	
	$T_j = 60^\circ C$				10		
	$T_j = 25^\circ C$	$V_R = 10V$	BAT47		4		
	$T_j = 60^\circ C$				20		
	$T_j = 25^\circ C$	$V_R = 20V$			10		
	$T_j = 60^\circ C$				30		
	$T_j = 25^\circ C$	$V_R = 10V$	BAT48		2		
	$T_j = 60^\circ C$				15		
	$T_j = 25^\circ C$	$V_R = 20V$			5		
	$T_j = 60^\circ C$				25		
	$T_j = 25^\circ C$	$V_R = 40V$			25		
	$T_j = 60^\circ C$				50		

#### DYNAMIC CHARACTERISTICS


Symbol	Test Conditions		Min.	Typ.	Max.	Unit
C	$T_j = 25^\circ C \quad V_R = 0V$	$f = 1MHz$		20		pF
	$T_j = 25^\circ C \quad V_R = 1V$			12		
$t_{rr}$	$T_j = 25^\circ C \quad I_F = 10mA$	$V_R = 1V$	$i_{rr} = 1mA$	$R_L = 100\Omega$	10	ns

\* Pulse test:  $t_p \leq 300\mu s \quad \delta < 2\%$ .


**Figure 1. Forward current versus forward voltage at different temperatures (typical values).**



**Figure 2. Forward current versus forward voltage (typical values).**



**Figure 3. Reverse current versus junction temperature.**



**Figure 4. Reverse current versus continuous reverse voltage (typical values).**






Figure 5. Capacitance C versus reverse applied voltage  $V_R$  (typical values).



## PACKAGE MECHANICAL DATA

DO 35 Glass



REF.	DIMENSIONS				NOTES	
	Millimeters		Inches			
	Min.	Max.	Min.	Max.		
A	3.050	4.500	0.120	0.117	1 - The lead diameter $\varnothing$ D is not controlled over zone E	
B	12.7		0.500		2 - The minimum axial length within which the device may be placed with its leads bent at right angles is 0.59"(15 mm)	
$\varnothing$ C	1.530	2.000	0.060	0.079		
$\varnothing$ D	0.458	0.558	0.018	0.022		
E		1.27		0.050		

Cooling method: by convection and conduction.

Marking: clear, ring at cathode end.

Weight: 0.015g

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - Printed in Italy - All rights reserved.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands  
Singapore - Spain - Sweden - Switzerland - Taiwan - United Kingdom - U.S.A.