


HIGH EFFICIENCY FAST RECOVERY RECTIFIER DIODES

FEATURES

- SUITED FOR SMPS
- VERY LOW FORWARD LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- HIGH SURGE CURRENT CAPABILITY
- HIGH AVALANCHE ENERGY CAPABILITY
- SURFACE MOUNT DEVICE

DESCRIPTION

Single chip rectifier suited for Switch Mode Power Supply and high frequency DC to DC converters. Packaged in SOD6, this surface mount device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications.



SOD6
(Plastic)

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
I _{F(RMS)}	RMS forward current	10	A
I _{F(AV)}	Average forward current	2	A
I _{FSM}	Non repetitive surge peak forward current	50	A
T _{stg} T _j	Storage and junction temperature range	- 40 to + 150 - 40 to + 150	°C °C

Symbol	Parameter	SMBYW02-				Unit
		50	100	150	200	
V _{RRM}	Repetitive peak reverse voltage	50	100	150	200	V

THERMAL RESISTANCE

Symbol	Parameter	Value	Unit
R _{th} (j-l)	Junction-leads	25	°C/W

SMBYW02

ELECTRICAL CHARACTERISTICS STATIC CHARACTERISTICS

Symbol	Test Conditions		Min.	Typ.	Max.	Unit
V_F *	$T_j = 25^\circ C$	$I_F = 6 A$			1.25	V
	$T_j = 100^\circ C$	$I_F = 2 A$			0.85	
I_R **	$T_j = 25^\circ C$	$V_R = V_{RRM}$			20	μA
	$T_j = 100^\circ C$				0.5	mA

Pulse test : * $t_p = 380 \mu s$, duty cycle < 2 %

** $t_p = 5 ms$, duty cycle < 2 %

RECOVERY CHARACTERISTICS

Symbol	Test Conditions		Min.	Typ.	Max.	Unit
trr	$T_j = 25^\circ C$	$I_F = 1A$ $V_R = 30V$			35	ns
tfr	$T_j = 25^\circ C$	$I_F = 1A$ $V_{FR} = 1.1 \times V_F$		30		ns
V_{FP}	$T_j = 25^\circ C$	$I_F = 1A$	$tr = 10 ns$		5	V

To evaluate the conduction losses use the following equation :

$$P = 0.7 \times I_{F(AV)} + 0.075 \times I_F^2(RMS)$$

Voltage (V)	50	100	150	200
Marking	A05	A10	A15	A20

Laser marking
Logo indicates cathode

Fig.1 : Low frequency power losses versus average current.




Fig.3 : Non repetitive surge peak forward current versus overload duration.




Fig.5 : Voltage drop versus forward current.
(Maximum values)




Fig.2 : Peak current versus form factor.




Fig.4 : Relative variation of thermal impedance junction to lead versus pulse duration.





Fig.6 : Average current versus ambient temperature. (duty cycle : 0.5)



SMBYW02

Fig.7 : Capacitance versus reverse voltage applied.




Fig.9 : Peak reverse current versus dI_F/dt.




Fig.11 : Thermal resistance junction to ambient versus copper surface under each lead.




Fig.8 : Recovery time versus dI_F/dt.








Fig.10 : Dynamic parameters versus junction temperature.



PACKAGE MECHANICAL DATA
SOD6

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.44	2.62	0.096	0.103
a1	0.10	0.20	0.004	0.008
B	1.96	2.11	0.077	0.083
b1	0.25	0.35	0.010	0.014
C	3.65	3.93	0.143	0.155
D	5.39	5.59	0.212	0.220
E	4.15	4.30	0.163	0.170
F	1.00	1.27	0.039	0.050
H	2.33	2.41	0.092	0.095
J	2.05	2.13	0.080	0.084

Laser Marking
Logo indicated cathode

SMBYW02

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

TURBOSWITCH, TRANSIL, TRISIL, SNUBBERLESS are Trademarks of SGS-THOMSON Microelectronics.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A