

## POWER SCHOTTKY RECTIFIER


### FEATURES

- VERY SMALL CONDUCTION LOSSES
- NEGLIGIBLE SWITCHING LOSSES
- LOW FORWARD VOLTAGE DROP
- LOW THERMAL RESISTANCE
- EXTREMELY FAST SWITCHING
- INSULATED PACKAGE :  
Insulating voltage = 2500 V(RMS)

### DESCRIPTION

Dual power schottky rectifier suited for switchmode power supply and high frequency DC to DC converters.

Packaged in ISOTOP™, this device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications.



### ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
I <sub>F(RMS)</sub>	RMS forward current		Per diode 125	A
I <sub>F(AV)</sub>	Average forward current	T <sub>C</sub> =85°C δ = 0.5	Per diode 80 Per device 160	A A
I <sub>FSM</sub>	Surge non repetitive forward current	tp=10ms sinusoidal	Per diode 900	A
I <sub>RRM</sub>	Peak repetitive reverse current	tp=2μs F=1KHz	Per diode 2	A
T <sub>stg</sub> T <sub>j</sub>	Storage and junction temperature range		- 65 to + 150 - 65 to + 150	°C °C
dV/dt	Critical rate of rise of reverse voltage		1000	V/μs

Symbol	Parameter	STPS		Unit
		16035TV	16045TV	
V <sub>RRM</sub>	Repetitive peak reverse voltage	35	45	V

\* : Tin plated Fast-on version is also available (without V suffix).

™: ISOTOP is a trademark of SGS-THOMSON Microelectronics.

# STPS16035T(V) / STPS16045T(V)

## THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
Rth (j-c)	Junction to case	Per diode	0.9	°C/W
		Total	0.5	
Rth (c)	Coupling		0.1	°C/W

When the diodes 1 and 2 are used simultaneously :

$$\Delta T_j(\text{diode } 1) = P(\text{diode}) \times R_{th}(\text{Per diode}) + P(\text{diode } 2) \times R_{th}(c)$$

## ELECTRICAL CHARACTERISTICS (Per diode)

### STATIC CHARACTERISTICS

Symbol	Test Conditions		Min.	Typ.	Max.	Unit
I <sub>R</sub> *	T <sub>j</sub> = 25°C	V <sub>R</sub> = V <sub>RRM</sub>			1	mA
	T <sub>j</sub> = 125°C				150	mA
V <sub>F</sub> **	T <sub>j</sub> = 125°C	I <sub>F</sub> = 160 A			0.90	V
	T <sub>j</sub> = 125°C	I <sub>F</sub> = 80 A			0.69	
	T <sub>j</sub> = 25°C	I <sub>F</sub> = 160 A			0.95	


Pulse test : \* t<sub>p</sub> = 5 ms, duty cycle < 2 %

\*\* t<sub>p</sub> = 380 μs, duty cycle < 2 %


To evaluate the conduction losses use the following equation :

$$P = 0.48 \times I_F(\text{AV}) + 0.00262 \times I_F^2(\text{RMS})$$


**Fig.1** : Average forward power dissipation versus average forward current. (Per diode)




**Fig.2** : Average current versus case temperature. (duty cycle : 0.5) (Per diode)




**Fig.3 :** Non repetitive surge peak forward current versus overload duration. (Maximum values) (Per diode)




**Fig.4 :** Relative variation of thermal transient impedance junction to case versus pulse duration.




**Fig.5 :** Reverse leakage current versus reverse voltage applied. (Typical values) (Per diode)



**Fig.6 :** Junction capacitance versus reverse voltage applied. (Typical values) (Per diode)




**Fig.7 :** Forward voltage drop versus forward current. (Maximum values) (Per diode)



# STPS16035T(V) / STPS16045T(V)

## PACKAGE MECHANICAL DATA ISOTOP



REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	11.80	12.20	0.465	0.480
B	8.90	9.10	0.350	0.358
C	1.95	2.05	0.077	0.081
D	0.75	0.85	0.029	0.034
E	12.60	12.80	0.496	0.504
F	25.10	25.50	0.988	1.004
G	31.50	31.70	1.240	1.248
H	4.00		0.157	
I	4.10	4.30	0.161	0.169
J	4.10	4.30	0.161	0.169
K	14.90	15.10	0.586	0.595
L	30.10	30.30	1.185	1.193
M	37.80	38.20	1.488	1.504
O	7.80	8.20	0.307	0.323
P	5.50		0.216	

Cooling method : C

Marking : Type number

Weight : 28 g (without screw)

Electrical isolation: 2500V (RMS)

Capacitance: < 45 pF

Inductance : < 5 nH

Recommended torque value: 1.3 N.m (MAX 1.6N.m) for the 6 x M4 screws. (2 x M4 screws recommended for mounting the package on the heatsink and the 4 screws given with the screw version).

The screws supplied with the package are adapted for mounting on a board (or other types of terminals) with a thickness of 0.6 mm min and 2..2 max.

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

TURBOSWITCH, TRANSIL, TRISIL, SNUBBERLESS are Trademarks of SGS-THOMSON Microelectronics.

SGS-THOMSON Microelectronics GROUP OF COMPANIES  
Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -  
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A