


---

## ULTRA FAST RECOVERY RECTIFIER DIODES

---

- SUITED FOR SMPS
- LOW LOSSES
- LOW FORWARD AND REVERSE RECOVERY TIME
- HIGH SURGE CURRENT CAPABILITY
- HIGH AVALANCHE ENERGY CAPABILITY



### DESCRIPTION

Low cost single chip rectifier suited for switchmode power supply and high frequency DC to DC converters.

Packaged in F 126, this device is intended for use in low voltage, high frequency inverters, free wheeling and polarity protection applications.

### ABSOLUTE RATINGS (limiting values)

Symbol	Parameter		Value	Unit
I <sub>F(AV)</sub>	Average Forward Current	T <sub>I</sub> = 60°C δ = 0.5	3	A
I <sub>FSM</sub>	Surge Non Repetitive Forward Current	T <sub>p</sub> = 10 ms Sinusoidal	30	A
T <sub>stg</sub> T <sub>J</sub>	Storage and Junction Temperature Range		- 65 to + 150 - 65 to + 150	°C

Symbol	Parameter	STPR		Unit
		310	320	
V <sub>RRM</sub>	Repetitive Peak Reverse Voltage	100	200	V

### THERMAL RESISTANCE

Symbol	Parameter	Value	Unit
R <sub>th(j-l)*</sub>	Junction-leads	25	°C/W

\* ou infinite heatsink with L = 5mm lead length.

## STPR310/STPR320

### ELECTRICAL CHARACTERISTICS

#### STATIC CHARACTERISTICS

Symbol	Tests Conditions		Min.	Typ.	Max.	Unit
$I_R^*$	$T_j = 25^\circ\text{C}$	$V_R = V_{RRM}$			10	$\mu\text{A}$
	$T_j = 100^\circ\text{C}$				0.5	mA
$V_F^{**}$	$T_j = 125^\circ\text{C}$	$I_F = 3\text{ A}$			0.99	V
	$T_j = 125^\circ\text{C}$	$I_F = 6\text{ A}$			1.20	
	$T_j = 25^\circ\text{C}$	$I_F = 6\text{ A}$			1.25	

Pulse test : \*  $t_p = 5\text{ ms}$ , duty cycle < 2 %

\*\*  $t_p = 380\text{ }\mu\text{s}$ , duty cycle < 2%


#### RECOVERY CHARACTERISTICS

Symbol	Tests Conditions			Min.	Typ.	Max.	Unit
$t_{rr}$	$T_j = 25^\circ\text{C}$	$I_F = 0.5\text{ A}$	$I_R = 1\text{ A}$ $I_{rr} = 0.25\text{ A}$			30	ns
$t_{fr}$	$T_j = 25^\circ\text{C}$	$I_F = 1\text{ A}$	$t_r = 10\text{ ns}$ $V_{FR} = 1.1 \times V_F$		20		ns
$V_{FP}$	$T_j = 25^\circ\text{C}$	$I_F = 1\text{ A}$	$t_r = 10\text{ ns}$		3		V


To evaluate the conduction losses use the following equation :

$$P = 0.78 \times I_F(AV) + 0.070 I_F^2(RMS)$$


**Fig.1 :** Average forward power dissipation versus average forward current.




**Fig.2 :** Peak current versus form factor.




**Fig.3 :** Average current versus ambient temperature. (duty cycle : 0.5)  
 \* circuit board e (Cu) = 35μm, S (cu) = 12mm<sup>2</sup>  
 L(LEADS)= 20mm




**Fig.4 :** Non repetitive surge peak forward current versus overload duration. (Maximum values)



**Fig.5 :** Relative variation of thermal transient impedance junction to case versus pulse duration.




**Fig.6 :** Forward voltage drop versus forward current. (Maximum values)




# STPR310/STPR320


**Fig.7** : Junction capacitance versus reverse voltage applied. (Typical values)




**Fig.8** : Recovery charge versus  $dI_F/dt$ .



**Fig.9** : Peak reverse current versus  $dI_F/dt$ .




**Fig.10** : Dynamic parameters versus junction temperature.



PACKAGE MECHANICAL DATA

F126



REF.	DIMENSIONS				NOTES
	Millimeters		Inches		
	Min.	Max.	Min.	Max.	
A	6.05	6.35	0.238	0.250	1 - The lead diameter $\varnothing D$ is not controlled over zone E 2 - The minimum axial length within which the device may be placed with its leads bent at right angles is 0.59" (15 mm)
B	26		1.024		
$\varnothing C$	2.95	3.05	0.116	0.120	
$\varnothing D$	0.76	0.86	0.029	0.034	
E		1.27		0.050	

Cooling method : by convention (method A)

Marking : Clear, ring at cathode end

Weight : 0.4 g

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

TURBOSWITCH, TRANSIL, TRISIL, SNUBBERLESS are Trademarks of SGS-THOMSON Microelectronics.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A