



## SMALL SIGNAL PNP TRANSISTOR

Type	Marking
SO692	P39

- SILICON EPITAXIAL PLANAR PNP TRANSISTORS
- MINIATURE PLASTIC PACKAGE FOR APPLICATION IN SURFACE MOUNTING CIRCUITS
- HIGH VOLTAGE TRANSISTOR FOR VIDEO AMPLIFIER
- NPN COMPLEMENT IS SO642


**SOT-23**

### INTERNAL SCHEMATIC DIAGRAM



SC08810

### ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
$V_{CBO}$	Collector-Base Voltage ( $I_E = 0$ )	-300	V
$V_{CEO}$	Collector-Emitter Voltage ( $I_B = 0$ )	-300	V
$V_{EBO}$	Emitter-Base Voltage ( $I_C = 0$ )	-5	V
$I_C$	Collector Current	-0.1	A
$I_{CM}$	Collector Peak Current	-0.3	A
$P_{tot}$	Total Dissipation at $T_c = 25\text{ }^\circ\text{C}$	310	mW
$T_{stg}$	Storage Temperature	-65 to 150	$^\circ\text{C}$
$T_j$	Max. Operating Junction Temperature	150	$^\circ\text{C}$

**THERMAL DATA**

$R_{thj-amb}$ •	Thermal Resistance Junction-Ambient	Max	450	$^{\circ}C/W$
$R_{thj-SR}$ •	Thermal Resistance Junction-Substrate	Max	320	$^{\circ}C/W$

• Mounted on a ceramic substrate area = 15 x 15 x 0.7 mm


**ELECTRICAL CHARACTERISTICS** ( $T_{case} = 25^{\circ}C$  unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$I_{CBO}$	Collector Cut-off Current ( $I_E = 0$ )	$V_{CB} = -200 V$			-100	nA
$V_{(BR)CBO}^*$	Collector-Emitter Breakdown Voltage ( $I_E = 0$ )	$I_C = -100 \mu A$	-300			V
$V_{(BR)CEO}^*$	Collector-Emitter Breakdown Voltage ( $I_B = 0$ )	$I_C = -1 mA$	-300			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage ( $I_C = 0$ )	$I_E = -100 \mu A$	-5			V
$V_{CE(sat)}^*$	Collector-Emitter Saturation Voltage	$I_C = -20 mA$ $I_B = -2 mA$			-0.5	V
$V_{BE(sat)}^*$	Base-Emitter Saturation Voltage	$I_C = -20 mA$ $I_B = -2 mA$			-0.9	V
$h_{FE}^*$	DC Current Gain	$I_C = -1 mA$ $V_{CE} = -10 V$ $I_C = -10 mA$ $V_{CE} = -10 V$ $I_C = -30 mA$ $V_{CE} = -10 V$	25 40 25			
$f_T$	Transition Frequency	$I_C = -10 mA$ $V_{CE} = -20 V$ $f = 50 MHz$	50			MHz
$C_{CB}$	Collector Base Capacitance	$V_{CB} = -20 V$ $f = 1 MHz$			6	pF

\* Pulsed: Pulse duration = 300  $\mu s$ , duty cycle  $\leq 2\%$

## SOT-23 MECHANICAL DATA

DIM.	mm			mils		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	0.85		1.1	33.4		43.3
B	0.65		0.95	25.6		37.4
C	1.20		1.4	47.2		55.1
D	2.80		3	110.2		118
E	0.95		1.05	37.4		41.3
F	1.9		2.05	74.8		80.7
G	2.1		2.5	82.6		98.4
H	0.38		0.48	14.9		18.8
L	0.3		0.6	11.8		23.6
M	0		0.1	0		3.9
N	0.3		0.65	11.8		25.6
O	0.09		0.17	3.5		6.7



Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1995 SGS-THOMSON Microelectronics - Printed in Italy - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A