
**M28F101 1 Megabit (128K x 8)
CMOS T5-U20 FLASH MEMORY in PLCC32**

INTRODUCTION

The M28F101 is a 1 Megabit FLASH Memory organised as 128K x 8 bits. It is manufactured in the SGS-THOMSON Advanced CMOS 0.8 micron T5-U20 (-20% upgrade) process which has been especially developed for flash memory products. The memory features a fast 100ns access time, very low standby power consumption of 100µA at 5V, an endurance of 10,000 Erase/Program cycles and an integrated Erase/Program Stop timer.

SGS-THOMSON recognises that the quality of a product must be built-in during the design, material procurement, manufacturing and testing. Also that the reliability must be demonstrated before the product is released to full mass production. The qualification of new products and the certification of new processes is a rigorous task undertaken by Quality and Reliability professionals, to ensure stable products and processes capable of fully meeting customer requirements.

A key step of this activity is the Design Review where we assure that,

- adequate and realistic product specifications have been developed;
- design and layout rules, as documented in the Design Rules Manual, have been respected;
- critical performance parameters and process variables have been identified;
- previously untested design techniques or manufacturing processes are recognised;
- manufacturability concerns are identified;
- comprehensive and efficient qualification programs are defined.

Product Qualification is made on all new products and on new packages. Qualification is also remade on existing products when there are major changes to the design or manufacturing. The tests performed are tailored to the parameters affected by the major change or to the combinations of new die or new package to be evaluated.

The results of the tests for the M28F101 FLASH MEMORY are on the attached pages of this qualification report.

Director of
Memory Products Group
Quality Control & Reliability



Attilio PANCHIERI

**Table 1. Product Qualification, Plastic Packages - Die Related Tests
M28F101, PLCC32, CMOS T5-U20**

Subgroup	Test Procedure	MIL-STD-883 Procedure	Test Conditions	Results			Note
				Lots	Samp.	Fail	
1	Operating Life Test	1005	140°C, V _{CC} = 6V, - 168 hrs - 500 hrs - 1000 hrs		302 302 302	0 0 0	1, 5
2	Retention Bake	1008	250°C, - 168 hrs - 500 hrs		123 123	0 0	2
3	Retention Bake	1008	150°C, - 168 hrs - 500 hrs - 1000 hrs		180 180 180	0 0 0	1
4	Retention Bake (after 10k cycles)	1008	250°C, - 168 hrs		233	0	
5	Write/Erase Cycling		10,000 cycles 20,000 cycles		234 173	1 0	1, 3, 6
6	Temperature, Humidity, Bias	CECC 90,000	85°C, RH = 85%, V _{CC} = 5V, - 168 hrs - 500 hrs - 1000 hrs		180 180 180	0 0 0	1, 5
7	Temperature Cycling	1010	-65 to 150°C, - 500 cycles - 1000 cycles		180 180	0 0	1, 5
8	Thermal Shock	1011	-55 to 125°C, - 100 cycles - 500 cycles		75 75	0 0	1, 5
9	Pressure Pot		121°C, 2 Atm, - 96 hrs - 168 hrs		180 180	0 0	5
10	Pressure Pot		121°C, 2 Atm, - 96 hrs - 168 hrs		180 180	0 0	
11	HAST	CECC 90,000	130°C, RH = 85%, 5,5V - 48 hrs - 96hrs		75 75	0 0	5
12	Electrostatic Discharge	3015	1500Ω, 100pF, 1750V		36	0	
13	Electrostatic Discharge	EIAJ IC-121	0Ω, 200pF, 200V (min)				4
14	Latch-up	JEDEC STD-17	Current Injection 200mA (min), Overvoltage 14V/500mA (min)		45	0	

- Notes:** 1. Sample is coming from 3 different lots minimum.
 2. Test performed on FDIP32W package.
 3. Data collection in progress.
 4. Test not performed.
 5. Samples previously submitted to preconditioning flow for Surface Mounting devices according to SGS-THOMSON specification.
 6. Single bit erasing failure.

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES
Australia - Brazil - Canada - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.