

SENSITIVE GATE SCRs IN PLASTIC PACKAGE

T _j max = 125 °C (except TS820-xxxB and TS420-xxxB: 110 °C)													
Type	I _{T(RMS)} (A)	T _a T _I T _c T _{tab} (°C)	V _{RRM} V _{DRM} (V)	I _{TSM} (A)	I _{RRM} @ I _{DRM} @ T _j max max (mA)	T _j = 25 °C					dv/dt 67% V _{DRM} T _j max min Typ* (V/μs)	di/dt max (A/μs)	Package
						I _{GT} min (μA)	I _{GT} max (μA)	I _H max (mA)	V _{TM} @ I _{TM} max (V)	I _{TM} (A)			
P0102xL P0109xL	0,2	25 (1)	100 → 400 (a)	7	0,1	–	0,2 1	5	1,3	0,4	25	30	SOT23
P0102xN	0,8	70 (1)	100 → 400 (a)	7	0,1	–	0,2	5	1,95	1,6	25	30	SOT223
X0202xN	1,4	90 (4)	200 → 800 (b)	22,5	0,2	–	0,2	5	1,5	2,8	15*	30	SOT223
TS420-400B TS420-600B	4	90 (3)	400 → 600	30	0,2	–	0,2	5	1,8	8	10*	50	DKPAK
TS820-400B TS820-600B	8	85 (3)	400 → 600	70	1	–	0,2	5	1,7	16	5*	50	DKPAK
TN805-400B TN805-600B TN805-700B TN805-800B	8	105 (3)	400 600 700 800	70	2	–	5	25	1,6	16	50	100	DKPAK
TN815-400B TN815-600B TN815-700B TN815-800B	8	105 (3)	400 600 700 800	70	2	–	15	50	1,6	16	100	100	DKPAK
TN1215-400G TN1215-600G TN1215-800G	12	90 (3)	200 400 600	120	3	–	15	30	1,6	24	200	100	D ² PAK
TN1625-400G TN1625-600G TN1625-800G	16	95 (3)	200 400 600	160	2	–	25	40	1,6	36	500	100	D ² PAK
TN2540-400G TN2540-600G TN2540-800G	25	95 (3)	200 400 600	250	4	–	40	50	1,6	50	500	100	D ² PAK
TN4050-400G TN4050-600G TN4050-800G	40	85 (3)	200 400 600	400	4	–	50	75	1,8	80	1,000	100	D ² PAK

- (1) A = 100V B = 200V C = 300V D = 400V
- (2) B = 200V D = 400V M = 600V N = 800V
- (3) E = 500V M = 600V S = 700V N = 800V
- (4) D = 400V M = 600V S = 700V N = 800V

▲ New Products.

SENSITIVE GATE SCRs IN PLASTIC PACKAGE (cont'd)

T _j max = 125 °C (except TS820-xxxB and TS420-xxxB: 110 °C)													
Type	I _{T(RMS)} (A)	T _a T _I (1) T _c (2) T _{tab} (3) (°C) (4)	V _R RM V _D RM (V)	I _{TSM} (A)	I _{RRM} @ I _{DRM} @ T _j max max (mA)	T _j = 25°C					dv/dt 67% V _{DRM} T _j max min Typ* (V/μs)	di/dt max (A/μs)	Package
						I _{GT} min (μA)	I _{GT} max (μA)	I _H max (mA)	V _{TM} @ I _{TM} max (V)	(A)			
P0102xL P0109xL	0,2	25 (1)	100 → 400 (a)	7	0,1	–	200 1	5	1,3	0,4	25 25	30	SOT23
P0102xN P0109xN P0111xN	0,8	70 (1)	100 → 400 (a)	7	0,1	–	200 1 4	5	1,95	1,6	25 25 50	30	SOT223
P0102xA P0109xA P0111xA P0115xA	0,8	55 (2)	100 → 400 (a)	7	0,1	–	200 1 4 15	5	1,93	1,6	25 25 50 100	30	TO92
X0202xA X0203xA X0205xA	1,25	60 (2)	200 → 800 (b)	22,5	0,2	–	200 20 20	5	1,45	2,5	15* 20* 15*	30	TO92
X0202xN	1,4	90 (4)	200 → 800 (b)	22,5	0,2	–	200	5	1,5	2,8	15*	30	SOT223
X0402xE X0403xE X0405xE	4	90 (3)	200 → 800 (b)	30	0,2	–	200 20 20	5	1,8	8	15* 20* 15*	50	TO202-1
X0402xF X0403xF X0405xF	4	90 (3)	200 → 800 (b)	30	0,2	–	200 20 20	5	1,8	8	15* 20* 15*	50	TO202-2
▲ TS420-400B ▲ TS420-600B	4	90 (3)	400 600	30	0,2	–	200	5	1,8	8	10*	50	DPAK
S0402xH	4	110 (3)	200 → 800 (b)	50	0,5	–	200	10	1,6	8	10*	100	TO220AB
S0602xH	6	100 (3)	200 → 800 (b)	60	0,5	–	200	10	1,6	12	10*	100	TO220AB
S0802xH	8	95 (3)	200 → 800 (b)	70	0,5	–	200	10	1,6	16	10*	100	TO220AB
▲ TS820-400B ▲ TS820-600B	8	85 (3)	400 600	70	1	–	200	5	1,7	16	5*	50	DPAK

(1) A = 100V B = 200V C = 300V D = 400V
 (2) B = 200V D = 400V M = 600V N = 800V
 (3) E = 500V M = 600V S = 700V N = 800V
 (4) D = 400V M = 600V S = 700V N = 800V

▲ New Products.

STANDARD SCRs IN PLASTIC PACKAGE

Type	I _{T(AV)} (A)	V _{RRM} = V _{DRM} (V)	I _{TSM} (A)	I _R RM @ I _{DRM} @ T _j max max (mA)	T _j = 25°C					dv/dt 67% V _{DRM} T _j max min Typ* (V/μs)	di/dt max (A/μs)	Package
					I _{GT} min (mA)	I _{GT} max (mA)	I _H max (mA)	V _{TM} @ I _{TM} max (V)	I _{TM} (A)			
4 Arms/T_C = 115°C T_j = 125°C I²t = 18A²s												
TYN204 → 1004	2.5	200 → 1000	60	2	–	15	30	1.8	8	200	100	TO220AB
4 Arms/T_C = 110°C T_j = 125°C I²t = 12,5A²s												
S0406 • H S0410 • H S0417 • H	2.5	200 → 800 (2)	50	0.5	0.5 10 4	5 25 15	25 75 50	1.6	8	50* 200 100	100	TO220AB
6 Arms/T_C = 110°C T_j = 125°C I²t = 24,5A²s												
TYN056 → 1006	3.8	50 → 1000	70	2	–	15	30	1.6	12	200	50	TO220AB
6 Arms/T_C = 100°C T_j = 125°C I²t = 18A²s												
S0606 • H S0610 • H S0617 • H	3.8	200 → 800 (2)	60	0.5	0.5 10 4	5 25 15	25 75 50	1.6	12	50* 200 100	100	TO220AB
8 Arms/T_C = 105°C T_j = 125°C I²t = 32A²s												
TYN058 → 1008(*)	5	50 → 1000	80	2	Without suffix 15 Suffix G 25		30 45	1.6	16	200 500	50	TO220AB
8 Arms/T_C = 95°C T_j = 125°C I²t = 32A²s												
S0806 • H S0810 • H S0817 • H	5.1	200 → 800 (2)	80	0.5	0.5 10 4	5 25 15	25 75 50	1.6	16	50* 200 100	100	TO220AB
10 Arms/T_C = 100°C T_j = 125°C I²t = 50A²s												
TYN0510 → 1010	6.4	50 → 1000	100	2	–	15	30	1.6	20	200	50	TO220AB
10 Arms/T_C = 95°C T_j = 125°C I²t = 50A²s												
S1006 • H S1010 • H S1017 • H	6.4	200 → 800 (2)	100	1.5	0.5 10 4	5 25 15	15 50 30	1.6	20	10* 200 100	100	TO220AB

(*) Insulating version available (TXN)

(2) B = 200V D = 400V M = 600V N = 800V ex: S0610MH

SCRs

STANDARD SCRs IN PLASTIC PACKAGE (cont'd)

Type	I _{T(AV)} (A)	V _{RRM} = V _{VDRM} (V)	I _{TSM} (A)	I _{RRM} @ I _{DRM} @ T _j max max (mA)	T _j = 25°C					dv/dt 67% V _{VDRM} T _j max min Typ* (V/μs)	di/dt max (A/μs)	Package
					I _{GT} min (mA)	I _{GT} max (mA)	I _H max (mA)	V _{TM} @ I _{TM} max (V)	I _{TM} (A)			
12 Arms/T_C = 90°C T_j = 125°C I²t = 72A²s												
TYN0512 → 1012(*)	8	50 → 1000	120	2	–	15	30	1.6	24	200	100	TO220AB
12 Arms/T_C = 90°C T_j = 125°C I²t = 72A²s												
S1206 • H S1210 • H S1217 • H	7.6	200 → 800 (2)	120	1.5	0.5 10 4	5 25 15	15 50 30	1.6	24	10* 200 100	100	TO220AB
16 Arms/T_C = 95°C T_j = 125°C I²t = 128A²s												
TYN0516 → 816	10	50 → 800	160	2	–	25	40	1.6	32	500	100	TO220AB
16 Arms/T_C = 90°C T_j = 125°C I²t = 128A²s												
S1610 • H S1616 • H	10	200 → 800 (2)	160	2	10 25	25 50	50 100	1.6	32	400 500	100	TO220AB
20 Arms/T_C = 105°C T_j = 125°C I²t = 310A²s												
TYN682 → 692	13	50 → 800	250	2	–	25	40	1.4	50	500	100	TO220AB
25 Arms/T_C = 95°C T_j = 125°C I²t = 310A²s												
TYN225 → 1025	16	200 → 1000	250	4	–	40	50	1.6	50	500	100	TO220AB
25 Arms/T_C = 85°C T_j = 125°C I²t = 310A²s												
S2514 • H S2516 • H	16	200 → 800 (2)	250	2.5	30 20	75 50	115 100	1.6	50	750 500	100	TO220AB
30 Arms/T_C = 90°C T_j = 125°C I²t = 512A²s												
S3014 • H S3016 • H	19	800 → 1200 (4)	320	5	30 20	75 50	115 100	1.6	60	500 500	100	TO220AB
40 Arms/T_C = 85°C T_j = 125°C I²t = 722A²s												
S4014 • H S4016 • H	25	200 → 800 (2)	380	3	30 20	75 50	115 100	1.6	80	750 500	100	TO220AB

(*) Insulating version available (TXN)

(2) B = 200V D = 400V M = 600V N = 800V ex: S1610MH

(4) N = 800V P = 1000V V = 1200V ex: S3016PH

STANDARD GATE SCRs IN PLASTIC PACKAGE

Type (See Note)	Fax Code	I _{T(AV)} (A)	V _{R_{RRM}} = V _{D_{DRM}} (V)	I _{TSM} (A)	I _{RRM} @ V _{RRM} I _{DRM} @ V _{D_{DRM}} T _j max max (mA)	T _j = 25°C				dv/dt @ 67% V _{D_{DRM}} T _j max min (V/μs)	di/dt max (A/μs)	Package
						V _{GT} max (V)	I _{GT} max (mA)	I _H max (mA)	V _{TM} @ I _{TM} max (V) (A)			

30 Arms/T_{case} = 80°C T_j = 125°C I²t = 800 A²s

BTW 68-200 → 1200		19	200 → 1200	400	6	1.5	50	75	2.1	60	500 (1) 250 (2)	100	TOP3
-------------------	--	----	------------	-----	---	-----	----	----	-----	----	--------------------	-----	------

30 Arms/T_{case} = 75°C T_j = 125°C I²t = 800 A²s

BTW 66-200 → 1200		20	200 → 1200	400	6	1.5	50	75	2.2	60	500 (1) 250 (2)	100	RD91
-------------------	--	----	------------	-----	---	-----	----	----	-----	----	--------------------	-----	------

35 Arms/T_{case} = 85°C T_j = 125°C I²t = 800 A²s

BTW 68-600 N → 1200 N		22	600 → 1200	400	6	1.5	50	75	2.2	70	500 (1) 250 (2)	100	TOP3
-----------------------	--	----	------------	-----	---	-----	----	----	-----	----	--------------------	-----	------

40 Arms/T_{case} = 75°C T_j = 125°C I²t = 1250 A²s

BTW 67-200 → 1200		25	200 → 1200	500	6	1.5	80	150	2	80	500 (1) 250 (2)	100	RD91
-------------------	--	----	------------	-----	---	-----	----	-----	---	----	--------------------	-----	------

50 Arms/T_{case} = 70°C T_j = 125°C I²t = 1250 A²s

BTW 69-200 → 1200		32	200 → 1200	500	6	1.5	80	150	1.9	100	500 (1) 250 (2)	100	TOP3
-------------------	--	----	------------	-----	---	-----	----	-----	-----	-----	--------------------	-----	------

55 Arms/T_{case} = 75°C T_j = 125°C I²t = 1250 A²s

BTW 69-600 N → 1200 N		35	600 → 1200	500	6	1.5	80	150	2	110	500 (1) 250 (2)	100	TOP3
-----------------------	--	----	------------	-----	---	-----	----	-----	---	-----	--------------------	-----	------

**Note: BTW insulated (insulating voltage = 2500 V_{RMS}).
BTW + suffix N uninsulated.**

- (1) V_{D_{DRM}} ≤ 800 V.
- (2) V_{D_{DRM}} ≥ 1000 V.

SENSITIVE AND FAST SCR

Type	I _{T(AV)} (A)	V _{RRM} = V _{DORM} (V)	I _{TSM} (A)	I _{RRM} @ V _{RRM} I _{DORM} @ V _{DORM} T _j max max (mA)	T _j = 25°C					dv/dt @ 67% V _{DORM} T _j max min (V/μs)	di/dt T _j =25°C max (A/μs)	t _q max (ns)	Package
					I _{GT} min (mA)	I _{GT} max (mA)	I _H max typ* (mA)	V _{TM} @ I _{TM} max (V)	I _{TM} (A)				

3.5 Arms/T_{case} = 85°C T_j = 125°C I²t = 2 A²s

▲ TR03- 400T	2	400	20	0.2	–	1.5	5*	2.2	10	20	100	15	TO220AB
--------------	---	-----	----	-----	---	-----	----	-----	----	----	-----	----	---------

8 Arms/T_C = 95°C T_j = 125°C I²t = 32 A²s

F0810 • H	5.1	200 → 800 (2)	80	1.5	10	25	75	2	16	300	100	20	TO220AB
-----------	-----	------------------	----	-----	----	----	----	---	----	-----	-----	----	---------

SCRs FOR OVERVOLTAGE PROTECTION IN PLASTIC PACKAGE

Type	I _{T(AV)} (A)	V _{RRM} = V _{DORM} (V)	I _{TSM} (A)	I _{RRM} @ V _{RRM} I _{DORM} @ V _{DORM} T _j max max (mA)	T _j = 25°C					dv/dt @ 67% V _{DORM} T _j max min (V/μs)	di/dt max (A/μs)	Package
					V _{GT} max (V)	I _{GT} max (mA)	I _H max (mA)	V _{TM} @ I _{TM} max (V)	I _{TM} (A)			

12 Arms/T_{case} = 110°C T_j = 125°C I²t = 450 A²s

TYP 212 → 2012	8	25 → 200	300	2	1.5	30	50	1.5	50	200	100	TO220AB
----------------	---	----------	-----	---	-----	----	----	-----	----	-----	-----	---------

▲ New product.

(2) B = 200V D = 400V M = 600V N = 800V ex: F0810MH

MODULE

Type	I _{T(AV)} (A)	V _{RRM} = V _{VDRM} (V)	I _{TSM} (A)	I _{RRM} @ V _{RRM} I _{DRM} @ V _{VDRM} T _j max max (mA)	T _j = 25°C					dv/dt @ 67% V _{VDRM} min (V/μs)	di/dt max (A/μs)	Package
					V _{GT} max (V)	I _{GT} max (mA)	I _H max (mA)	V _{TM} max (V)	I _{TM} (A)			

50 Arms/T_{case} = 85°C T_j = 125°C I²t = 800 A²s

MDS35-800 → 1200	25	800 → 1200	400	10	1.5	50	80	1.7	80	500	100	ISOTOP® (Screw version)
------------------	----	------------	-----	----	-----	----	----	-----	----	-----	-----	----------------------------

70 Arms/T_{case} = 85°C T_j = 125°C I²t = 1800 A²s

MDS50-800 → 1200	35	800 → 1200	600	10	1.5	50	80	1.75	110	500	100	ISOTOP® (Screw version)
------------------	----	------------	-----	----	-----	----	----	------	-----	-----	-----	----------------------------

55 Arms/T_{case} = 80°C T_j = 125°C I²t = 800 A²s

▲ MSS40-800 → 1400		800 → 1400	400	10	1.5	50	80	1.7	80	500	100	ISOTOP® (Screw version)
--------------------	--	------------	-----	----	-----	----	----	-----	----	-----	-----	----------------------------

70 Arms/T_{case} = 80°C T_j = 125°C I²t = 1800 A²s

▲ MSS50-800 → 1400		800 → 1400	600	10	1.5	50	80	1.7	100	500	100	ISOTOP® (Screw version)
--------------------	--	------------	-----	----	-----	----	----	-----	-----	-----	-----	----------------------------

▲ : New product 1400 V

	MSS	MDS
Structure		
Pin connection		

APPLICATION SPECIFIC DISCRETES - AUTOMOTIVE ASD™ : IGNITION CONTROL CIRCUIT

THYRISTOR PARAMETERS

Type	V _{DRM} (V)	I _{TSM} @ T _j = 25°C (A)	I _{GT} @ T _j = 25°C max (mA)	V _{TM} max (V)	@ I _{TM} (A)	I _{DRM} max @ T _j max (mA)	Package
ICC01-400B5	400	5	1	1,9	4	1	SO16
ICC03-400B2	400	5	1	1,9	4	1	DIL8

DIODE PARAMETERS

Type	Diode	V _{RRM} T _j = 25°C (V)	I _{FSM} @ T _j = 25°C tp = 10 ms (A)	I _r @ V _r = V _{rrm} max (mA)	V _F @ I _F @ T _j = 25 °C @ tp < 1 ms (V)	I _F (A)	Package
ICC01-400B5	D1	25	2	1	1,2	0,1	SO16
ICC03-400B2	D2	400	5	1	1,9	4	
ICC01-400B5	D3	400	5	1	1,9	4	DIL8
	D4	25	2	1	1,2	0,1	

APPLICATION SPECIFIC DISCRETES - INDUSTRIAL ASD™ : FIRE LIGHTER CIRCUIT

THYRISTORS AND ZENERS PARAMETERS

Type	$I_{RM} @ V_{RM} = 200V$	$V_{BO} max$	$I_{BO} max$	$I_{BO1} max$ pin 3 open	$I_{BO2} min$ pin 1&3 in C/C	$V_T @ I_T max$ @ $T_j max$		Package
	(μA)	(A)	(mA)	(mA)	(mA)	(V)	(A)	
FLC01-200D	100	250	1	-	-	1,9	4	SOT82
FLC02-200D	100	250	-	0,5	40	1,9	4	SOT82

DIODE PARAMETERS

Type	$V_F @ I_F$ @ $T_j max$ @ $t_p < 1 ms$ max	
	(V)	(A)
FLC01-200D	1,7	2
FLC02-200D	1,7	2

APPLICATION SPECIFIC DISCRETES - LIGHTING ASD™ : SPECIAL SCRs FOR STARTLIGHT

T _j max = 125 °C													
Type	I _{T(RMS)} (A)	T _a T _I T _c T _{tab} (°C)	V _{R(RM)} V _{DRM} (V)	I _{TSM} (A)	I _{RRM} @ I _{DRM} @ T _j max max (mA)	T _j = 25°C					dv/dt 67% V _{DRM} T _j max min Typ* (V/μs)	di/dt max (A/μs)	Package
						I _{GT} min (μA)	I _{GT} max (μA)	I _H max (mA)	V _{TM} @ I _{TM} max (V)	I _{TM} (A)			
P0130AL	0,2	25	100	7	0,1	0,1	1	5	1,3	0,4	25	30	SOT23
P0130AA	0,8	55	100	7	0,1	0,1	1	5	1,25	0,5	25	30	TO92

T _j max = 110 °C													
Type	I _{T(RMS)} (A)	T _a T _I T _c T _{tab} (°C)	V _{BR} min (V)	V _{BR} max (V)	I _{TSM} (A)	T _j = 25°C					dv/dt 67% V _{DRM} T _j max min Typ* (V/μs)	di/dt max (A/μs)	Package
						I _{GT} min (μA)	I _{GT} max (μA)	I _H max (mA)	V _{TM} @ I _{TM} max (V)	I _{TM} (A)			
TN22-1500	2	95	1200	1500	20	-	1,5	175	3,1	2	500	50	SOT82 SOT194
TN22-1600			1000	1600	20	-	1,5	175	3,1	2	500	50	SOT82 SOT194