





MECHANICAL DATA

Dimensions in mm(inches)





NPN SILICON POWER TRANSISTOR

FEATURES

- HIGH CURRENT
- FAST SWITCHING
- HIGH RELIABILITY

APPLICATIONS

- POWER SWITCHING CIRCUITS
- MOTOR CONTROL

TO-204AE (TO-3)

PIN 2 — Emitter Case is Collector. PIN 1 — Base

ABSOLUTE MAXIMUM RATINGS ($T_{case} = 25$ °C unless otherwise stated)

$R_{\theta JC}$	Thermal Resistance Junction to Case	1.0°C/W
T_{j}	Junction Temperature	200°C
T_{stg} ,	Storage Temperature	−65 to 200°C
P_{tot}	Total Power Dissipation at T _{case} ≤ 25°C	175W
I_{B}	Base Current	10A
I_{CM}	Peak Collector Current (t _p = 10 ms)	30A
I_{C}	Collector Current	15A
V_{EBO}	Emitter – Base Voltage (I _C = 0)	7V
V_{CEO}	Collector – Emitter Voltage $(I_B = 0)$	450V
V _{CES}	Collector – Emitter Voltage $(V_{BE} = 0V)$	900V

Semelab PIc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.

E-mail: sales@semelab.co.uk Website: http://www.semelab.co.uk

Semelab plc. Telephone +44(0)1455 556565. Fax +44(0)1455 552612.





ELECTRICAL CHARACTERISTICS (T_{case} = 25°C unless otherwise stated)

	Parameter	Test Conditions		Min.	Тур.	Max.	Unit
V _{CEO(BR)*}	Collector - Emitter Breakdown	I _C = 100mA		450			V
	Voltage	I IC = 100IIIA		450			v
I _{CES}	Collector Cut-off Current	V _{CE} = 900V	$V_{BE} = 0V$			500	μΑ
			T _C = 125°C			3	mA
I _{EBO}	Emitter Cut-off Current	I _C = 0	V _{EB} = 7V			1.0	mA
V _{CE(sat)*}	Collector – Emitter	I _C = 10A	I _B = 2A			1.5	V
	Saturation Voltage	I _C = 7A	I _B = 1.0A			1.5	
V _{BE(sat)*}	Base – Emitter	I _C = 10A	$I_B = 2A$			1.8	V
	Saturation Voltage	I _C = 7A	I _B = 1.0A			1.4	
t _{on}	Turn-On Time	I _C = 10A	I _{B1} =2A		0.75	μs	
		V _{CC} = 250V			0.75		
t _s	Storage Time	I _C = 10A	I _{B1} =2A			3	
t _f	Fall Time	V _{CC} = 250V	$I_{B2} = -2A$			0.8	μs

(*) Pulse test: $~t_p \leq 300 \mu s$, $\delta \leq 1.5\%$

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.

Semelab plc. Telephone +44(0)1455 556565. Fax +44(0)1455 552612. Document Number 6321 E-mail: sales@semelab.co.uk Website: http://www.semelab.co.uk Issue 1