


MECHANICAL DATA

Dimensions in mm(inches)



**LCC1 PACKAGE
(SOT23 Compatible)**

Underside View

Pad 1 – Anode Pad 2 – N/C Pad 3 – Cathode

**VOLTAGE REGULATOR
DIODE IN A
CERAMIC SURFACE MOUNT
PACKAGE
FOR HI-REL APPLICATIONS**

FEATURES

- HERMETIC CERAMIC SURFACE MOUNT PACKAGE
- SCREENING OPTIONS AVAILABLE

ABSOLUTE MAXIMUM RATINGS

P_{TOT}	Power Dissipation	$T_{AMB} = 25^{\circ}C$	400mW
	Derate above 25°C		3.2mW/°C
T_{OP}	Maximum Operating Ambient Temperature		-65 to +150°C
T_{STG}	Storage Temperature Range		-65 to +175°C
$R_{\theta JA}$	Thermal Resistance Junction to Ambient		312°C/W

ELECTRICAL CHARACTERISTICS ($T_A = 25^{\circ}C$ unless otherwise stated)

Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_Z Zener Voltage	I_{PINCH} (mA) @ $V_S = 25.0V$	3.24	3.60	3.96	V
V_L Maximum Limiting Voltage	$I_L = 0.8 I_{PINCH(min)}$			2.50	
Z_S^* Minimum Dynamic Impedance	$V_S = 25.0V$	0.265			mΩ
Z_K^* Minimum Knee Impedance	$V_K = 6.0V$	0.020			

* Z_S is derived by superimposing a 90Hz RMS signal equal to 10% of V_S onto V_S .

Similarly, Z_K is derived by superimposing a 90Hz RMS signal equal to 10% of V_S onto V_K .

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.