

# **GL480/GL480Q GL483Q**

## ■ Features

1. Narrow beam angle ( $\Delta\theta$ : TYP. $\pm 13^\circ$ )
  2. Radiant flux ( $\Phi_e$ : MIN. 0.7mW at  $I_F=20mA$ )
  3. Compact, high reliability by chip coating  
**(GL480Q/GL483Q)**
  4. Long lead type (**GL483Q**)



## ■ Applications

1. Copiers
  2. Floppy disk drives
  3. Optoelectronic switches

# Infrared Emitting Diode

#### **■ Outline Dimensions**

(Unit : mm)



#### Absolute Maximum Ratings (Ta = 25°C)

Parameter	Symbol	Rating	Unit
Power dissipation	P	75	mW
Forward current	I <sub>F</sub>	50	mA
* <sup>1</sup> Peak forward current	I <sub>FM</sub>	1	A
Reverse voltage	V <sub>R</sub>	6	V
Operating temperature	T <sub>opr</sub>	-25 to +85	°C
Storage temperature	T <sub>stg</sub>	-40 to +85	°C
* <sup>2</sup> Soldering temperature	T <sub>sol</sub>	260	°C

\*1 Pulse width  $\leq$  100  $\mu$ s. Duty ratio = 0.01.

\*1 Pulse width  $\leq$  100  $\mu$ s, Duty ratio= 0.01  
 \*2 For 3 seconds at the position of 14mm from the bottom face of resin package


"In the absence of confirmation by device specification sheets, SHARP takes no responsibility for any defects that occur in equipment using any of SHARP's devices, shown in catalogs, data books, etc. Contact SHARP in order to obtain the latest version of the device specification sheets before using any SHARP's device."

## ■ Electro-optical Characteristics


(Ta= 25°C )

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Forward voltage	V <sub>F</sub>	I <sub>F</sub> =20mA		1.2	1.4	V
Peak forward voltage	V <sub>FM</sub>	I <sub>FM</sub> = 0.5A		3.0	4.0	V
Reverse current	I <sub>R</sub>	V <sub>R</sub> = 3V	—	10	μA	
Terminal capacitance	C <sub>t</sub>	V <sub>R</sub> =0, f=1MHz	·	50	—	pF
Response frequency	f <sub>c</sub>		—	300	—	kHz
Radiant flux	Φe	I <sub>F</sub> = 20mA	0.7	—	3.0	mW
Peak emission wavelength	λ <sub>p</sub>	I <sub>F</sub> =5mA		950	—	nm
Half intensity wavelength	Δ λ	I <sub>F</sub> =5mA	—	45	—	nm
Half intensity angle	Δ θ		—	±13	—	


**Fig. 1 Forward Current vs. Ambient Temperature**




**Fig. 2 Peak Forward Current vs. Duty Ratio**










**Fig. 3 Spectral Distribution**



**Fig. 4 Peak Emission Wavelength vs. Ambient Temperature**



**Fig. 5 Forward Current vs. Forward Voltage****Fig. 7 Radiant Flux vs. Forward Current****Fig. 9 Relative Collector Current vs. Distance  
(Detector : PT480)****Fig. 6 Relative Radiant Flux vs.  
Ambient Temperature****Fig. 8 Relative Radiant Intensity vs.  
Distance****Fig. 10 Radiation Diagram (GL480Q/GL483Q)**

**Fig.11 Radiation Diagram (GL480) ( $T_a=25^\circ\text{C}$ )**

- Please refer to the chapter "Precautions for Use." (Page 78 to 93)