

LTO22MS

Features

- Compact (diameter 56 mm)
- Low noise
- S/N: -60 dB (according to measurement method Fig. 27-2)
- Wavelength: 780nm
- Single transverse mode

Applications

- CD players
- CD-ROMs
- Information processing equipment



Absolute Maximum Ratings

($T_c = 25^\circ\text{C}$)

Parameter	symbol	Ratings	Units
Optical power output	P_o	5	mW
Reverse voltage	V _R	2	V
Laser PIN			
Operating temperature * ¹	T _{opr}	-10 to +60	°C
Storage temperature * ¹	T _{stg}	-10 to +60	°C
		-40 to +85	

*¹ Case temperature

Electro-optical Characteristics **

($T_c = 25^\circ\text{C}$)

Parameter	symbol	Condition	Rating	Units
			MIN	MAX
Threshold current	I _{th}		45	mA
Operating current	I _{op}	$P_o = 3\text{mW}$	55	mA
Operating voltage	V _{op}	$P_o = 3\text{mW}$	175	V
Wavelength * ²	λ_p	$P_o = 3\text{mW}$	770	nm
Monitor current	I _m	$V_R = 15\text{V}$	012	0.85 mA
Radiation characteristics	Angle * ³	Parallel to junction	8.5	16 deg
		Perpendicular to junction	29	48 deg
Emission point accuracy	Ripple		±20	%
	Angle	$\Delta\phi_{//}$	±2	deg
Position		$\Delta\phi_{\perp}$	±3	deg
		A_x, A_y, A_z	±80	μm
Differential efficiency	η	$I_r(3\text{mW}) - I_r(1\text{mW})$	015	0.5 mW/mA

*¹ Initial value

*³ Angle at 50% peak intensity (full width at half-maximum)

*² Single transverse mode

Electrical Characteristics of Photodiode

($T_c = 25^\circ\text{C}$)

Parameter	Symbol	Condition	Ratings			Units
			MIN	TYP	MAX	
Sensitivity	S	$V_R = 15\text{V}$	013			mA/mW
Dark current	I _D	$V_R = 15\text{V}$	-	+ ^a	150	nA
Terminal capacitance	C _t	$V_R = 15\text{V}$	—	3.5	10	pF