

LT5005□ Series

16x 16 Dot Matrix LEDs

■ Model No.


- | | |
|-----------------------|-----------|
| LT5005D Red | GaAsP/GaP |
| LT5005S Sunset orange | GaAsP/GaP |
| LT5005E Yellow-green | GaP |

■ Features

1. Substrate type
2. 1.48" character height

■ Outline Dimensions

(Unit: mm)



SHARP

LT5005□

■ Absolute Maximum Ratings

(Ta = 25°C)

Parameter	Symbol	LT5005D	LT5005E	Unit
		LT5005S		
※1 Power dissipation	P	1800	1800	mW
Continuous forward current	Per dot	I _F	15	mA
※2 Peak forward current	Per dot	I _{FM}	80	mA
Derating factor	Per dot	D _C	—	mA/°C
	Pulse	—	1.45	mA/°C
Reverse voltage	Per dot	V _R	5	V
Operating temperature	T _{opr}	-20 to +60		
Storage temperature	T _{stg}	-20 to +80		
※3 Soldering temperature	T _{sol}	260 (within 5 seconds)		

※1 Per device

※2 Duty ratio=1/16, Pulse width=0.1ms, Lighting ratio=50%

When a unit is driven over half rate of lighting, a heat sink must be installed

※3 At the position of 3.6 mm from ⑧ level of outline dimensions

LT5005D(Red)






■ Electro-optical Characteristics ^{*4}

(Ta = 25°C)

Parameter	Symbol	Model No.	Conditions	MIN.	TYP.	MAX.	Unit
Forward voltage	V _F	LT5005D	I _F = 10mA	—	1.9	—	V
		LT5005D	I _{FM} = 50mA	—	2.2	2.7	
*5 Luminous intensity	I _V	LT5005D	I _F = 10mA	0.80	1.4	—	mcd
		LT5005D	I _{FM} = 50mA	—	635	—	
Peak emission wavelength	λ_p	LT5005D	I _{FM} = 50mA	—	35	—	nm
		LT5005D	I _{FM} = 50mA	—	—	—	
Spectrum radiation bandwidth	$\Delta\lambda$	LT5005D	I _{FM} = 50mA	—	35	—	nm
		LT5005D	I _{FM} = 50mA	—	—	—	
Reverse current	I _R	LT5005D	V _R = 4V	—	—	10	μ A
		LT5005D	V _R = 4V	—	—	—	
Response frequency	f _C	LT5005D	—	—	4	—	MHz
		LT5005D	—	—	—	—	

^{*4} Per dot^{*5} Tolerance: $\pm 30\%$

■ Characteristics Diagrams



LT5005S(Sunset orange)

■ Electro-optical Characteristics ^{*4}





(Ta = 25°C)

Parameter	Symbol	Model No.	Conditions	MIN.	TYP.	MAX.	Unit
Forward voltage	V _F	LT5005S	I _F = 10mA	—	1.9	—	V
		LT5005S	I _{FM} = 50mA	—	2.2	2.7	
*5 Luminous intensity	I _V	LT5005S	I _F = 10mA	0.50	1.4	—	mcd
		LT5005S	I _{FM} = 50mA	—	610	—	
Peak emission wavelength	λ_p	LT5005S	I _{FM} = 50mA	—	35	—	nm
		LT5005S	I _{FM} = 50mA	—	—	—	
Spectrum radiation bandwidth	$\Delta\lambda$	LT5005S	V _R = 4V	—	—	10	μA
		LT5005S	V _R = 4V	—	—	—	
Reverse current	I _R	LT5005S	—	—	—	4	MHz
		LT5005S	—	—	—	—	
Response frequency	f _c	LT5005S	—	—	—	—	MHz
		LT5005S	—	—	—	—	


*4 Per dot

*5 Tolerance: ±30%

■ Characteristics Diagrams

Forward Current vs.
Forward VoltageLuminous Intensity vs.
Forward CurrentPeak Forward Current
Derating CurveRelative Luminous Intensity vs.
Ambient Temperature

Spectrum Distribution



LT5005E(Yet low-green)

■ Electro-optical Characteristics^{※4}

(Ta=25°C)

Parameter	Symbol	Model No.	Conditions	MIN.	TYP.	MAX.	Unit
Forward voltage	V _F	LT5005E	I _F =10mA	—	2.0	—	
							V
		LT5005E	I _{FM} =50mA	—	2.4	3.0	
※5 Luminous intensity	I _V	LT5005E	I _F =10mA	1.0	1.7	—	mcd
Peak emission wavelength	λ _p	LT5005E	I _{FM} =50mA	—	565	—	nm
Spectrum radiation bandwidth	Δλ	LT5005E	I _{FM} =50mA	—	30	—	nm
Reverse current	I _R	LT5005E	V _R =4V			10	μA
Response frequency	f _c	LT5005E	—		4	—	MHz

※4 Per dot

※5 Tolerance: +30%

■ Characteristics Diagrams

